



PRODUCT DATA SHEET

3-36® Multi-Purpose Lubricant & Corrosion Inhibitor, 16 Fl Oz

No. 03007 | Item# 1003259 | Case# 1003258



Product Description	A versatile petroleum based compound that forms a clear, thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects, displaces moisture, and cleans.
Applications	Tubeing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air actuated tools, conveyors, frozen joints, locks, hoists, etc.
Unit Package Description	16 Ounce Spray Bottle
Brand	CRC
Generic Description 1	Multi-Purpose Precision Lubricant & Corrosion Inhibitor
Net Fill	16 Fl Oz
UPC Code	078254030074
Unit Dimensions	9.38H x 2.75W x 3.75D in
Units Per Case	12
Case Dimensions	10.44H x 8.5W x 11.25D in
Cases Per Pallet	95
Case Weight	13 lbs
I 2 of 5 Code	30078254030075
Appearance	Clear Blue-Green Liquid
Base Type	Petroleum
Flash point (F)	192°F
Flash point (C)	89°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.83
Plastic Safe	No
Film Type	Non-Drying
Film Thickness	0.025 to 0.075 Mil
Evaporation Rate	Slow

Last revised: 11/28/2017
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Dielectric Strength	38,800 Volts
Working Temp (F)	-50 to 250°F
Working Temp (C)	-45.6 to 121.1°C
Propellant	None
NSF Category Code	H2
NSF Number	017429
Federal Specification Number	V-V-P-216,O-W-1284
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with petroleum products, mineral spirits, or contact cleaner.

Last revised: 11/28/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET

3-36® Multi-Purpose Lubricant & Corrosion Inhibitor, 16 Fl Oz

No. 03007 | Item# 1003259 | Case# 1003258



Product Description	A versatile petroleum based compound that forms a clear, thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects, displaces moisture, and cleans.
Applications	Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air actuated tools, conveyors, frozen joints, locks, hoists, etc.
Unit Package Description	16 Ounce Spray Bottle
Brand	CRC
Generic Description 1	Multi-Purpose Precision Lubricant & Corrosion Inhibitor
Net Fill	16 Fl Oz
UPC Code	078254030074
Unit Dimensions	9.38H x 2.75W x 3.75D in
Units Per Case	12
Case Dimensions	10.44H x 8.5W x 11.25D in
Cases Per Pallet	95
Case Weight	13 lbs
1 2 of 5 Code	30078254030075
Appearance	Clear Blue-Green Liquid
Base Type	Petroleum
Flash point (F)	192°F
Flash point (C)	89°C
Flammability Class - CPSC	None
Spec Gravity Concentrate	0.83
Plastic Safe	No
Film Type	Non-Drying
Film Thickness	0.025 to 0.075 Mil
Evaporation Rate	Slow

Last revised: 11/28/2017
Page 1 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.



PRODUCT DATA SHEET



Dielectric Strength	38,800 Volts
Working Temp (F)	-50 to 250°F
Working Temp (C)	-45.6 to 121.1°C
Propellant	None
NSF Category Code	H2
NSF Number	017429
Federal Specification Number	V-V-P-216,O-W-1284
DOT Proper Shipping Name	Not Regulated
VOC % (Consumer Product def)	0
VOC g/L (Consumer Product def)	0
VOC lbs/gal (Consumer Prod def)	0
VOC Category	Multi-Purpose Lubricant
Removal (How To)	Remove with petroleum products, mineral spirits, or contact cleaner.

Last revised: 11/28/2017
Page 2 of 2



Customer Care: 800-556-5074
Technical Assistance: 800-521-3168
www.crcindustries.com

CRC Industries is a worldwide leader in the production of specialty chemicals for maintenance and repair professionals serving industrial, electrical, aviation, automotive and marine markets. CRC is ISO 9001:2008 certified and adheres to the strictest guidelines for quality in all facets of research, development and production.



CRC®, K&W®, Sta-Lube®, Marykate® and products denoted with ® and ™ are trademarks of CRC Industries, Inc.