

Deluxe Cord Grips

Aluminum Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables.

IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages X-61 through X-68.

Straight Male Thread



| NPT Thread Size Inches | Grip Diameter Range Inches (cm) | Form Size | Catalog Number |
|------------------------|---------------------------------|-----------|----------------|
| 3/8 | .250"-.312" (.63-.79) | F1 | 07401001 |
| | .312"-.375" (.79-.95) | | 07401002 |
| | .375"-.437" (.95-1.11) | | 07401003 |
| 1/2 | .187"-.250" (.47-.63) | F2 | 07401004 |
| | .250"-.375" (.63-.95) | | 07401006 |
| | .375"-.500" (.95-1.27) | | 07401008 |
| 1/2 | .500"-.625" (1.27-1.59) | F3 | 07401010 |
| | .625"-.750" (1.59-1.90) | | 074011247* |
| | .750"-.875" (1.90-2.22) | | 074011248* |
| 3/4 | .187"-.250" (.47-.63) | F2 | 07401011 |
| | .250"-.375" (.63-.95) | | 07401013 |
| | .375"-.500" (.95-1.27) | | 07401015 |
| 3/4 | .500"-.625" (1.27-1.59) | F3 | 07401017 |
| | .625"-.750" (1.59-1.90) | | 07401018 |
| | .750"-.875" (1.90-2.22) | | 074011249* |
| 1 | .375"-.500" (.95-1.27) | F4 | 074011195 |
| | .500"-.625" (1.27-1.59) | | 07401019 |
| | .625"-.750" (1.59-1.90) | | 07401021 |
| 1 | .750"-.875" (1.90-2.22) | F5 | 07401023 |
| | .875"-.1.000" (2.22-2.54) | | 07401025 |
| | 1.000"-.1.125" (2.54-2.86) | | 074011250* |
| 1 | 1.125"-.1.250" (2.86-3.17) | F5 | 074011028* |
| | 1.250"-.1.375" (3.17-3.49) | | 074011029* |
| | .750"-.875" (1.90-2.22) | | 074011251 |
| 1 1/4 | .875"-.1.000" (2.22-2.54) | F5 | 07401026 |
| | 1.000"-.1.125" (2.54-2.86) | | 07401027 |
| | 1.125"-.1.250" (2.86-3.17) | | 07401028 |
| 1 1/2 | 1.250"-.1.375" (3.17-3.49) | F5 | 074011178* |
| | .750"-.875" (1.90-2.22) | | 074011252 |
| | .875"-.1.000" (2.22-2.54) | | 07401029 |
| 1 1/2 | 1.000"-.1.125" (2.54-2.86) | F5 | 07401030 |
| | 1.125"-.1.250" (2.86-3.17) | | 07401031 |
| | 1.250"-.1.375" (3.17-3.49) | | 07401032 |
| 1 1/2 | 1.312"-.1.437" (3.33-3.65) | F6 | 074011253 |
| | 1.437"-.1.562" (3.65-3.97) | | 074011254* |
| | 1.562"-.1.687" (3.97-4.28) | | 074011255* |
| 1 1/2 | 1.687"-.1.812" (4.28-4.60) | F6 | 074011256* |
| | 1.750"-.1.875" (4.44-4.76) | | 074011257* |
| | 1.250"-.1.375" (3.17-3.49) | | 074011258 |
| 2 | 1.312"-.1.437" (3.33-3.65) | F6 | 074011259 |
| | 1.437"-.1.562" (3.65-3.97) | | 07401033 |
| | 1.562"-.1.687" (3.97-4.28) | | 07401034 |
| 2 | 1.687"-.1.812" (4.28-4.60) | F7 | 07401035 |
| | 1.750"-.1.875" (4.44-4.76) | | 074011260 |
| | 1.812"-.1.937" (4.60-4.92) | | 074011261 |
| 2 | 1.937"-.2.062" (4.92-5.24) | F7 | 074011262* |
| | 2.062"-.2.187" (5.24-5.55) | | 074011263* |
| | 2.187"-.2.312" (5.55-5.87) | | 074011264* |
| 2 1/2 | 2.312"-.2.437" (5.87-6.19) | F7 | 074011265* |
| | 1.688"-.1.812" (4.29-4.60) | | 074011030 |
| | 1.812"-.1.937" (4.60-4.92) | | 074011031 |
| 2 1/2 | 1.937"-.2.062" (4.92-5.24) | F7 | 074011032 |
| | 2.062"-.2.187" (5.24-5.55) | | 074011033 |
| | 2.187"-.2.312" (5.55-5.87) | | 074011034 |
| 3 | 2.312"-.2.437" (5.87-6.19) | F7 | 074011266* |
| | 1.937"-.2.062" (4.92-5.24) | | 074011036 |
| | 2.062"-.2.187" (5.24-5.55) | | 074011037 |
| 3 | 2.187"-.2.312" (5.55-5.87) | F8 | 074011038 |
| | 2.312"-.2.437" (5.87-6.19) | | 074011039 |
| | 2.437"-.2.625" (6.19-6.67) | | 074011186 |
| 3 | 2.625"-.2.812" (6.67-7.14) | F8 | 074011187 |
| | 2.812"-.3.000" (7.14-7.62) | | 074011188 |
| | 3.000"-.3.250" (7.62-8.25) | | 074011189* |

Note: Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).
*Cable jacket may have to be stripped to pass through connector body.

Dimensions in Inches (mm)

Deluxe Cord Grips

Aluminum Fittings, Stainless Steel Mesh, Liquidtight for Insulated Cables.

IMPORTANT:

Read all safety and technical data relating to this product.

Refer to pages X-61 through X-68.

Straight Male Thread



| NPT Thread Size Inches | Grip Diameter Range Inches (cm) | Form Size | Catalog Number |
|------------------------|---------------------------------|-----------|----------------|
| 3/8 | .250"- .312" (.63-.79) | F1 | 07401001 |
| | .312"- .375" (.79-.95) | | 07401002 |
| | .375"- .437" (.95-1.11) | | 07401003 |
| 1/2 | .187"- .250" (.47-.63) | F2 | 07401004 |
| | .250"- .375" (.63-.95) | | 07401006 |
| | .375"- .500" (.95-1.27) | | 07401008 |
| 1/2 | .500"- .625" (1.27-1.59) | F3 | 07401010 |
| | .625"- .750" (1.59-1.90) | | 074011247* |
| | .750"- .875" (1.90-2.22) | | 074011248* |
| 3/4 | .187"- .250" (.47-.63) | F2 | 07401011 |
| | .250"- .375" (.63-.95) | | 07401013 |
| | .375"- .500" (.95-1.27) | | 07401015 |
| 3/4 | .500"- .625" (1.27-1.59) | F3 | 07401017 |
| | .625"- .750" (1.59-1.90) | | 07401018 |
| | .750"- .875" (1.90-2.22) | | 074011249* |
| 1 | .375"- .500" (.95-1.27) | F4 | 074011195 |
| | .500"- .625" (1.27-1.59) | | 07401019 |
| | .625"- .750" (1.59-1.90) | | 07401021 |
| 1 | .750"- .875" (1.90-2.22) | F5 | 07401023 |
| | .875"- 1.000" (2.22-2.54) | | 07401025 |
| | 1.000"- 1.125" (2.54-2.86) | | 074011250* |
| 1 | 1.125"- 1.250" (2.86-3.17) | F5 | 074011028* |
| | 1.250"- 1.375" (3.17-3.49) | | 074011029* |
| | .750"- .875" (1.90-2.22) | | 074011251 |
| 1 1/4 | .875"- 1.000" (2.22-2.54) | F5 | 07401026 |
| | 1.000"- 1.125" (2.54-2.86) | | 07401027 |
| | 1.125"- 1.250" (2.86-3.17) | | 07401028 |
| 1 1/2 | 1.250"- 1.375" (3.17-3.49) | F5 | 074011178* |
| | .750"- .875" (1.90-2.22) | | 074011252 |
| | .875"- 1.000" (2.22-2.54) | | 07401029 |
| 1 1/2 | 1.000"- 1.125" (2.54-2.86) | F5 | 07401030 |
| | 1.125"- 1.250" (2.86-3.17) | | 07401031 |
| | 1.250"- 1.375" (3.17-3.49) | | 07401032 |
| 1 1/2 | 1.312"- 1.437" (3.33-3.65) | F6 | 074011253 |
| | 1.437"- 1.562" (3.65-3.97) | | 074011254* |
| | 1.562"- 1.687" (3.97-4.28) | | 074011255* |
| 1 1/2 | 1.687"- 1.812" (4.28-4.60) | F6 | 074011256* |
| | 1.750"- 1.875" (4.44-4.76) | | 074011257* |
| | 1.250"- 1.375" (3.17-3.49) | | 074011258 |
| 2 | 1.312"- 1.437" (3.33-3.65) | F6 | 074011259 |
| | 1.437"- 1.562" (3.65-3.97) | | 07401033 |
| | 1.562"- 1.687" (3.97-4.28) | | 07401034 |
| 2 | 1.687"- 1.812" (4.28-4.60) | F7 | 07401035 |
| | 1.750"- 1.875" (4.44-4.76) | | 074011260 |
| | 1.812"- 1.937" (4.60-4.92) | | 074011261 |
| 2 | 1.937"- 2.062" (4.92-5.24) | F7 | 074011262* |
| | 2.062"- 2.187" (5.24-5.55) | | 074011263* |
| | 2.187"- 2.312" (5.55-5.87) | | 074011264* |
| 2 1/2 | 2.312"- 2.437" (5.87-6.19) | F7 | 074011265* |
| | 1.688"- 1.812" (4.29-4.60) | | 074011030 |
| | 1.812"- 1.937" (4.60-4.92) | | 074011031 |
| 2 1/2 | 1.937"- 2.062" (4.92-5.24) | F7 | 074011032 |
| | 2.062"- 2.187" (5.24-5.55) | | 074011033 |
| | 2.187"- 2.312" (5.55-5.87) | | 074011034 |
| 3 | 2.312"- 2.437" (5.87-6.19) | F7 | 074011266* |
| | 1.937"- 2.062" (4.92-5.24) | | 074011036 |
| | 2.062"- 2.187" (5.24-5.55) | | 074011037 |
| 3 | 2.187"- 2.312" (5.55-5.87) | F8 | 074011038 |
| | 2.312"- 2.437" (5.87-6.19) | | 074011039 |
| | 2.437"- 2.625" (6.19-6.67) | | 074011186 |
| 3 | 2.625"- 2.812" (6.67-7.14) | F8 | 074011187 |
| | 2.812"- 3.000" (7.14-7.62) | | 074011188 |
| | 3.000"- 3.250" (7.62-8.25) | | 074011189* |

Note: Kellems® Deluxe Cord Grips are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 of the National Electric Code Sections 501.10(b)(2), 502.10(a)(2), 502.10(b)(2), 503.10(a)(2) and 503.10(b).
*Cable jacket may have to be stripped to pass through connector body.

Dimensions in Inches (mm)