

ELLIOTT **E**LECTRIC **S**UPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



0ET1 1/2" Oet Cond Body & CVR Crouse-Hinds

Catalog Number	OET1
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Oe Conduit Outlet Body With Cover, Feraloy Iron Alloy, T Shape, 1/2"
Weight per unit	2.1 (lbs/each)
Product Category	Bodies & Covers
eatures	
connection	Threaded
dimensions	5.5000 IN X 1.8100 IN X 2.4400 IN
Material, Color, and Finish	
Finish	Electrogalvanized With Aluminum Acrylic Painted
Dimensions and Weight	
Hub Size	1/2 in
Descriptions	
Description	1/2" OET COND BODY & CVR
extra long description	CRS-H OET1 1/2 CNDT OUTLET BODY CVR
Features	OE and EKC conduit bodies from Eaton's Crouse-Hinds Division
	are installed in conduit systems within hazardous areas to
	protect conductors in threaded rigid conduit, provide an opening
	in the conduit system for pulling or splicing conductors,
	interconnect lengths of conduit, change direction of conduit, and
	provide access for maintenance and future system changes. OE
	and EKC conduit bodies are certified for use in Class I, Division 1
	and Class II, Division 1 hazardous areas.
Long Description	Eaton Crouse-Hinds series Condulet OE conduit outlet body with
	cover, Feraloy iron alloy, T shape, 1/2"
Product Type	1/2 CNDT Outlet Body CVR
Special Features	With Cover
Manufacturer Information	
Brand	Eaton
GTIN	00782274552606
Manufacturers Part Number	OET1
UPC	782274552606
axonomies, Classifications, and C	Categories
Category Description	
Туре	Conduit outlet body with cover



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

Carton	
Package	2
-	2.05

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Class I Div 1 2 Group C D, Class II Div 1 Group E F G, Class II Div 2
	Group F G, Class III
standard	UL 886, CSA C22.2