

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



10316H1600 1NO 1NC 10A TD Limit Switch Eaton Corp

Catalog Number	10316H1600		
Manufacturer	Eaton Corp		
Description	Eaton 10316 Hazardous Location Limit Switch, Type LP Pneumatic Time Delay Limit Switch, Pneumatic Time Delay, Die Cast Zinc Enclosure, 10A Max Ac, 0.2A Max DC, 1NO-1NC, 10A At 120VAC / 0.2A At 120VDC, Screw Terminals, Side Rotary		
Weight per unit	1.9 (lbs/each)		
Product Category	Severe Duty Limit Switches		
eatures			
connection	Screw Terminal		
Contact Configuration	1 NO-1 NC		
Contact Rating	10A at 120Vac / 0.2A at 120Vdc		
escriptions			
Description	1NO 1NC 10A TD LIMIT SWITCH		
extra long description	ETN 10316H1600 Type LP Pneumatic Ti		
Features	Type LX, CX and CBX limit switches are designed for extreme environmental service in NEMA 7 9 locations where the danger of an internal or external explosion of flammable gases, vapors, metal alloy or grain dust exists. Type CB provides excellent corrosion-resistant properties in NEMA 4X applications. Markets served include mining, grain storage, forest products, petrochemical, pharmaceutical and waste and sewage management.		
Long Description	Eaton 10316 hazardous location limit switch, Type LP Pneumatic Time Delay Limit Switch, Pneumatic Time Delay, Die Cast Zinc enclosure, 10A max AC, 0.2A max DC, 1NO-1NC, 10A at 120Vac / 0.2A at 120Vdc, Screw Terminals, Side Rotary		
Product Type	Type LP Pneumatic Time Delay Limit Switch		
Nanufacturer Information			
Brand	EATON CUTLER-HAMMER		
GTIN	00782113266336		
Manufacturers Part Number	10316H1600		
UPC	782113266336		

Taxonomies, Classifications, and Categories

Category Description	LIMIT SWITCHES
Туре	Hazardous location limit switch



ELLIOTT ELECTRIC SUPPLY We Deliver Lower Cost, Quality Products, & Personal Service 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

we DeliverLower	Cost, Qu	iality Produc	ts, & Personal Service

Packaging	
Carton	1
Weight Per each	1.85
Uses, Certifications, and Standards	
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
Operating Temperature	32
standard	UL Listed,Contact Manufacturer