
Heavy duty grade power receptacles



5-50R **6-50R**

Product description

2-pole, 3-wire grounding
50A, 125V/AC
50A, 250V/AC



1253



1252

Design features

- Heavy gauge galvanized steel mounting strap for corrosion resistance
- For use with copper or aluminum wire
- Flush receptacles fit one-gang or two-gang enclosures
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom

Flush power receptacles

Rating A	V/AC	NEMA	Description	Color	Catalog no.		
50	125	5-50R	Flush mount power receptacle, matching plug A41	BK	☐ 1253	•	•
50	250	6-50R	Flush mount power receptacle, matching plug S42	BK	☐ 1254	•	•

Listed to UL498, file no. E15058; CSA certified to CSA C22.2, no. 42

Surface power receptacles

Rating A	V/AC	NEMA	Description	Color	Catalog no.		
50	250	6-50R	Surface mount power receptacle, matching plug S42	BK	☐ 1252	•	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Compatible wallplates / standard size for flush power receptacles

Description	Color suffix	Catalog no.		
Thermoset 1-Gang wallplate for one power receptacle	A, B, V, W	☐ 2068__	•	•
Thermoset 2-Gang wallplate for one power receptacle	A, B, LA, V, W	☐ 2168__	•	•
Nylon 1-Gang wallplate for one power receptacle	V	☐ 5068	•	•
Polycarbonate 1-Gang wallplate of one power receptacle	B, BK, V, W	☐ PJ724__		•
Polycarbonate 2-Gang wallplate for one power receptacle	B, V, W	☐ PJ703__		•
Stainless steel 1-Gang wallplate for one power receptacle	Stainless Steel	☐ 93221*	•	•
Stainless steel 2-Gang wallplate for one power receptacle	Stainless Steel	☐ 93227*	•	•

Listed to UL498, file no. E15058, *CSA certified to C22.2, no. 42

Color ordering information:


For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), Stainless Steel, W (White)

A	B	BK	LA	V		W
(Almond)	(Brown)	(Black)	(Lt. Almond)	(Ivory)	(Stainless Steel)	(White)

Dimensional information: B-70 **Specification information:** Please visit www.eaton.com/wiringdevices
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page G-21 RoHS compliant - Page G-21

Heavy duty grade power receptacles



5-50R **6-50R**

Product description

2-pole, 3-wire grounding
50A, 125V/AC
50A, 250V/AC



1253



1252

Design features

- Heavy gauge galvanized steel mounting strap for corrosion resistance
- For use with copper or aluminum wire
- Flush receptacles fit one-gang or two-gang enclosures
- Surface receptacles have patented lay-in terminals that accept up to #4 AWG wire
- Surface receptacle backs feature concentric knockouts and an adjustable cord clamp to allow wiring from back or bottom

Flush power receptacles

Rating A	V/AC	NEMA	Description	Color	Catalog no.		
50	125	5-50R	Flush mount power receptacle, matching plug A41	BK	☐ 1253	•	•
50	250	6-50R	Flush mount power receptacle, matching plug S42	BK	☐ 1254	•	•

Listed to UL498, file no. E15058; CSA certified to CSA C22.2, no. 42

Surface power receptacles

Rating A	V/AC	NEMA	Description	Color	Catalog no.		
50	250	6-50R	Surface mount power receptacle, matching plug S42	BK	☐ 1252	•	•

Listed to UL498, file no. E15058; CSA certified to C22.2, no. 42; NOM certified

Compatible wallplates / standard size for flush power receptacles

Description	Color suffix	Catalog no.		
Thermoset 1-Gang wallplate for one power receptacle	A, B, V, W	☐ 2068__	•	•
Thermoset 2-Gang wallplate for one power receptacle	A, B, LA, V, W	☐ 2168__	•	•
Nylon 1-Gang wallplate for one power receptacle	V	☐ 5068	•	•
Polycarbonate 1-Gang wallplate of one power receptacle	B, BK, V, W	☐ PJ724__		•
Polycarbonate 2-Gang wallplate for one power receptacle	B, V, W	☐ PJ703__		•
Stainless steel 1-Gang wallplate for one power receptacle	Stainless Steel	☐ 93221*	•	•
Stainless steel 2-Gang wallplate for one power receptacle	Stainless Steel	☐ 93227*	•	•

Listed to UL498, file no. E15058, *CSA certified to C22.2, no. 42

Color ordering information:

For ordering devices, include Catalog no. followed by the Color suffix: A (Almond), B (Brown), BK (Black), LA (Light Almond), V (Ivory), Stainless Steel, W (White)

A	B	BK	LA	V		W
(Almond)	(Brown)	(Black)	(Lt. Almond)	(Ivory)	(Stainless Steel)	(White)

Dimensional information: B-70 **Specification information:** Please visit www.eaton.com/wiringdevices
Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page G-21 RoHS compliant - Page G-21