

# Thin Wall Conduit Fittings (for EMT Conduit)

## Compression Type Fittings – Steel

### COMPRESSION TYPE FITTINGS – STEEL

#### Applications:

Thin wall conduit fittings are used:

- To join EMT to a box or enclosure
- To couple two ends of EMT conduit

#### Features:

- Compression type
- Threadless
- Male hub threads – NPSM
- Steel locknuts
- Heavy steel walls
- Standard material: steel
- Standard finish: zinc plated

### Concrete Tight Straight Connectors – Insulated

UL File No. E-22132



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 1650   | 1/2"   | 50        | 11               |
| 1651   | 3/4"   | 25        | 16               |
| 1652   | 1"     | 25        | 25               |
| 1653   | 1 1/2" | 10        | 43               |
| 1654   | 1 1/2" | 10        | 54               |
| 1655   | 2"     | 5         | 76               |
| 1656   | 2 1/2" | 2         | 190              |
| 1657   | 3"     | 1         | 300              |
| 1658   | 3 1/2" | 1         | 330              |
| 1659   | 4"     | 1         | 360              |

### Straight Connectors – Non-insulated


UL File No. E-22132



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 650S   | 1/2"   | 50        | 9                |
| 651S   | 3/4"   | 25        | 16               |
| 652    | 1"     | 25        | 25               |
| 653    | 1 1/4" | 10        | 43               |
| 654    | 1 1/2" | 10        | 54               |
| 655    | 2"     | 5         | 76               |
| 656    | 2 1/2" | 2         | 190              |
| 657    | 3"     | 1         | 300              |
| 658    | 3 1/2" | 1         | 280              |
| 659    | 4"     | 1         | 360              |

### Couplings

UL File No. E-22132



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 660S   | 1/2"   | 50        | 12               |
| 661S   | 3/4"   | 25        | 18               |
| 662    | 1"     | 25        | 27               |
| 663    | 1 1/4" | 10        | 46               |
| 664    | 1 1/2" | 10        | 63               |
| 665    | 2"     | 5         | 92               |
| 666    | 2 1/2" | 2         | 250              |
| 667    | 3"     | 1         | 410              |
| 668    | 3 1/2" | 1         | 390              |
| 669    | 4"     | 1         | 485              |

EMT Fittings

### Available in 7 Colors

Crouse-Hinds series painted EMT fittings consists of set screw, compression, insulated and non-insulated EMT fittings. Although red is the most commonly used, other colors offered include white, blue, green, yellow, black, and orange. These can also be used in architectural design, to better match look and feel to suit architectural specification and preference.



Part Number Example:

**650SGreen**

| Non-insulated Straight Connector |      | Color  |
|----------------------------------|------|--------|
| 1/2"                             | 650S | Red    |
| 3/4"                             | 651S | White  |
| 1"                               | 652  | Blue   |
| 1 1/4"                           | 653  | Yellow |
| 1 1/2"                           | 654  | Orange |
| 2"                               | 655  | Green  |
| 2 1/2"                           | 656  | Black  |
| 3"                               | 657  |        |
| 3 1/2"                           | 658  |        |
| 4"                               | 659  |        |

To order, simply add the name of the color needed after the catalog number.

# Thin Wall Conduit Fittings (for EMT Conduit)

## Compression Type Fittings – Steel

### COMPRESSION TYPE FITTINGS – STEEL

#### Applications:

Thin wall conduit fittings are used:

- To join EMT to a box or enclosure
- To couple two ends of EMT conduit

#### Features:

- Compression type
- Threadless
- Male hub threads – NPSM
- Steel locknuts
- Heavy steel walls
- Standard material: steel
- Standard finish: zinc plated

### Concrete Tight Straight Connectors – Insulated

UL File No. E-22132



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 1650   | 1/2"   | 50        | 11               |
| 1651   | 3/4"   | 25        | 16               |
| 1652   | 1"     | 25        | 25               |
| 1653   | 1 1/2" | 10        | 43               |
| 1654   | 1 1/2" | 10        | 54               |
| 1655   | 2"     | 5         | 76               |
| 1656   | 2 1/2" | 2         | 190              |
| 1657   | 3"     | 1         | 300              |
| 1658   | 3 1/2" | 1         | 330              |
| 1659   | 4"     | 1         | 360              |

### Straight Connectors – Non-insulated

UL File No. E-22132



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 650S   | 1/2"   | 50        | 9                |
| 651S   | 3/4"   | 25        | 16               |
| 652    | 1"     | 25        | 25               |
| 653    | 1 1/4" | 10        | 43               |
| 654    | 1 1/2" | 10        | 54               |
| 655    | 2"     | 5         | 76               |
| 656    | 2 1/2" | 2         | 190              |
| 657    | 3"     | 1         | 300              |
| 658    | 3 1/2" | 1         | 280              |
| 659    | 4"     | 1         | 360              |

### Couplings

UL File No. E-22132



| Cat. # | Size   | Unit Qty. | Wt. Lbs. Per 100 |
|--------|--------|-----------|------------------|
| 660S   | 1/2"   | 50        | 12               |
| 661S   | 3/4"   | 25        | 18               |
| 662    | 1"     | 25        | 27               |
| 663    | 1 1/4" | 10        | 46               |
| 664    | 1 1/2" | 10        | 63               |
| 665    | 2"     | 5         | 92               |
| 666    | 2 1/2" | 2         | 250              |
| 667    | 3"     | 1         | 410              |
| 668    | 3 1/2" | 1         | 390              |
| 669    | 4"     | 1         | 485              |

EMT Fittings

### Available in 7 Colors

Crouse-Hinds series painted EMT fittings consists of set screw, compression, insulated and non-insulated EMT fittings. Although red is the most commonly used, other colors offered include white, blue, green, yellow, black, and orange. These can also be used in architectural design, to better match look and feel to suit architectural specification and preference.



#### Part Number Example:

**650SGreen**

| Non-insulated Straight Connector |      | Color  |
|----------------------------------|------|--------|
| 1/2"                             | 650S | Red    |
| 3/4"                             | 651S | White  |
| 1"                               | 652  | Blue   |
| 1 1/4"                           | 653  | Yellow |
| 1 1/2"                           | 654  | Orange |
| 2"                               | 655  | Green  |
| 2 1/2"                           | 656  | Black  |
| 3"                               | 657  |        |
| 3 1/2"                           | 658  |        |
| 4"                               | 659  |        |

To order, simply add the name of the color needed after the catalog number.