



**Rust Proof Enamel Spray Paint
and Primer**

I. Product Description

CRC Rust Proof Enamel Spray Paint is a rust resistant, premium quality alkyd enamel, and the premier corrosion fighter in the marketplace. **CRC Rust Proof Enamel Primer** seals out moisture and fills in hairline cracks and other slight surface imperfections to provide a uniform basecoat for **Rust Proof Enamel**. They're specifically formulated for moderate to severe corrosive environments to resist rusting, peeling, and fading. **Rust Proof Enamel and Primer** fight weathering, salt spray and the most severe and demanding industrial conditions.

II. Applications

Recommended for use on iron, steel, wood and aluminum. For best results and highest durability, use **CRC Rust Proof Enamel Spray Paint** in conjunction with **CRC Rust Proof Enamel Primer**.

III. Features & Benefits

- **Will Not Fade.** Hard, durable finish is long-lasting, premium quality.
- **Excellent Resistance to Abrasion, Corrosion, and Solvents.** Lengthens time between repainting.
- **Enamel Formulation.** Offers gloss, durability, and flexibility superior to lacquer.
- **Fast Drying.** Reduces down time associated with slower-drying coatings.
- **Available in a Wide Range of Colors.** Meets almost every color need, including OSHA colors.
- **M.S.D.[L.]™-Material Safety Data Label.** Provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**
- Available in **20 oz. aerosol** can size.

IV. Physical Properties with propellant

Resin System	Alkyd enamel	% Volatile	42-56
Flash Point	<0°F TCC	Boiling Point	135°F-302°F
Odor and Appearance	Typical Ketone odor	Propellant	Hydrocarbon
Vapor Density	Heavier than air		
VOC Content (Fed) (Wt.)	65% maximum		
Sara Title III, Sect. 313 Chemicals	Yes		
Prop 65	Yes		

V. Performance Characteristics

Dry Time, Tack Free	15 to 30 minutes
Dry Time, Fully Dry	1 hour
Recoat	Before 1 hour or after 72 hours
Square Foot Coverage	25 to 40 square feet

VI. Directions

- Shake vigorously for at least one minute after rattling of mixing ball is heard. Shake intermittently during application.
- For best results, spray at room temperature (70°F to 80°F).
- Surface to be painted should be clean and dry. Remove dirt, grease, oil, rust, scale and other contaminants.
- Mask areas not to be sprayed to protect from overspray.
- Hold can 12 to 16 inches from surface. Press spray button firmly. Do not apply with continuous spray. Use back and forth motion, keeping can in a level line with surface.
- For best results 3-4 thin coats are recommended rather than one heavy coat. Recoat anytime.
- To prevent valve from clogging after spraying, turn can upside down and press sprayhead for about 3 seconds. This will clean paint from siphon tube and valve. If spray button is clogged, remove from can and run knife edge through tiny slit at end of spray button stem. Clear spray button orifice by inserting pin. Do not insert pins or other sharp objects into valve opening of can.

VII. Package Description

The Occupational Safety and Health Act (OSHA) stipulates that industrial plants provide color coded safety equipment in the workplace. OSHA also requires that hazardous areas be identified with certain colors. CRC provides a wide range of OSHA colors for the correct application and safety.

Rust Proof Enamel Spray Paint

18100	OSHA Red	18106	OSHA White
18101	OSHA Yellow	18109	Flat Black
18102	OSHA Blue	18114	Machinery Light Gray
18105	OSHA Black		

Rust Proof Enamel Spray Primer

18150	Gray Primer		
-------	-------------	--	--

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn.

Some state and local agencies may require that aerosol paints be sold from locked cages or other specialized displays in order to conform to local anti-graffiti regulations. Check with local authorities to ensure compliance with existing regulations. CRC can provide locked cages to aid in conformance to anti-graffiti legislation.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.