

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **266RT 2-1/2" Diecast Emt Raintight Compression Coupling** *Bridgeport Fittings*

Catalog Number	266RT
Manufacturer	Bridgeport Fittings
Description	2-1/2" Raintight Coupling
Weight per unit	1.5 (lbs/each)
Product Category	Liquid Tight Fittings
Features	
Connector Type	Compression
media	Yes
outside diameter	3.44
Dimensions and Weight	
Length	3.75
Descriptions	
Description	2-1/2" DIECAST EMT RAINTIGHT COMPRESSION COUPLING
extra long description	BPT 266-RT 2-1/2" RAIN TIGHT CPLG
Features	Think Orange: Quality In, Water Out. Listed for Damp or Wet Locations.
Long Description	2-1/2" Raintight Coupling
Product Type	2-1/2" Rain Tight CPLG
Special Features	With Bridgeport's newly redesigned Raintight Compression Couplings, 266-RT through 269-RT, contractors can install just one wet location fitting for either thread less Rigid / IMC or EMT.
Manufacturer Information	
Brand	Bridgeport Fittings
GTIN	00781747142665
Manufacturers Part Number	266RT
UPC	781747142665
Taxonomies, Classifications, and C	Categories
Category Description	DIECAST EMT FITTINGS
Туре	Raintight
Trade Size	
Trade Size	2.5
Packaging	
Carton	12
Weight Per each	1.525

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

ses, Certifications, and Sta	andaras
Application	These 2-1/2" dual Listed Zinc Alloy fittings come standard with a 105° C temperature rated insulated throat and the words "Rigid / EMT and RAINTIGHT" clearly cast into the body. This marking helps the AHJ to precisely confirm the products intended use.
	Patented
standard	cULus