Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

1207 Energy Drive
75662-0000, TX Kilgore
Phone: 903-984-8485
Fax: 903-984-8193



30024 Noalox (.5 Oz. Tube)

Ideal

Catalog Number	30024
Manufacturer	Ideal
Description	Anti-Oxidant Compound, 0.5 Oz Tube, Petroleum Base, 1.04 Specific Gravity, 310 °F Flash Point, 0.08 LB
Weight per unit	0.0800 (lbs/each)
Product Category	Paint, Chemicals, Etc.

Features

specific gravity	1.04

Dimensions and Weight

Size	0.5 OZ Tube

Descriptions

Description	NOALOX (.5 OZ. TUBE)
extra long description	IDEAL 30-024 NOALOX(.5 OZ.TUBE)
Features	IDEAL Noalox Anti-Oxidant compound improves efficiency and service life of aluminum electrical applications. Suspended zinc particles penetrate and cut aluminum oxide, while carrier material excludes air to minimize further oxidation. Provides additional inner-strand and inner-conductor current paths for improved conductivity and cooler connections. For use with pressure-type wire connectors including lugs, taps, service entrances and split-bolts. It is used with all types of pressure-type wire connectors.
Special Features	Anti-oxidant and anti-seizing compound improves efficiency and service life of aluminum-to-aluminum and aluminum-to-copper electrical connections; Suspended zinc particles penetrate and cut aluminum oxide; Provides additional interstrand and inter-conductor current paths for improved conductivity and cooler connections; Carrier material excludes air to prevent further oxidation; Reduces galling and seizing and promotes good ground continuity on aluminum conduit joints; Improves service life of aluminum ele

Manufacturer Information

Brand	Ideal
GTIN	00783250300242
UPC	783250300242

Taxonomies, Classifications, and Categories

Category Description	WIRE LUBE, MARKERS, & TIES
Type	Anti-Oxidant Compound

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
1207 Energy Drive
75662-0000, TX Kilgore
Phone: 903-984-8485
Fax: 903-984-8193

Packaging

Carton	1
Package	5
Weight Per each	0.08

Uses, Certifications, and Standards

standard	UL Listed