

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **30087J In-Sure Push-In Wire Conn, 87 5-PRT Gray, 150/Jar** *Ideal*

Catalog Number	30087J
Manufacturer	Ideal
Description	Push-In Wire Connector, Gray Insulation Color, +221 °F Operating Temperature, 0.355 In Overall Length, 0.907 In Overall Width, 0.729 In Overall Height, 600 V (Building Wire);1000 V (Maximum Signs/Lighting Fixture), 0.01 LB
Weight per unit	0.0098 (lbs/each)
Product Category	Electrical Fixture Conn ( Nuts
eatures	
connection	5 Ports
Voltage Rating	600 V Maximum Building Wire, 1000 V Maximum Signs And Lighting Fixtures
Wire Size	#12 AWG - #20 AWG Solid, #14 AWG - #16 AWG (19 Strand Or Less) #18 AWG (7 Strand Or Less) Stranded, #12 AWG - #14 AWG (19 Strand Or Less) #16 AWG (26 Strand Or Less) 318 AWG (16 Strand Or Less) Stranded (Tin Bonded)
Wire Type	Solid, Stranded, Stranded (Tin Bonded)
Material, Color, and Finish Color	Gray
imensions and Weight Size	0.355 IN Length X 0.907 IN Width X 0.729 IN Height
escriptions	
Description	IN-SURE PUSH-IN WIRE CONN, 87 5-PRT GRAY, 150/JAR
extra long description	IDEAL 30-087J PUSH-IN 12AWG 5-PORT,
Features	The In-Sure Push-In Wire Connector is perfect for residential, light commercial, lighting retrofit, and pre-fab wiring systems, or any other branch circuit wiring application where a traditional twist-on wire connector would be used. Simply push the wire in the low insertion force makes it easy. The color-coded shell allows for quick identification of port configuration while the clear polycarbonate housing allows for visual verification of every connection. The ergonomic design is easier to grip which me
Nanufacturer Information	
Brand	Ideal
GTIN	00783250460779
UPC	783250460779



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Temperature Rating 105 DEG C Shell Rated

Taxonomies, Classifications, and Cate	egories
Category Description	Datacom Wiring Devices and Accessories
Туре	Push-In
Availability	
minimum qty	150
Packaging	
Carton	150
Package	900
Weight Per each	0.0098
Uses, Certifications, and Standards	
standard	CSA C22.2 #188, 486C/467 UL Listed, RoHS