

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



30144 Twister Pro Wire Conn, 344 Red/Tan, 50/Box *Ideal*

Catalog Number	30144	
Manufacturer	Ideal	
Description	Ideal, Wire Connector, Twister Pro, Conductor Range: 22 - 8 Awg, 2/18 Awg Min, 4/10 Awg Max, Number Of Conductors: 2 to 4, Material: Flame-Retardant Polypropelene, Color: Red/Tan, Voltage Rating: 600 V, Environmental Conditions: Tough, UI 94V-2 Flame-Retardant Shell Rated At 105 Deg C (221 Deg F), Wire Type: Cu/Cu, Model Number: 344	
Weight per unit	0.4750 (lbs/each)	
Product Category	Electrical Fixture Conn (Nuts	
Features		
Material	Flame-Retardant Polypropylene	
Number of Conductors	2 to 4	
Voltage Rating	600	
Wire Type	Cu/Cu	
Material, Color, and Finish Color	Red/Tan	
	1.17.71	



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

criptions	
Description	TWISTER PRO WIRE CONN, 344 RED/TAN, 50/BOX
extra long description	IDEAL 30-144 TWISTER PRO 344 RED TA
Features	Twister Wire Connectors have earned a solid reputation as the most technically advanced wire connector available. These superior wire connectors are designed from top to bottom with features to provide more comfort and less fatigue to professional electricians. With swept wings and an expanding, live-action spring, the Twister supports a wide range of common wiring configurations with comfort and ease, even on the toughest combinations like solid-to-stranded. The copolymer shell expands for smooth, progres
Long Description	IDEAL, Wire Connector, Twister PRO, Conductor Range: 22 - 8 AWG, 2/18 AWG Min, 4/10 AWG MAX, Number Of Conductors: 2 to 4, Material: Flame-retardant Polypropelene, Color: Red/Tan, Voltage Rating: 600 V, Environmental Conditions: Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 DEG F), Wire Type: Cu/Cu, Model Number: 344
Product Type	Twister Pro 344 Red Tan, 50 BX
Special Features	Features: The Widest Red/Tan Wire Range In The Industry; Min. 2 #18 To Max. 4 #10; Suregrip Overmolding Provides Better Grip For Improved Leverage And More Torque; Comfortable Swept Wings Designed To Help Reduce Hand Fatigue; Expanding Square-Wire Spring Provides A Secure Connection Every Time; Better Grip And More Leverage For Faster Connections With Less Effort; Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 Degree C (221 Degree F); UL Listed To 486C And CSA Certified To C22.2 #188; Comply With Feder

Manufacturer Information

Brand	ldeal
GTIN	00783250707812
Manufacturers Part Number	30-144
sub brand	Twister ® PRO
UPC	783250707812

Taxonomies, Classifications, and Categories

Category Description	Datacom Wiring Devices and Accessories
\vailability	

Availability

minimum qty	50
-------------	----



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_		•
Pac	$I/ \cap \cap$	111111
יאכ	K An	
uu	NUU	

Carton	50	
Package	500	
Weight Per each	0.475	

Uses, Certifications, and Standards

Application	Insulating or Joining 1 or more conductors
environmental conditions	Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 DEG F)
standard	CSA C22.2 #188, UL 486C Listed, RoHS