

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Ideal	303184
Catalog Number Manufacturer	Ideal
Description	Crounding Tail Serow Torminal Croop 0.02 LD/Ea
Weight per unit	· · · · · · · · · · · · · · · · · · ·
Product Category	0.0240 (lbs/each) Miniature/Appliance WRG Dev
eatures	Williatare/Appliance Wike Bev
connection	#10 Fork And #10 Ring And Ground Screw
Wire Size	12
Wire Type	STRANDED
	SHANDED
Descriptions	CTOND COND TAIL #10 FORK/#10 DINC/CDD CCDM/ 2F/DAC
Description	STRND GRND TAIL-#10 FORK/#10 RING/GRD SCRW, 25/BAG IDEAL 30-3184 JUMPER W RING, SCREW
extra long description Special Features	Stranded pigtail lead wires are convenient for device grounding
Special reatules	applications; Grounding screw offers a unique thread-forming,
	hole-finding feature plus combination 5/16 IN hex, #2 Phillips,
	1/4 IN slotted and #2 Robertson head; Ultra-flexible lead wire
	tucks easily into box; Heavy-duty fork terminal attaches easily to
	grounding screw; Reduces time required for device bonding;
	Custom tails available
Nanufacturer Information	
Brand	ldeal
GTIN	00783250454525
UPC	783250454525
axonomies, Classifications, and Cat	egories
	Fuses & Fuse Accessories
Туре	Grounding Tail
vailability	
minimum qty	25
ackaging	
Carton	25
Package	250
Weight Per each	0.024
Ises, Certifications, and Standards	
Application	For Device Grounding Applications
standard	C/US UL Listed, Ensures Compliance With NEC Standards, RoHS

Compliant