

Carton

Weight Per each

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Catalog Number	303392
Manufacturer	ldeal
Description	Solid Wire Grounding Tail, Green Insulation Color, 0.02 LB
Weight per unit	0.0230 (lbs/each)
Product Category	Splicing & Terminating Kits
atures	
connection	Loop With Ground Screw And Stripped End
Wire Size	12
Wire Type	SOLID
aterial, Color, and Finish	
Color	Green
escriptions	
Description	SOLID GRND TAIL -LOOP/GRD SCRW-STRIPPD END, 50/BOX
extra long description	IDEAL 30-3392 12AWG 8INCH BOX OF 50
Features	Coming in various lengths and styles, IDEAL Grounding Pigtails
	are designed for a wide variety of grounding applications to h
	ensure compliance with Article 250 of the National Electric Co
	Whether you need solid or stranded, fork or stripped end, sm
	packaging for the occasional use or bulk packaging for the big
	jobs, we have a solution. The ultra-flexible lead wire and bond
	jumpers make for fast and efficient pigtailing and the thread
	–forming, hole finding ground screw cuts down on installatio
Special Features	Solid pigtail lead wires are convenient for device grounding
	applications; Grounding screw offers a unique thread-forming
	hole-finding feature plus combination 5/16 IN hex, #2 Phillips, 1/4 IN slotted and #2 Robertson head; Custom tails available
anufacturar Information	174 IIV Slotted and #2 Robertson nead, custom talls available
anufacturer Information Brand	Ideal
GTIN	00783250474981
UPC	783250474981
xonomies, Classifications, an	d Categories
C-4 D!!	Fuses & Fuse Accessories
Туре	
vailability	
minimum qty	50
	3.7
nckaging	

50

0.023

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	For Device Grounding Applications
standard	C/US UL Listed, Ensures Compliance With NEC Standards, RoHS
	Compliant