

# RECTORSEAL® PIPE THREAD SEALANTS

Continued

## BLUE+™

### PTFE Enriched Non-Setting Thread Pipe Sealant

| Code  | Description | Qty. |
|-------|-------------|------|
| 31633 | 1/4 pt.     | 24   |
| 31553 | 1/2 pt.     | 24   |
| 31433 | 1 pt.       | 12   |
| 31303 | 1 qt.       | 12   |



File No. 1282



SYSTEM COMPATIBLE



NSF



US



LISTED  
PIPE JOINT COMPOUND  
MH12259

#### FEATURES

- Non-Setting
- Lead Free
- 2 year shelf life
- Certified to NSF/ANSI 61-G & 372

**Application** • Use on lines carrying potable water (hot or cold), DWV, natural gas, LPG, compressed air, and most other industrial gases. • Up to 10,000 psi liquid and 2,000 psi gases. • Temperature service range of -15°F to 350°F. • Not recommended for oxygen.

**Recommended for** • Iron  
• Galvanized Steel • Stainless Steel • Brass • Copper  
• Aluminum • Polyethylene  
• PVC • ABS • CPVC  
• Reinforced Fiberglass

See ordering chart for container sizes available.



## RectorSeal Tru-Blu™

### Vibration resistant pipe thread sealant

| Code  | Description | Qty. |
|-------|-------------|------|
| 31780 | 1-3/4 oz.   | 24   |
| 31631 | 1/4 pt.     | 24   |
| 31551 | 1/2 pt.     | 24   |
| 31431 | 1 pt.       | 12   |
| 31300 | 1 qt.       | 12   |



Certified to NSF/ANSI 61 & 372



FILE NO. 1282

#### FEATURES

- Fast drying / Flexible set
- Contains PTFE
- Lead free
- 2 year shelf life
- Certified to NSF/ANSI 61-G & 372

**Application** • For high vibration environments such as refrigeration and industrial applications • Designed for sealing vibration prone NPT connections

**Recommended for**  
• Galvanized Steel • Iron  
• Brass • Copper • Aluminum  
• Stainless Steel • PVC  
• Polyethylene  
• Reinforced fiberglass



## No. 5® Sub-Zero

### Low temperature, low odor pipe thread sealant

| Code  | Description | Qty. |
|-------|-------------|------|
| 27731 | 1/4 pt.     | 24   |
| 27651 | 1/2 pt.     | 24   |
| 27541 | 1 pt.       | 12   |
| 27460 | 1 qt.       | 12   |
| 27371 | 1 gal.      | 4    |
| 27111 | 5 gal.      | 1    |
| 27222 | 55 gal.     | 1    |



US



FILE NO. 1282

#### FEATURES

- Low temperature application -35°F
- All weather formula
- Lead free

**Application** • Odorless, non-staining, low temperature application  
• Brushable to -35°F • Can be pressurized immediately

**Recommended for** • Galvanized Steel  
• Iron • Brass • Copper • Aluminum  
• Stainless Steel  
• Polyethylene  
• RTRP • PVC

See ordering chart for container sizes available.



\*FBC™ "System Compatible" indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings. \*\*FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation.

# RECTORSEAL® PIPE THREAD SEALANTS

Continued

## BLUE+™

### PTFE Enriched Non-Setting Thread Pipe Sealant

| Code  | Description | Qty. |
|-------|-------------|------|
| 31633 | 1/4 pt.     | 24   |
| 31553 | 1/2 pt.     | 24   |
| 31433 | 1 pt.       | 12   |
| 31303 | 1 qt.       | 12   |



File No. 1282



SYSTEM COMPATIBLE



NSF



US



LISTED  
PIPE JOINT COMPOUND  
MH12259

#### FEATURES

- Non-Setting
- Lead Free
- 2 year shelf life
- Certified to NSF/ANSI 61-G & 372

**Application** • Use on lines carrying potable water (hot or cold), DWV, natural gas, LPG, compressed air, and most other industrial gases. • Up to 10,000 psi liquid and 2,000 psi gases. • Temperature service range of -15°F to 350°F. • Not recommended for oxygen.

**Recommended for** • Iron  
• Galvanized Steel • Stainless Steel • Brass • Copper  
• Aluminum • Polyethylene  
• PVC • ABS • CPVC  
• Reinforced Fiberglass

See ordering chart for container sizes available.



## RectorSeal Tru-Blu™

### Vibration resistant pipe thread sealant

| Code  | Description | Qty. |
|-------|-------------|------|
| 31780 | 1-3/4 oz.   | 24   |
| 31631 | 1/4 pt.     | 24   |
| 31551 | 1/2 pt.     | 24   |
| 31431 | 1 pt.       | 12   |
| 31300 | 1 qt.       | 12   |



Certified to NSF/ANSI 61-G & 372



FILE NO. 1282

#### FEATURES

- Fast drying / Flexible set
- Contains PTFE
- Lead free
- 2 year shelf life
- Certified to NSF/ANSI 61-G & 372

**Application** • For high vibration environments such as refrigeration and industrial applications • Designed for sealing vibration prone NPT connections

**Recommended for**  
• Galvanized Steel • Iron  
• Brass • Copper • Aluminum  
• Stainless Steel • PVC  
• Polyethylene  
• Reinforced fiberglass



## No. 5® Sub-Zero

### Low temperature, low odor pipe thread sealant

| Code  | Description | Qty. |
|-------|-------------|------|
| 27731 | 1/4 pt.     | 24   |
| 27651 | 1/2 pt.     | 24   |
| 27541 | 1 pt.       | 12   |
| 27460 | 1 qt.       | 12   |
| 27371 | 1 gal.      | 4    |
| 27111 | 5 gal.      | 1    |
| 27222 | 55 gal.     | 1    |



US



FILE NO. 1282

#### FEATURES

- Low temperature application -35°F
- All weather formula
- Lead free

**Application** • Odorless, non-staining, low temperature application  
• Brushable to -35°F • Can be pressurized immediately

**Recommended for** • Galvanized Steel  
• Iron • Brass • Copper • Aluminum  
• Stainless Steel  
• Polyethylene  
• RTRP • PVC

See ordering chart for container sizes available.



\*FBC™ "System Compatible" indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings. \*\*FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation.