



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 31381 Clearglide, 1-Gallon Bucket

*Ideal*

|                  |   |
|------------------|---|
| Catalog Number   | 31381   |
| Manufacturer     | Ideal   |
| Description      | Lubricant, 1 Gal Pail, Colorless, Slight Odor, Clearglide Lubricant, 1.09 Specific Gravity, +40 to +100 °F, 8.58 LB |
| Weight per unit  | 8.6 (lbs/each)  |
| Product Category | Paint, Chemicals, Etc.  |

### Features

|                  |      |
|------------------|------|
| specific gravity | 1.09 |
|------------------|------|

### Dimensions and Weight

|      |   |
|------|---|
| Size | 1 |
|------|---|

### Descriptions

|             |                             |
|-------------|-----------------------------|
| Description | CLEARGLIDE, 1-GALLON BUCKET |
|-------------|-----------------------------|

|                        |                                      |
|------------------------|--------------------------------------|
| extra long description | IDEAL 31-381 ClearGlide Lubricant, I |
|------------------------|--------------------------------------|

|          |   |
|----------|---|
| Features | IDEAL ClearGlide Wire pulling lubricant is a polymer-based formula well suited for all electrical and datacom applications, and safe to use with all cable types. It is clear and colorless, and suitable for indoor as well as outdoor applications. This formula provides quick and easy clean up, and extraordinary lubricity for super-fast pulls. Its controlled evaporation rate is ideal for shorter runs. It remains stable over wide temperature ranges from 32°F to 180°F (0°C to 82°C) and dries to a semi-fluid fil |
|----------|---|

|                  |  |
|------------------|--|
| Special Features | Clear and colorless for quick and easy clean-up; Exceptional lubricity for super-fast pulls; Polymer-based formula perfect for all electrical and datacom applications; Safe to use with all cable types; Remains stable over wide temperature range; Dries to a semi-fluid film that won't clog conduit; Clings to cable throughout long pulls; Easy to apply by hand, brush, or pump; Environmentally safe - non-toxic, non-flammable, and non-corrosive |
|------------------|--|

### Manufacturer Information

|       |       |
|-------|-------|
| Brand | Ideal |
|-------|-------|

|      |                |
|------|----------------|
| GTIN | 00783250348145 |
|------|----------------|

|     |              |
|-----|--------------|
| UPC | 783250348145 |
|-----|--------------|

### Taxonomies, Classifications, and Categories

|                      |                            |
|----------------------|----------------------------|
| Category Description | WIRE LUBE, MARKERS, & TIES |
|----------------------|----------------------------|

|      |           |
|------|-----------|
| Type | Lubricant |
|------|-----------|



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Package         | 4     |
| Weight Per each | 8.575 |

## Uses, Certifications, and Standards

|          |           |
|----------|-----------|
| standard | UL Listed |
|----------|-----------|