


## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





**UPC** 

## 33+SUPER34X76FT Super 33+ Vinyl Electrical Tape, 3/4" X 76', BK Minnesota Mining (3M)

The state of the s	
Catalog Number	33+SUPER34X76FT
Manufacturer	Minnesota Mining (3M)
Description	"Scotch® Super 33+ Vinyl Electrical Tape, 3/4 In X 76 FT, 1 In Core, Black, 10 Rolls/Carton, 100 Rolls/Case"
Weight per unit	0.0027 (lbs/each)
Product Category	Tools & Testers
- Features	
Adhesive Type	Rubber
Dielectric Strength	1150
Elongation at Break	2.5
media	Yes
Voltage Rating	600
Material, Color, and Finish	Dobacinal Chlorida
Backing Material	Polyvinyl Chloride
Dimensions and Weight	_
Thickness	7
Descriptions	
Description	SUPER 33+ VINYL ELECTRICAL TAPE, 3/4" X 76', BK
extra long description	3M 7100201470 Scotch® Super 33+™ Vi
Features	Scotch® Super 33+™ Vinyl Electrical Tape is a premium grade, 7 mil thick, all-weather vinyl-insulating tape. It is designed to perform continuously in ambient temperatures up to 105°C (220°F). The tape is conformable for cold weather application down to -18°C (0°F). It has excellent resistance to abrasion, moisture, alkalies, acids, corrosion and varying weather conditions (including ultraviolet exposure). The combination of elastic backing and aggressive adhesive provides moisture-tight electrical and mec
Long Description	"Scotch® Super 33+ Vinyl Electrical Tape, 3/4 in x 76 ft, 1 in Core,Black, 10 rolls/carton, 100 rolls/Case"
Product Type	Scotch® Super 33+™ Vinyl Electrical Tape
Vlanufacturer Information	
Brand	Super 33+
GTIN	00638060290354
Manufacturers Part Number	33+34X76FT1
1100	(000/000007/

638060290354



## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	TAPE
Packaging Carton	1
Package	100
Weight Per each	0.0027
Uses, Certifications, and Standards	
Application	Insulation