

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



3BR3042B200 3PH 200A 10KAIC MCB 30/42 Cir. Al Bus Nema 1 *Eaton Corp*

| E B B C T | |
|----------------------------------|---|
| Catalog Number | 3BR3042B200 |
| Manufacturer | Eaton Corp |
| Description | Main Circuit Breaker Loadcenter, 30 Spaces, 42 Circuits, 200 A, 120/208/240 V Ac, #1 Awg to 250 Kcmil Wire Size, Metallic (Enclosure) Material, Aluminum Bus Material, 73.9902 CM Overall Length, 36.3474 CM Overall Width, 98.5520 CM Overall Height, 40 LB |
| Weight per unit | 40.0 (lbs/each) |
| Product Category | Three Phase Main Breaker Load |
| Features | |
| amperage rating | 200 |
| Cover Type | Cover included |
| Phase | 3 |
| Dimensions and Weight | |
| Depth | 3.88 |
| Height | 4.5 |
| Size | L1 |
| Width | 14.31 |
| Descriptions | |
| Description | 3PH 200A 10KAIC MCB 30/42 CIR. AL BUS NEMA 1 |
| extra long description | ETN 3BR3042B200 3 Ph/BR LC 200A MCB |
| Features | Specially designed for easy installation, Eaton's BR 1-inch load centers house the branch circuit breakers and the wiring required to distribute power to individual circuits. They serve as main breaker for service entrances or as main lug when adding circuits to existing service. The main breaker protects the entire panel and can be used as a service disconnect. The branch breakers protect the wires leading to individual electrical loads such as fixtures and outlets. |
| Manufacturer Information | |
| GTIN | 00786676440707 |
| UPC | 786676440707 |
| Taxonomies, Classifications, and | l Categories |
| Category Description | LOADCENTERS & COVERS |
| Туре | Main breaker loadcenter |



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

UL 50,UL 67

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Packaging | |
|-------------------------------------|-------------------|
| Carton | 1 |
| Weight Per each | 40 |
| Uses, Certifications, and Standards | |
| Mounting | Combination Mount |