

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



3BR4242L200 3PH 200A Mlo 42/42 Cir. Al Bus Nema 1 *Eaton Corp*

| Catalog Number | 3BR4242L200 |
|----------------------------------|--|
| Manufacturer | Eaton Corp |
| Description | Main Lug Load Center, 42 Spaces, 42 Circuits, 200 A, |
| | 120/208/240 V Ac, #6-1/0 Awg Wire Size, Metallic (Enclosure) |
| | Material, Aluminum Bus Material, 36.3474 CM Overall Length, |
| | 10.3378 CM Overall Width, 98.5520 CM Overall Height |
| Weight per unit | 29.6 (lbs/each) |
| Product Category | Three Phase Main Lug Load Cent |
| Features | |
| amperage rating | 200 |
| Cover Type | Cover included |
| number of spaces | 42 |
| Phase | 3 |
| Dimensions and Weight | |
| Depth | 3.88 |
| Height | 40.7 |
| Size | L1 |
| Width | 14.31 |
| Descriptions | |
| Description | 3PH 200A MLO 42/42 CIR. AL BUS NEMA 1 |
| extra long description | ETN 3BR4242L200 3 Ph/BR LC 200A MLO |
| Features | Specially designed for easy installation, Eaton's BR 1-inch load |
| | centers house the branch circuit breakers and the wiring required |
| | to distribute power to individual circuits. They serve as main |
| | breaker for service entrances or as main lug when adding circuits |
| | to existing service. The main breaker protects the entire panel |
| | and can be used as a service disconnect. The branch breakers |
| | protect the wires leading to individual electrical loads such as fixtures and outlets. |
| | lixtures and outlets. |
| Manufacturer Information | 0070//7/440500 |
| GTIN | 00786676442503 |
| UPC | 786676442503 |
| Taxonomies, Classifications, and | |
| Category Description | |
| Type | Main lug loadcenter |
| Packaging | |
| Carton | 1 |
| Weight Per each | 29.6 |
| | |

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Mounting | Combination Mount |
|----------|-------------------|
| standard | UL 67,UL 50 |