

ETP™ 4000S Series Steel EMT Set Screw Connectors

NEC/CEC:
Listed for Ordinary Locations

Application

- To ground and secure EMT raceways to boxes and enclosures.

Features

- Heavy steel walls.
- Concretetight when taped.
- Pre-set/pre-staked set screws.
- Male hub threads — NPS.
- Available with insulated throat.
- Three-way combination screws 1/2" thru 2".
- Slotted hexhead screw 2-1/2" thru 4".
- Insulated throat connector rated +90 °C (+194 °F).
- 2-1/2" thru 4" rated for threadless Aluminum RMC and steel IMC.

Materials/Finish

- Steel/zinc plated

NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E-14895
- CSA Certified: 028507
- NEMA: FB-1



4050S-4100S



4125S - 4400S

Dimensions in Millimeters (Inches)

| Trade Size (Inches) | Body Length | Maximum Diameter | Thread Length | Weight per 100 kg (lb) | Catalog Number | Insulated Throat Catalog Number |
|---------------------|-------------|------------------|---------------|------------------------|----------------|---------------------------------|
| 1/2 | 26.2 (1.03) | 21.3 (0.84) | 11.2 (0.44) | 4.54 (10.00) | 4050S | 4050ST |
| 3/4 | 27.7 (1.09) | 27.4 (1.08) | 11.2 (0.44) | 6.80 (15.00) | 4075S | 4075ST |
| 1 | 30.2 (1.19) | 33.3 (1.31) | 11.2 (0.44) | 10.43 (23.00) | 4100S | 4100ST |
| 1-1/4 | 44.5 (1.75) | 42.9 (1.69) | 14.2 (0.56) | 19.05 (42.00) | 4125S | 4125ST |
| 1-1/2 | 49.3 (1.94) | 49.3 (1.94) | 14.2 (0.56) | 24.04 (53.00) | 4150S | 4150ST |
| 2 | 55.6 (2.19) | 60.5 (2.38) | 16.0 (0.63) | 34.02 (75.00) | 4200S | 4200ST |
| 2 - 1/2 | 60.5 (2.38) | 79.5 (3.13) | 22.4 (0.88) | 58.97 (130.00) | 4250S | 4250ST |
| 3 | 73.2 (2.88) | 95.3 (3.75) | 22.4 (0.88) | 104.33(230.00) | 4300S | 4300ST |
| 3 - 1/2 | 76.2 (3.00) | 108.0 (4.25) | 25.4 (1.00) | 113.40 (250.00) | 4350S | 4350ST |
| 4 | 81.0 (3.19) | 120.7 (4.75) | 25.4 (1.00) | 113.40 (250.00) | 4400S | 4400ST |

ETP™ 4000S Series Steel EMT Set Screw Connectors

NEC/CEC:
Listed for Ordinary Locations

Application

- To ground and secure EMT raceways to boxes and enclosures.

Features

- Heavy steel walls.
- Concretetight when taped.
- Pre-set/pre-staked set screws.
- Male hub threads — NPS.
- Available with insulated throat.
- Three-way combination screws 1/2" thru 2".
- Slotted hexhead screw 2-1/2" thru 4".
- Insulated throat connector rated +90 °C (+194 °F).
- 2-1/2" thru 4" rated for threadless Aluminum RMC and steel IMC.

Materials/Finish

- Steel/zinc plated

NEC/CEC Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- CSA Standard: C22.2 No. 18.3
- cUL Listed: E-14895
- CSA Certified: 028507
- NEMA: FB-1



4050S-4100S



4125S - 4400S

Dimensions in Millimeters (Inches)

| Trade Size (Inches) | Body Length | Maximum Diameter | Thread Length | Weight per 100 kg (lb) | Catalog Number | Insulated Throat Catalog Number |
|---------------------|-------------|------------------|---------------|------------------------|----------------|---------------------------------|
| 1/2 | 26.2 (1.03) | 21.3 (0.84) | 11.2 (0.44) | 4.54 (10.00) | 4050S | 4050ST |
| 3/4 | 27.7 (1.09) | 27.4 (1.08) | 11.2 (0.44) | 6.80 (15.00) | 4075S | 4075ST |
| 1 | 30.2 (1.19) | 33.3 (1.31) | 11.2 (0.44) | 10.43 (23.00) | 4100S | 4100ST |
| 1-1/4 | 44.5 (1.75) | 42.9 (1.69) | 14.2 (0.56) | 19.05 (42.00) | 4125S | 4125ST |
| 1-1/2 | 49.3 (1.94) | 49.3 (1.94) | 14.2 (0.56) | 24.04 (53.00) | 4150S | 4150ST |
| 2 | 55.6 (2.19) | 60.5 (2.38) | 16.0 (0.63) | 34.02 (75.00) | 4200S | 4200ST |
| 2 - 1/2 | 60.5 (2.38) | 79.5 (3.13) | 22.4 (0.88) | 58.97 (130.00) | 4250S | 4250ST |
| 3 | 73.2 (2.88) | 95.3 (3.75) | 22.4 (0.88) | 104.33(230.00) | 4300S | 4300ST |
| 3 - 1/2 | 76.2 (3.00) | 108.0 (4.25) | 25.4 (1.00) | 113.40 (250.00) | 4350S | 4350ST |
| 4 | 81.0 (3.19) | 120.7 (4.75) | 25.4 (1.00) | 113.40 (250.00) | 4400S | 4400ST |