

## Commercial grade straight blade plugs & connectors

### Product description


2-pole, 3-wire grounding  
20A, 125V/AC  
NEMA 5-20



5-20P



5-20R



4866AN

### Commercial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	125	5-20	Vinyl straight body	0.25-0.66" (6.3-16.6mm)	Y	□ 4409*	□ 4228*	•	•
			Vinyl angled body	0.25-0.66" (6.3-16.6mm)	Y	□ 4409AN	—	•	•

\* UL and CSA Listed Only

## Commercial grade straight blade plugs & connectors

### Product description


2-pole, 2-wire grounding  
15A, 250V/AC  
NEMA 6-15



6-15P



6-15R



4509AN

### Commercial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	250	6-15	Vinyl straight body	0.25-0.66" (6.3-16.6mm)	Y	—	□ 4227*	•	•
			Vinyl angled body	0.25-0.66" (6.3-16.6mm)	Y	□ 4866AN	—	•	•

\* UL and CSA Listed Only

## Commercial grade straight blade plugs & connectors

### Product description


2-pole, 2-wire grounding  
20A, 250V/AC  
NEMA 6-20



6-20P



6-20R



4229

### Commercial grade plugs & connectors



Rating A	V/AC	Vinyl NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	250	6-20	Vinyl straight body	0.25-0.66" (6.3-16.6mm)	Y	□ 4509*	□ 4229 <sup>†</sup>	•	•
			Vinyl angled body	0.25-0.66" (6.3-16.6mm)	Y	□ 4509AN	—	•	•

<sup>†</sup> Not NOM cert, \* UL Listed Only

### Color information:

Y (Yellow)



(Yellow)

**Commercial grade dimensional information:** B-17

**Specification information:**  
Commercial grade plugs & connectors: B-26

**Compliances, specifications and availability are subject to change without notice.**

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32

## Commercial grade straight blade plugs & connectors

### Product description


2-pole, 3-wire grounding  
20A, 125V/AC  
NEMA 5-20




5-20P




5-20R



4866AN



4509AN



4229

### Commercial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	125	5-20	Vinyl straight body	0.25-0.66" (6.3-16.6mm)	Y	□ 4409*	□ 4228*	•	•
			Vinyl angled body	0.25-0.66" (6.3-16.6mm)	Y	□ 4409AN	—	•	•

\* UL and CSA Listed Only

## Commercial grade straight blade plugs & connectors

### Product description

2-pole, 2-wire grounding  
15A, 250V/AC  
NEMA 6-15



6-15P



6-15R

### Commercial grade plugs & connectors



Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	250	6-15	Vinyl straight body	0.25-0.66" (6.3-16.6mm)	Y	—	□ 4227*	•	•
			Vinyl angled body	0.25-0.66" (6.3-16.6mm)	Y	□ 4866AN	—	•	•

\* UL and CSA Listed Only

## Commercial grade straight blade plugs & connectors

### Product description

2-pole, 2-wire grounding  
20A, 250V/AC  
NEMA 6-20



6-20P



6-20R

### Commercial grade plugs & connectors



Rating A	V/AC	Vinyl NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
20	250	6-20	Vinyl straight body	0.25-0.66" (6.3-16.6mm)	Y	□ 4509*	□ 4229 <sup>†</sup>	•	•
			Vinyl angled body	0.25-0.66" (6.3-16.6mm)	Y	□ 4509AN	—	•	•

<sup>†</sup> Not NOM cert, \* UL Listed Only

### Color information:

Y (Yellow)



(Yellow)

**Commercial grade dimensional information:** B-17

**Specification information:**  
Commercial grade plugs & connectors: B-26

**Compliances, specifications and availability are subject to change without notice.**

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32