

Commercial grade straight blade plugs & connectors

Product description


2-pole, 3-wire grounding
20A, 125V/AC
NEMA 5-20




5-20P




5-20R



4866AN



4509AN



4229

Commercial grade plugs & connectors



| Rating A | V/AC | NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | | |
|-------------|------|------|---------------------|-------------------------|-------|---------------------|--------------------------|---|---|
| 20 | 125 | 5-20 | Vinyl straight body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4409* | □ 4228* | • | • |
| | | | Vinyl angled body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4409AN | — | • | • |

* UL and CSA Listed Only

Commercial grade straight blade plugs & connectors

Product description

2-pole, 2-wire grounding
15A, 250V/AC
NEMA 6-15



6-15P



6-15R

Commercial grade plugs & connectors



| Rating A | V/AC | NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | | |
|-------------|------|------|---------------------|-------------------------|-------|---------------------|--------------------------|---|---|
| 15 | 250 | 6-15 | Vinyl straight body | 0.25-0.66" (6.3-16.6mm) | Y | — | □ 4227* | • | • |
| | | | Vinyl angled body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4866AN | — | • | • |

* UL and CSA Listed Only

Commercial grade straight blade plugs & connectors

Product description

2-pole, 2-wire grounding
20A, 250V/AC
NEMA 6-20



6-20P



6-20R

Commercial grade plugs & connectors



| Rating A | V/AC | Vinyl NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | | |
|-------------|------|---------------|---------------------|-------------------------|-------|---------------------|--------------------------|---|---|
| 20 | 250 | 6-20 | Vinyl straight body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4509* | □ 4229 [†] | • | • |
| | | | Vinyl angled body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4509AN | — | • | • |

[†] Not NOM cert, * UL Listed Only

Color information:

Y (Yellow)



(Yellow)

**Commercial grade dimensional
Information:** B-17

Specification information:

Commercial grade plugs &
connectors: B-26

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32

Commercial grade straight blade plugs & connectors

Product description


2-pole, 3-wire grounding
20A, 125V/AC
NEMA 5-20




5-20P




5-20R



4866AN



4509AN



4229

Commercial grade plugs & connectors



| Rating A | V/AC | NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | | |
|-------------|------|------|---------------------|-------------------------|-------|---------------------|--------------------------|---|---|
| 20 | 125 | 5-20 | Vinyl straight body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4409* | □ 4228* | • | • |
| | | | Vinyl angled body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4409AN | — | • | • |

* UL and CSA Listed Only

Commercial grade straight blade plugs & connectors

Product description

2-pole, 2-wire grounding
15A, 250V/AC
NEMA 6-15



6-15P



6-15R

Commercial grade plugs & connectors



| Rating A | V/AC | NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | | |
|-------------|------|------|---------------------|-------------------------|-------|---------------------|--------------------------|---|---|
| 15 | 250 | 6-15 | Vinyl straight body | 0.25-0.66" (6.3-16.6mm) | Y | — | □ 4227* | • | • |
| | | | Vinyl angled body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4866AN | — | • | • |

* UL and CSA Listed Only

Commercial grade straight blade plugs & connectors

Product description

2-pole, 2-wire grounding
20A, 250V/AC
NEMA 6-20



6-20P



6-20R

Commercial grade plugs & connectors



| Rating A | V/AC | Vinyl NEMA | Description | Cord diameter | Color | Plug catalog no. | Connector catalog no. | | |
|-------------|------|---------------|---------------------|-------------------------|-------|---------------------|--------------------------|---|---|
| 20 | 250 | 6-20 | Vinyl straight body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4509* | □ 4229 [†] | • | • |
| | | | Vinyl angled body | 0.25-0.66" (6.3-16.6mm) | Y | □ 4509AN | — | • | • |

[†] Not NOM cert, * UL Listed Only

Color information:

Y (Yellow)



(Yellow)

**Commercial grade dimensional
Information:** B-17

Specification information:

Commercial grade plugs &
connectors: B-26

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32