

Industrial grade straight blade devices

Product description

2-pole, 3-wire grounding
15A, 125V/AC
NEMA 5-15



5-15P **5-15R**



AH5266



AH5969BK



AH5278C



AH5278

Industrial grade plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	125	5-15	Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	☐ AH5266	☐ AH5269	•	•
			Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK	☐ AH5266BK	☐ AH5269BK	•	•
			Safety grip angled body	0.33-0.66" (8.3-16.7mm)	BK & W	☐ AH5266A	—	•	•
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	BK	☐ AH5965BK	☐ AH5969BK		•
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	Y	☐ AH5965Y	☐ AH5969Y		•
			Auto grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	☐ 5266N	☐ 5269N	•	•

Industrial grade flanged inlets & outlets

Rating A	V/AC	NEMA	Description	Color	Inlet catalog no.	Outlet catalog no.	
15	125	5-15	Nylon construction, back wire	BK & W	☐ AH5278C†	☐ AH5279C*	•
			Metal shell, back wire	Steel	☐ AH5278Δ	☐ AH5246	•

* UL and CSA Listed, † Fed Spec certified, ΔOnly NOM spec

Industrial grade dimensional Information: B-16, B-17

Specification information:
Safety grip industrial plugs & connectors: B-24
Quick grip plugs & connectors: B-24
Auto grip industrial plugs & connectors: B-24
Industrial flanged inlets & Flanged outlets: B-25

Color information:

BK (Black), W (White), Y (Yellow)

BK (Black) W (White) Y (Yellow) (Steel)

Compliances, specifications and availability are subject to change without notice.


Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32


Industrial grade straight blade devices

Product description

2-pole, 3-wire grounding
15A, 125V/AC
NEMA 5-15



5-15P **5-15R**



AH5266



AH5969BK



AH5278C



AH5278

Industrial grade plugs & connectors

Rating A	V/AC	NEMA	Description	Cord diameter	Color	Plug catalog no.	Connector catalog no.		
15	125	5-15	Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	☐ AH5266	☐ AH5269	•	•
			Ultra grip straight body	0.33-0.66" (8.3-16.7mm)	BK	☐ AH5266BK	☐ AH5269BK	•	•
			Safety grip angled body	0.33-0.66" (8.3-16.7mm)	BK & W	☐ AH5266A	—	•	•
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	BK	☐ AH5965BK	☐ AH5969BK		•
			Quick grip straight body	0.22-0.66" (5.6-16.7mm)	Y	☐ AH5965Y	☐ AH5969Y		•
			Auto grip straight body	0.33-0.66" (8.3-16.7mm)	BK & W	☐ 5266N	☐ 5269N	•	•

Industrial grade flanged inlets & outlets

Rating A	V/AC	NEMA	Description	Color	Inlet catalog no.	Outlet catalog no.	
15	125	5-15	Nylon construction, back wire	BK & W	☐ AH5278C†	☐ AH5279C*	•
			Metal shell, back wire	Steel	☐ AH5278Δ	☐ AH5246	•

* UL and CSA Listed, † Fed Spec certified, ΔOnly NOM spec

Industrial grade dimensional Information: B-16, B-17

Specification information:
Safety grip industrial plugs & connectors: B-24
Quick grip plugs & connectors: B-24
Auto grip industrial plugs & connectors: B-24
Industrial flanged inlets & Flanged outlets: B-25

Color information:

BK (Black), W (White), Y (Yellow)

BK (Black) W (White) Y (Yellow) (Steel)

Compliances, specifications and availability are subject to change without notice.

Indicates NAFTA compliant - Page Q-32

RoHS compliant - Page Q-32