

# Ionization Smoke & Fire Alarm

## 120 Volt AC Hardwired with Battery Backup

### Model 5304

### Model 5304L (10 Year Lithium Battery)

Protects Against

Responds Quickly To  
Fast Flaming Fires



Perfect for new or replacement installations, this 120 volt AC/DC hardwired smoke and fire alarm offers time-saving installation features, value and quality. This alarm is fully interconnectable with all USI and Universal brand alarms.

#### Features

Quick Find® alarm origination feature  
Quick activation battery pull tab  
Universal mounting bracket  
Quick connect wiring harness  
Larger mounting base  
Interconnectable  
Front-load battery drawer  
Single silence/test button  
Full-size plastic dust cover  
2 tamper resistant locking features  
10-year lithium battery backup

#### Benefits

*Patented feature easily identifies first alarm to sound in an interconnected system*  
*Preserve battery life. Preinstalled battery is quickly activated without removing alarm from bracket*  
*Fits any standard wiring junction box, single gang, round or octagon, up to 4"*  
*Longer 8" pigtail wires are pre-stripped*  
*Covers drywall imperfections and old paint marks*  
*With all USI and Universal brand 120V alarm using existing wiring & mounting*  
*Replace battery without removing alarm from bracket*  
*Temporarily quiets nonemergency alarms and tests alarm functionality*  
*Protects alarm from dust, debris and painting during construction or home remodeling*  
*Prevents unauthorized alarm or battery removal*  
*Provides power for the life of the alarm--Model 5304L only*

#### Technical Specifications

Sensor Type:	Dual Ionization Sensing Chamber
Primary Power:	120 Volt AC 60Hz
Battery Backup:	9 Volt super heavy duty battery
Audible Alarm:	85 dB at 10 feet
Temperature Range:	40° F to 100° F (4° C to 38° C)
Humidity Range:	5% to 95% RH
Interconnect:	Maximum 24 USI/Universal devices
LED:	Green=AC power, Red=alarm
Size:	5.63" x 5.63" x 1.75"
Warranty:	10 year limited

#### Regulatory Compliance:

Underwriters Laboratories (UL-US)  
Underwriters Laboratories Canada (ULC)  
California State Fire Marshal (CSFM)  
National Fire Protection Association (NFPA)  
Housing and Urban Development (HUD)  
Federal Housing Authority (FHA)  
UTGT / UTHA



Box		SHELF PACK (in.)		WEIGHT		MASTER CTN (in.)		WEIGHT	
MODEL	BRAND	Clam	QTY	L x W x H	(Lbs.)	UPC CODE	QTY	L x W x H	(Lbs.)
5304	USI	BX	1	5.75 x 5.75 x 1.75	0.42	0-42741-05304-4	12	12.00 x 12.00 x 6.13	8.55
5304L	USI	BX	1	5.75 x 5.75 x 1.75	0.42	0-42741-15304-1	6	12.00 x 6.38 x 6.38	4.55

**UNIVERSAL**  
SECURITY INSTRUMENTS, INC.  
ALWAYS WORKING TO  
PROTECT YOUR FAMILY®

**Corporate Office**  
11407 Cronhill Dr., Suite A, Owings Mills, MD 21117  
**Phone:** 800.390.4321  
**Fax:** 410.363.2218  
**Web:** www.UniversalSecurity.com www.UsiElectric.com



© 2010 Universal Security Instruments, Inc.  
Rev. 10.18.16  
CM107

# Ionization Smoke & Fire Alarm

## 120 Volt AC Hardwired with Battery Backup

### Model 5304

### Model 5304L (10 Year Lithium Battery)

Protects Against

Responds Quickly To  
Fast Flaming Fires



Perfect for new or replacement installations, this 120 volt AC/DC hardwired smoke and fire alarm offers time-saving installation features, value and quality. This alarm is fully interconnectable with all USI and Universal brand alarms.

#### Features

Quick Find® alarm origination feature  
Quick activation battery pull tab  
Universal mounting bracket  
Quick connect wiring harness  
Larger mounting base  
Interconnectable  
Front-load battery drawer  
Single silence/test button  
Full-size plastic dust cover  
2 tamper resistant locking features  
10-year lithium battery backup

#### Benefits

*Patented feature easily identifies first alarm to sound in an interconnected system*  
*Preserve battery life. Preinstalled battery is quickly activated without removing alarm from bracket*  
*Fits any standard wiring junction box, single gang, round or octagon, up to 4"*  
*Longer 8" pigtail wires are pre-stripped*  
*Covers drywall imperfections and old paint marks*  
*With all USI and Universal brand 120V alarm using existing wiring & mounting*  
*Replace battery without removing alarm from bracket*  
*Temporarily quiets nonemergency alarms and tests alarm functionality*  
*Protects alarm from dust, debris and painting during construction or home remodeling*  
*Prevents unauthorized alarm or battery removal*  
*Provides power for the life of the alarm--Model 5304L only*

#### Technical Specifications

Sensor Type:	Dual Ionization Sensing Chamber
Primary Power:	120 Volt AC 60Hz
Battery Backup:	9 Volt super heavy duty battery
Audible Alarm:	85 dB at 10 feet
Temperature Range:	40° F to 100° F (4° C to 38° C)
Humidity Range:	5% to 95% RH
Interconnect:	Maximum 24 USI/Universal devices
LED:	Green=AC power, Red=alarm
Size:	5.63" x 5.63" x 1.75"
Warranty:	10 year limited

#### Regulatory Compliance:

Underwriters Laboratories (UL-US)  
Underwriters Laboratories Canada (ULC)  
California State Fire Marshal (CSFM)  
National Fire Protection Association (NFPA)  
Housing and Urban Development (HUD)  
Federal Housing Authority (FHA)  
UTGT / UTHA



Box		SHELF PACK (in.)		WEIGHT		MASTER CTN (in.)		WEIGHT	
MODEL	BRAND	Clam	QTY	L x W x H	(Lbs.)	UPC CODE	QTY	L x W x H	(Lbs.)
5304	USI	BX	1	5.75 x 5.75 x 1.75	0.42	0-42741-05304-4	12	12.00 x 12.00 x 6.13	8.55
5304L	USI	BX	1	5.75 x 5.75 x 1.75	0.42	0-42741-15304-1	6	12.00 x 6.38 x 6.38	4.55

**UNIVERSAL**  
SECURITY INSTRUMENTS, INC.  
ALWAYS WORKING TO  
PROTECT YOUR FAMILY®

**Corporate Office**  
11407 Cronhill Dr., Suite A, Owings Mills, MD 21117  
**Phone:** 800.390.4321  
**Fax:** 410.363.2218  
**Web:** www.UniversalSecurity.com www.UsiElectric.com



© 2010 Universal Security Instruments, Inc.  
Rev. 10.18.16  
CM107