

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



**Application** 

standard

## **54512 4/0 Butt Splice** Abb Installation Products, Inc

| (ORZA)                             |   |
|------------------------------------|---|
| Catalog Number                     | 54512   |
| Manufacturer                       | Abb Installation Products, Inc  |
| Description                        | Two-Way Splice Connector, 4/0 Awg Conductor Size,<br>Non-Insulated, Copper Conductor Material, Purple (Die Color)<br>Insulation Color, 2 Conductors, 1.88 In Overall Length,<br>Compression Terminal, 35 KV, 0.08 LB/Ea |
| Weight per unit                    | 0.0750 (lbs/each)   |
| Product Category                   | Large Terminals & Connectors  |
| eatures                            |   |
| insulation                         | None  |
| Material                           | Copper  |
| Voltage Rating                     | 600 V   |
| Material, Color, and Finish        |   |
| Color                              | Purple  |
| Finish                             | Tin Plated  |
| Descriptions                       |   |
| Description                        | 4/0 BUTT SPLICE   |
| extra long description             | ABB 54512 2 WAY SPLICE CONNECTOR 4/   |
| Manufacturer Information           |   |
| Brand                              | COLOR-KEYED   |
| GTIN                               | 00786210545127  |
| UPC                                | 786210545127  |
| Taxonomies, Classifications, and ( | Categories  |
| Category Description               | Comp & Mech Lugs and Butt Splices   |
| Туре                               | SPLICE  |
| Packaging                          |   |
| Carton                             | 10  |
| Weight Per each                    | 0.075   |
| Uses, Certifications, and Standard | ls  |
|                                    |   |

UL E9809 / UL E9809

Applications certified to 600 V and recommended up to 35 kVÂ¥