

Ultratite® Type NM



Liquidtight Flexible Nonmetallic Conduit. UL/CSA Listed. Oil-Resistant. Sunlight-Resistant. Crush-Resistant. Temperature Rated -30°C to 80°C.

APPLICATIONS

Ultratite® Liquidtight Flexible Nonmetallic Conduit is suitable of the following installations:

- For the installation and protection of electrical conductors
- Motor circuits - for conductors of motor feeders, branch and control circuits
- Where the conditions of installation, operation, or maintenance require flexibility or protection from liquids, vapors, solids, or weather
- Agricultural buildings per NEC® 547.5
- Used in industrial and commercial applications for conveyors, blowers, cranes, air conditioners, machine tooling and lubrication equipment
- Exposed or concealed installations
- Applications requiring movement, crossover connections, or tight bends
- For direct burial and encased in concrete
- For flexible connections to swimming pool, spa, and hot tub motors per NEC® 680.21(A)(3) & 680.42(A)(1)
- Electric signs and outline lighting supply and secondary-circuit conductors per NEC® 600.7, 600.31 (1000 volts or less) & 600.32 (over 1000 volts)
- Hazardous locations - see Additional Applications Section on the following page for more details

STANDARDS & REFERENCES

- NEC® Type designation - Type LFNC-B (Liquidtight Flexible Nonmetallic Conduit)
- ANSI / NFPA-70, NEC® Article 356
- UL Listed to Underwriters Laboratories Standard UL 1660
- Approved by Canadian Standards Association
- REACH/RoHS-2 (Chemical Limit) Compliant

CONSTRUCTION

Ultratite® Type NM is manufactured with rigid PVC reinforcement imbedded within a flexible PVC wall. The construction provides excellent impact and crush strength while remaining highly flexible. The conduit resists oils, mild acids and exposure to sunlight.

™Ultratite is a trademark of Southwire Company.



The Power of Connections.™



Southwire®

©2016 Southwire Company, LLC. All rights reserved. ®Registered Trademark of Southwire Company, LLC.
One Southwire Drive, Carrollton, GA 30119, USA

| TRADE SIZE (INCHES) | STOCK NUMBER | | DIAMETER (INCHES) | | WEIGHT (LBS/100') | APPROX. BEND DIAMETER (INCHES) |
|--|-----------------------|------------------------|----------------------|--------------------|----------------------|---|
| | | | INNER (MIN/MAX) | OUTER (MIN/MAX) | | |
| GRAY | | | | | | |
| 3/8 | 55-09-41-01 (100') | 55-09-41-06 (600') | .484/.504 | .69/.71 | 11 | 4 |
| 1/2 | 58-04-62-01 (100') | 55-09-42-02 (1000') | .622/.642 | .82/.84 | 13 | 6.5 |
| 3/4 | 58-04-63-01 (100') | 55-09-43-03 (1000') | .82/.84 | 1.03/1.05 | 18 | 8.5 |
| 1 | 55-09-44-01 (100') | 55-09-44-04 (400') | 1.041/1.066 | 1.29/1.315 | 26 | 13 |
| 1-1/4 | 55-09-45-01 (50') | 55-09-45-04 (250') | 1.38/1.41 | 1.63/1.66 | 31 | 16 |
| 1-1/2 | 55-09-46-01 (50') | 55-09-46-04 (150') | 1.575/1.6 | 1.865/1.99 | 45 | 18 |
| 2 | 55-09-48-01 (50') | 55-09-48-04 (100') | 2.02/2.045 | 2.34/2.375 | 62 | 22 |
| * Minimum bend radius based on NEC Chapter 9, Table 2 (other bends) per Article 356. | | | | | | |

FEATURES

- A protective combination of thermoplastic materials formed into a conduit/raceway which seals out water, liquids, abrasives, alcohol, coolants, corrosive fumes and gases, dirt, grease, mineral acids, non-concentrated fixed alkalines, petroleum oils, salt air and spray, and weather
- Smooth interior for easy wire pulling
- UV sunlight resistant jacket
- Rated for temperature range of -30°C to 80°C , 60°C Oil (-22 to +176, 140°F Oil)
- Accepts standard liquid-tight fittings for use with LFNC-B

ADDITIONAL APPLICATIONS

- In Hazardous Locations - where necessary for flexible connections within hazardous locations in accordance with the following:
 - Class I, Div. 2 - NEC® 501.10(B)(2)
 - Class II, Div. 1 - NEC® 502.10(A)(2)
 - Class II, Div. 2 - NEC® 502.10(B)(2)
 - Class III, Div. 1 - NEC® 503.10(A)(2)
 - Class III, Div. 2 - NEC® 503.10(B)
- Floating building feeders and services per NEC® 553.7
- Boatyards & Marinas in accordance with NEC® 555.13
- Cranes & Hoists in accordance with NEC® 610.11(C)
- For Elevator, Dumbwaiters, Escalators, Moving Walks, Wheel Chair Lifts & Stairway Chair Lifts in accordance with NEC® 620.21 (where expressly permitted)
- Under raised floors in information technology equipment conductors and cables in accordance with NEC® 645.5 (D) & 645.5(D)(2)
- Service entrance in lengths up to six feet per NEC® 230.43(15)
- For containment of 600 Volt and lower potential circuits
- Approved for use in lengths longer than 6 feet per NEC® 356.10(5)
- Motor leads per NEC® 430.145(B)

The Power of Connections.™



ONLINE CERTIFICATIONS & TOOLS

- [UL Online Certifications Directory \(www.ul.com \)](http://www.ul.com)
- [CSA Online Certifications Directory \(www.csa.ca \)](http://www.csa.ca)
- [UL Guide Information - Flexible Non-Metallic Conduit, Liquid-tight \(DXOQ\)](#)
- [CSA Product Information - Conduit-Flexible Nonmetallic, Liquid-Tight Conduit \(1813-01\)](#)

Ultratite® Type NM



Liquidtight Flexible Nonmetallic Conduit. UL/CSA Listed. Oil-Resistant. Sunlight-Resistant. Crush-Resistant. Temperature Rated -30°C to 80°C.

APPLICATIONS

Ultratite® Liquidtight Flexible Nonmetallic Conduit is suitable of the following installations:

- For the installation and protection of electrical conductors
- Motor circuits - for conductors of motor feeders, branch and control circuits
- Where the conditions of installation, operation, or maintenance require flexibility or protection from liquids, vapors, solids, or weather
- Agricultural buildings per NEC® 547.5
- Used in industrial and commercial applications for conveyors, blowers, cranes, air conditioners, machine tooling and lubrication equipment
- Exposed or concealed installations
- Applications requiring movement, crossover connections, or tight bends
- For direct burial and encased in concrete
- For flexible connections to swimming pool, spa, and hot tub motors per NEC® 680.21(A)(3) & 680.42(A)(1)
- Electric signs and outline lighting supply and secondary-circuit conductors per NEC® 600.7, 600.31 (1000 volts or less) & 600.32 (over 1000 volts)
- Hazardous locations - see Additional Applications Section on the following page for more details

STANDARDS & REFERENCES

- NEC® Type designation - Type LFNC-B (Liquidtight Flexible Nonmetallic Conduit)
- ANSI / NFPA-70, NEC® Article 356
- UL Listed to Underwriters Laboratories Standard UL 1660
- Approved by Canadian Standards Association
- REACH/RoHS-2 (Chemical Limit) Compliant

CONSTRUCTION

Ultratite® Type NM is manufactured with rigid PVC reinforcement imbedded within a flexible PVC wall. The construction provides excellent impact and crush strength while remaining highly flexible. The conduit resists oils, mild acids and exposure to sunlight.

™Ultratite is a trademark of Southwire Company.



The Power of Connections.™



Southwire®

©2016 Southwire Company, LLC. All rights reserved. ®Registered Trademark of Southwire Company, LLC.
One Southwire Drive, Carrollton, GA 30119, USA

| TRADE SIZE (INCHES) | STOCK NUMBER | | DIAMETER (INCHES) | | WEIGHT (LBS/100') | APPROX. BEND DIAMETER (INCHES) |
|--|-----------------------|------------------------|----------------------|--------------------|----------------------|---|
| | | | INNER (MIN/MAX) | OUTER (MIN/MAX) | | |
| GRAY | | | | | | |
| 3/8 | 55-09-41-01 (100') | 55-09-41-06 (600') | .484/.504 | .69/.71 | 11 | 4 |
| 1/2 | 58-04-62-01 (100') | 55-09-42-02 (1000') | .622/.642 | .82/.84 | 13 | 6.5 |
| 3/4 | 58-04-63-01 (100') | 55-09-43-03 (1000') | .82/.84 | 1.03/1.05 | 18 | 8.5 |
| 1 | 55-09-44-01 (100') | 55-09-44-04 (400') | 1.041/1.066 | 1.29/1.315 | 26 | 13 |
| 1-1/4 | 55-09-45-01 (50') | 55-09-45-04 (250') | 1.38/1.41 | 1.63/1.66 | 31 | 16 |
| 1-1/2 | 55-09-46-01 (50') | 55-09-46-04 (150') | 1.575/1.6 | 1.865/1.99 | 45 | 18 |
| 2 | 55-09-48-01 (50') | 55-09-48-04 (100') | 2.02/2.045 | 2.34/2.375 | 62 | 22 |
| * Minimum bend radius based on NEC Chapter 9, Table 2 (other bends) per Article 356. | | | | | | |

FEATURES

- A protective combination of thermoplastic materials formed into a conduit/raceway which seals out water, liquids, abrasives, alcohol, coolants, corrosive fumes and gases, dirt, grease, mineral acids, non-concentrated fixed alkalines, petroleum oils, salt air and spray, and weather
- Smooth interior for easy wire pulling
- UV sunlight resistant jacket
- Rated for temperature range of -30°C to 80°C , 60°C Oil (-22 to +176, 140°F Oil)
- Accepts standard liquid-tight fittings for use with LFNC-B

ADDITIONAL APPLICATIONS

- In Hazardous Locations - where necessary for flexible connections within hazardous locations in accordance with the following:
 - Class I, Div. 2 - NEC® 501.10(B)(2)
 - Class II, Div. 1 - NEC® 502.10(A)(2)
 - Class II, Div. 2 - NEC® 502.10(B)(2)
 - Class III, Div. 1 - NEC® 503.10(A)(2)
 - Class III, Div. 2 - NEC® 503.10(B)
- Floating building feeders and services per NEC® 553.7
- Boatyards & Marinas in accordance with NEC® 555.13
- Cranes & Hoists in accordance with NEC® 610.11(C)
- For Elevator, Dumbwaiters, Escalators, Moving Walks, Wheel Chair Lifts & Stairway Chair Lifts in accordance with NEC® 620.21 (where expressly permitted)
- Under raised floors in information technology equipment conductors and cables in accordance with NEC® 645.5 (D) & 645.5(D)(2)
- Service entrance in lengths up to six feet per NEC® 230.43(15)
- For containment of 600 Volt and lower potential circuits
- Approved for use in lengths longer than 6 feet per NEC® 356.10(5)
- Motor leads per NEC® 430.145(B)

The Power of Connections.™



ONLINE CERTIFICATIONS & TOOLS

- [UL Online Certifications Directory \(www.ul.com \)](http://www.ul.com)
- [CSA Online Certifications Directory \(www.csa.ca \)](http://www.csa.ca)
- [UL Guide Information - Flexible Non-Metallic Conduit, Liquid-tight \(DXOQ\)](#)
- [CSA Product Information - Conduit-Flexible Nonmetallic, Liquid-Tight Conduit \(1813-01\)](#)