ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685



613400 3/4"X10' CU GROUND ROD

ERICO, INC. ERITEC-CADDY

Catalog Number	613400
Manufacturer	ERICO, INC. ERITEC-CADDY
Description	Ground Rod, Copper Bonded Steel, 0.681 in Overall Width, 10 ft Overall Height, 12.3999 lb
Weight per unit	12.4 (lbs/each)
Product Category	Ground Rods & Grounding System

Features

Material	Copper-Bonded Steel
Tensile Strength	80,000

Material, Color, and Finish

Color	Yellow

Dimensions and Weight

Length	10-10

Descriptions

Description	3/4"X10' CU GROUND ROD
Features	The nVent ERICO Copper-Bonded Ground Rod, Pointed delivers the proven performance needed for dependable grounding and bonding systems. Engineered with a high-strength steel core and molecularly bonded copper coating, it combines the durability required for easy installation with the long-term corrosion resistance needed to help protect critical electrical infrastructure. The pointed tip design enables efficient driving into the ground, making installation faster while providing a reliable, low-impedance pa
Long Description	Copper-Bonded Ground Rod, Pointed, 3/4" dia, 10', 10 mil Plating, 12.6 lb
Product Type	Cu-Bonded Ground Rod, Pointed, 3/4"X10'
Short Description	EARTH ROD, CU BOND, POINTED, 1
Special Features	GR ROD,PTD,CU-BOND,NOM 3/4INX10FT,10MIL
Extra Long Description	NVNT 613400 Cu-Bonded Ground Rod, P

Manufacturer Information

Brand	nVent
	nVent ERICO
GTIN	00782856306177
UPC	782856

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Taxonomies, Classifications, and Categories

Category Description	SERVICE ENTRANCE FITTINGS: Weatherheads & Grounding Fittings & Ground Rods
Type	Copper-Bonded Ground Rods

Packaging

Carton	5
Weight Per Each	12.4 (lbs/each)

Uses, Certifications, and Standards

Application	Grounding and Bonding
Standard	cULus®