

ETP Steel EMT Compression Couplings

6000S Series Couplings

Application

- To ground and secure EMT raceway sections together.

Feature

- Concretetight.
- Raintight (wet locations) Canada.

Material/Finish

- Body and nut: steel
- Steel/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14895
- cUL Listed: E14895, E14815
- CSA Certified: 009795 • NEMA: FB-1

6000US Series Couplings

Application

- To ground and secure EMT raceway sections together.

Feature

- Made in the U.S.A.
- Concretetight.
- Raintight (wet locations) Canada.

Material/Finish

- Body and nut: steel
- Steel/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: (1/2 - 3) E14815
- CSA Standard: C22.2 No. 18.3
- cUL Listed: (1/2 - 3) E14815
- NEMA: FB-1



6050S – 6400S



6050US – 6200US



6250US – 6400US

| Trade Size (Inches) | Catalog Number | Dimensions in Inches/Millimeters | | Weight Lbs./Kgs. Per 100 |
|------------------------|-------------------|-------------------------------------|---------------------|-----------------------------|
| | | Body Length | Maximum Diameter | |
| 1/2 | 6050S | 1.38/35.1 | 0.84/21.3 | 19.00/8.62 |
| 3/4 | 6075S | 1.50/38.1 | 1.38/35.1 | 25.00/11.34 |
| 1 | 6100S | 1.66/42.2 | 1.31/33.3 | 39.00/17.69 |
| 1-1/4 | 6125S | 2.50/63.5 | 1.69/42.9 | 88.00/39.92 |
| 1-1/2 | 6150S | 2.50/63.5 | 1.94/49.3 | 104.00/47.17 |
| 2 | 6200S | 2.50/63.5 | 2.38/60.5 | 149.00/67.59 |
| 2-1/2 * | 6250S | 4.25/108.0 | 3.13/79.5 | 240.00/108.86 |
| 3 * | 6300S | 4.50/114.3 | 3.75/95.3 | 350.00/158.76 |
| 3-1/2 * | 6350S | 4.75/120.7 | 4.25/108.0 | 475.00/215.46 |
| 4 * | 6400S | 5.00/127.0 | 4.75/120.7 | 600.00/272.16 |

| Trade Size (Inches) | Catalog Number | Dimensions in Inches/Millimeters | |
|---------------------------|-------------------|-------------------------------------|---------------------|
| | | Body Length | Maximum Diameter |
| 1/2 | 6050US | 1.34/34.0 | 0.97/24.6 |
| 3/4 | 6075US | 1.34/34.0 | 1.22/31.0 |
| 1 | 6100US | 1.41/35.8 | 1.50/38.1 |
| 1-1/4 | 6125US | 1.75/44.5 | 1.91/48.5 |
| 1-1/2 | 6150US | 1.88/47.8 | 2.16/54.9 |
| 2 | 6200US | 2.13/54.1 | 2.69/68.3 |
| 2-1/2 | 6250US | 5.50/139.7 | 4.13/104.9 |
| 3 | 6300US | 5.50/139.7 | 4.69/119.1 |
| 3-1/2 | 6350US | 5.63/143.0 | 5.34/135.6 |
| 4 | 6400US | 5.75/146.1 | 5.88/149.4 |

* Rated for steel EMT, aluminum and steel RMC, and steel IMC.

ETP Steel EMT Compression Couplings

6000S Series Couplings

Application

- To ground and secure EMT raceway sections together.

Feature

- Concretetight.
- Raintight (wet locations) Canada.

Material/Finish

- Body and nut: steel
- Steel/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14895
- cUL Listed: E14895, E14815
- CSA Certified: 009795 • NEMA: FB-1

6000US Series Couplings

Application

- To ground and secure EMT raceway sections together.

Feature

- Made in the U.S.A.
- Concretetight.
- Raintight (wet locations) Canada.

Material/Finish

- Body and nut: steel
- Steel/zinc plated

Certifications and Compliances

- UL Standard: 514B
- UL Listed: (1/2 - 3) E14815
- CSA Standard: C22.2 No. 18.3
- cUL Listed: (1/2 - 3) E14815
- NEMA: FB-1



6050S – 6400S



6050US – 6200US



6250US – 6400US

| Trade Size (Inches) | Catalog Number | Dimensions in Inches/Millimeters | | Weight Lbs./Kgs. Per 100 |
|------------------------|-------------------|-------------------------------------|---------------------|-----------------------------|
| | | Body Length | Maximum Diameter | |
| 1/2 | 6050S | 1.38/35.1 | 0.84/21.3 | 19.00/8.62 |
| 3/4 | 6075S | 1.50/38.1 | 1.38/35.1 | 25.00/11.34 |
| 1 | 6100S | 1.66/42.2 | 1.31/33.3 | 39.00/17.69 |
| 1-1/4 | 6125S | 2.50/63.5 | 1.69/42.9 | 88.00/39.92 |
| 1-1/2 | 6150S | 2.50/63.5 | 1.94/49.3 | 104.00/47.17 |
| 2 | 6200S | 2.50/63.5 | 2.38/60.5 | 149.00/67.59 |
| 2-1/2 * | 6250S | 4.25/108.0 | 3.13/79.5 | 240.00/108.86 |
| 3 * | 6300S | 4.50/114.3 | 3.75/95.3 | 350.00/158.76 |
| 3-1/2 * | 6350S | 4.75/120.7 | 4.25/108.0 | 475.00/215.46 |
| 4 * | 6400S | 5.00/127.0 | 4.75/120.7 | 600.00/272.16 |

| Trade Size (Inches) | Catalog Number | Dimensions in Inches/Millimeters | |
|---------------------------|-------------------|-------------------------------------|---------------------|
| | | Body Length | Maximum Diameter |
| 1/2 | 6050US | 1.34/34.0 | 0.97/24.6 |
| 3/4 | 6075US | 1.34/34.0 | 1.22/31.0 |
| 1 | 6100US | 1.41/35.8 | 1.50/38.1 |
| 1-1/4 | 6125US | 1.75/44.5 | 1.91/48.5 |
| 1-1/2 | 6150US | 1.88/47.8 | 2.16/54.9 |
| 2 | 6200US | 2.13/54.1 | 2.69/68.3 |
| 2-1/2 | 6250US | 5.50/139.7 | 4.13/104.9 |
| 3 | 6300US | 5.50/139.7 | 4.69/119.1 |
| 3-1/2 | 6350US | 5.63/143.0 | 5.34/135.6 |
| 4 | 6400US | 5.75/146.1 | 5.88/149.4 |

* Rated for steel EMT, aluminum and steel RMC, and steel IMC.