

Model 700 Hand-Held Power Drive



Optional Carrying Case



Threading using a pipe wrench as a support arm



Capacity

- Pipe: 1/8"-2" (3 mm-50 mm).
Bolt: 1/4"-1" (6 mm-25 mm) using OO-RB Die Heads.

Features

- Heavy-duty hand-held power drive.
- Designed for RIDGID® No. 12-R die heads. Other RIDGID die heads (OO-R, OO-RB, 11-R) using adapters. Also used with 258/258XL pipe cutters. Die heads not included, see page 4.5.
- Approved by CSA to CSA and UL standards (115V only).

Technical Specifications

- Weight: 25 lbs. (11 kg) Power Drive only.
- Length: 28 1/4" (71.7 cm).
- Motor: Universal, 1/2 HP, 115V or 230V 50/60 Hz.
- Switch: Double-throw reversible.
- Gear Head: Spur gear reduction face gear drive. Spring-loaded adapter pawls. Hardened steel spindle gear.
- Body: Cast aluminum.
- Spindle Speed: 26-30 RPM (no load).

Selection

| Catalog No. | Model No. | Description | Pipe Threading Capacity | | Rod Threading Capacity | | Max. Geared Threader Capacity | | Weight | |
|-------------|-----------|--------------------|-------------------------|------|------------------------|------|-------------------------------|-----|--------|----|
| | | | in. | mm | in. | mm | in. | mm | lb. | kg |
| 41935 | 700 | 115V 50/60 Hz Only | 1/8-2 | 3-50 | 1/4-1 | 6-25 | 6 | 150 | 25 | 11 |
| 41940 | 700 | 230V 50/60 Hz Only | 1/8-2 | 3-50 | 1/4-1 | 6-25 | 6 | 150 | 25 | 11 |

Accessories

| Catalog No. | Model No. | Accessories Description | Weight | |
|-------------|-----------|--|--------|-----|
| | | | lb. | kg |
| 42600 | 770 | Adapter for OO-R and OO-RB | 3 3/8 | 2 |
| 42605 | 771 | Adapter for O-R | 3 3/8 | 2 |
| 42610 | 772 | Adapter for 11-R | 3 1/2 | 2 |
| 42615 | 773 | Adapter for 111-R | 3 | 1 |
| 42620 | 774 | Square Drive Adapter - 1 5/16" | 5 1/4 | 2 |
| 42625 | 775 | Support Arm for No. 700 | 11 | 5 |
| 42950 | B-171-X | Metal Carrying Case | 29 | 13 |
| 10883 | 418 | Oiler w/1 Gallon of Premium Thread Cutting Oil | 20 1/2 | 9,4 |
| 41620 | - | Gearhead Motor Grease | 1 | 0,5 |



See page 4.12

Model 700 Hand-Held Power Drive



Optional Carrying Case



Threading using a pipe wrench as a support arm



Capacity

- Pipe: 1/8"-2" (3 mm-50 mm).
Bolt: 1/4"-1" (6 mm-25 mm) using OO-RB Die Heads.

Features

- Heavy-duty hand-held power drive.
- Designed for RIDGID® No. 12-R die heads. Other RIDGID die heads (OO-R, OO-RB, 11-R) using adapters. Also used with 258/258XL pipe cutters. Die heads not included, see page 4.5.
- Approved by CSA to CSA and UL standards (115V only).

Technical Specifications

- Weight: 25 lbs. (11 kg) Power Drive only.
- Length: 28 1/4" (71.7 cm).
- Motor: Universal, 1/2 HP, 115V or 230V 50/60 Hz.
- Switch: Double-throw reversible.
- Gear Head: Spur gear reduction face gear drive. Spring-loaded adapter pawls. Hardened steel spindle gear.
- Body: Cast aluminum.
- Spindle Speed: 26-30 RPM (no load).

Selection

| Catalog No. | Model No. | Description | Pipe Threading Capacity | | Rod Threading Capacity | | Max. Geared Threader Capacity | | Weight | |
|-------------|-----------|--------------------|-------------------------|------|------------------------|------|-------------------------------|-----|--------|----|
| | | | in. | mm | in. | mm | in. | mm | lb. | kg |
| 41935 | 700 | 115V 50/60 Hz Only | 1/8-2 | 3-50 | 1/4-1 | 6-25 | 6 | 150 | 25 | 11 |
| 41940 | 700 | 230V 50/60 Hz Only | 1/8-2 | 3-50 | 1/4-1 | 6-25 | 6 | 150 | 25 | 11 |

Accessories

| Catalog No. | Model No. | Accessories Description | Weight | |
|-------------|-----------|--|--------|-----|
| | | | lb. | kg |
| 42600 | 770 | Adapter for OO-R and OO-RB | 3 3/8 | 2 |
| 42605 | 771 | Adapter for O-R | 3 3/8 | 2 |
| 42610 | 772 | Adapter for 11-R | 3 1/2 | 2 |
| 42615 | 773 | Adapter for 111-R | 3 | 1 |
| 42620 | 774 | Square Drive Adapter - 1 5/16" | 5 1/4 | 2 |
| 42625 | 775 | Support Arm for No. 700 | 11 | 5 |
| 42950 | B-171-X | Metal Carrying Case | 29 | 13 |
| 10883 | 418 | Oiler w/1 Gallon of Premium Thread Cutting Oil | 20 1/2 | 9,4 |
| 41620 | - | Gearhead Motor Grease | 1 | 0,5 |



See page 4.12