

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



6368043 480V, 3P + G, 20HP Rating Inlet, Male *Meltric Corporation*

umber	6368043
A	Meltric Corporation
Description	Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of
	Poles: 3; Wire Size: Min 12 Awg, Max 4 Awg; Auxiliary Contacts -
	Max 14 Awg; Amperage Rating: 60 Amp; Voltage Rating: 480 Vac;
	Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm
or unit	0.5700 (lbs/each)
	,
ategory	Pin & Sleeve Devices
rating	60 Hz
	Poly Bag
	3 in
	3 in
Voltage Rating	Overall Dimension 4-1/16 Inch Width x 3-3/16 Inch Depth x 4-3/4
	Inch Height; Fuel Type Natural; Capacity 23000 to 290000
	BTU/Hour; Pressure Tapping 1/8 Inch Threaded with Plug;
	Pressure Regulator Set Point 3.5 Inch WC
	Min 12 AWG, Max 4 AWG; Auxiliary Contacts - Max 14 AWG
or, and Finish	
	Blue Light
	•
	480V, 3P + G, 20HP RATING INLET, MALE
	MEL 63-68043 DSN60 INLET
	Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of
Long Description	Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contacts
	- Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480
	VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X;
	Environm
vne	DSN60 Inlet
, ·	Features: Switch Ratings (AC Only): Branch Circuit & Motor
Special Features	Circuit Disconnect Switching; Short Circuit Rating: 100 KAMP
	Close & Withstand Testing Was Performed With RK1 Current
	Limiting Fuses Sized At 400 PEC Of The Highest Full Load Motor
	Ampacity Associated With The Devices HP Rating; Listings: UL,
	CSA, IEC, CE Contact Customer Service; Horsepower Ratings: 20
	HP At 3 PH, 480 V; Polarity: 3P+G; Temperature Rating: -40 To
	140 DEG F
	urer on er unit ategory rating dor, and Finish on description ription



Carton

Manufacturer Information

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

0.57

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Brand	Meltric
GTIN	00784474545426
Manufacturers Part Number	63-68043
sub brand	Decontactor
UPC	784474545426
Taxonomies, Classifications, and	Categories
Category Description	Residential GFCI devices
Туре	DSN60, Switch Rated
Packaging	

Weight Per each

Uses, Certifications, and Standards	
Application	DS30A inlet decontactor
standard	UL, CSA, IEC,CE