

## **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## 6368043 480V, 3P + G, 20HP Rating Inlet, Male Meltric Corporation

Catalog Number	6368043
Manufacturer	Meltric Corporation
Description	Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of
	Poles: 3; Wire Size: Min 12 Awg, Max 4 Awg; Auxiliary Contacts
	Max 14 Awg; Amperage Rating: 60 Amp; Voltage Rating: 480 Va
	Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X;
	Environm
Weight per unit	0.5700 (lbs/each)
Product Category	Pin & Sleeve Devices
atures	
amperage rating	60 Hz
Material	Poly Bag
Phase	3 in
Poles	3 in
Voltage Rating	Overall Dimension 4-1/16 Inch Width x 3-3/16 Inch Depth x 4-3/
	Inch Height; Fuel Type Natural; Capacity 23000 to 290000
	BTU/Hour; Pressure Tapping 1/8 Inch Threaded with Plug;
	Pressure Regulator Set Point 3.5 Inch WC
Wire Size	Min 12 AWG, Max 4 AWG; Auxiliary Contacts - Max 14 AWG
aterial, Color, and Finish	
Color	Blue Light
	Dide Light
escriptions	U U U U U U U U U U U U U U U U U U U
escriptions Description	480V, 3P + G, 20HP RATING INLET, MALE
escriptions Description extra long description	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET
escriptions Description	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of
escriptions Description extra long description	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact
escriptions Description extra long description	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480
escriptions Description extra long description	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X;
escriptions Description extra long description Long Description	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm
escriptions Description extra long description Long Description Product Type	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm DSN60 Inlet
escriptions Description extra long description Long Description	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm DSN60 Inlet Features: Switch Ratings (AC Only): Branch Circuit & Motor
escriptions Description extra long description Long Description Product Type	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm DSN60 Inlet Features: Switch Ratings (AC Only): Branch Circuit & Motor Circuit Disconnect Switching; Short Circuit Rating: 100 KAMP
escriptions Description extra long description Long Description Product Type	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm DSN60 Inlet Features: Switch Ratings (AC Only): Branch Circuit & Motor Circuit Disconnect Switching; Short Circuit Rating: 100 KAMP Close & Withstand Testing Was Performed With RK1 Current
escriptions Description extra long description Long Description Product Type	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm DSN60 Inlet Features: Switch Ratings (AC Only): Branch Circuit & Motor Circuit Disconnect Switching; Short Circuit Rating: 100 KAMP Close & Withstand Testing Was Performed With RK1 Current Limiting Fuses Sized At 400 PEC Of The Highest Full Load Motor
escriptions Description extra long description Long Description Product Type	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm DSN60 Inlet Features: Switch Ratings (AC Only): Branch Circuit & Motor Circuit Disconnect Switching; Short Circuit Rating: 100 KAMP Close & Withstand Testing Was Performed With RK1 Current Limiting Fuses Sized At 400 PEC Of The Highest Full Load Motor Ampacity Associated With The Devices HP Rating; Listings: UL,
escriptions Description extra long description Long Description Product Type	480V, 3P + G, 20HP RATING INLET, MALE MEL 63-68043 DSN60 INLET Meltric; Inlet; Decontactor; DSN60, Switch Rated; Number Of Poles: 3; Wire Size: Min 12 AWG, Max 4 AWG; Auxiliary Contact - Max 14 AWG; Amperage Rating: 60 AMP; Voltage Rating: 480 VAC; Phase: 3; Material: Polyster; Color: Blue; Nema Rating: 4X; Environm DSN60 Inlet Features: Switch Ratings (AC Only): Branch Circuit & Motor Circuit Disconnect Switching; Short Circuit Rating: 100 KAMP Close & Withstand Testing Was Performed With RK1 Current Limiting Fuses Sized At 400 PEC Of The Highest Full Load Motor



## **ELLIOTT ELECTRIC SUPPLY**

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Manufacturer Information**

Brand	Meltric	
GTIN	00784474545426	
Manufacturers Part Number	63-68043	
sub brand	Decontactor	
UPC	784474545426	
Taxonomies, Classifications, and C	ategories	
Category Description	Residential GFCI devices	
Туре	DSN60, Switch Rated	
Packaging		
Carton	1	
Weight Per each	0.57	
Uses, Certifications, and Standards	5	
Application	DS30A inlet decontactor	
standard	UL, CSA, IEC,CE	