



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 664RTSC 6X6X4 RT Junction Box *Unity MFG*

|                  |  |
|------------------|--|
| Catalog Number   | 664RTSC  |
| Manufacturer     | Unity MFG  |
| Description      | Enclosure, Low Carbon Steel, Screw On/Slip On, Gray, Gunsmoke Gray Powder Coated, 4 In Overall Width, 6 In Overall Length, 6 In Overall Height, 3 LB |
| Weight per unit  | 3.0 (lbs/each)   |
| Product Category | Nema Types 3 & 3R Metallic Enc   |

### Features

|                        |   |
|------------------------|---|
| Cable Entry connection | (2) (1/2 - 3/4 IN) Conduit Concentric Knockout Bottom, (1) (3/4 - 1 IN) Conduit Concentric Knockout Bottom Freeform Pattern<br>Screw Terminal |
|------------------------|---|

### Descriptions

|                        |  |
|------------------------|--|
| Construction           | Formed From Code Gauge, Low Carbon Steel, Drip Shield Top, Seam Free Sides |
| Description            | 6X6X4 RT JUNCTION BOX  |
| extra long description | UNT 664RTSC N3R SCREW COVER PULL BO  |

### Manufacturer Information

|       |                |
|-------|----------------|
| Brand | Unity          |
| GTIN  | 00761515340509 |
| UPC   | 761515340509   |

### Taxonomies, Classifications, and Categories

|                      |                                  |
|----------------------|----------------------------------|
| Category Description | STEEL WIRE WAY JUNCTION BOXES    |
| Type                 | Screw-On Slip-On Cover Enclosure |

### Packaging

|                 |   |
|-----------------|---|
| Carton          | 1 |
| Package         | 8 |
| Weight Per each | 3 |

### Uses, Certifications, and Standards

|                   |  |
|-------------------|--|
| Mounting standard | WALL<br>C/US UL 50 And UL 50E - Type 3R: Intended For Indoor Use<br>Primarily To Provide A Degree Of Protection Against Rain, Sleet, Damage From External Ice Formation, CSA C22.2 No. 40 Certified, IEC 60529, RoHS Compliant |
|-------------------|--|