

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Catalog Number | 693 |
|---------------------------------|---|
| Manufacturer | Dass & Soumour/Logrand |
| Description | 15 Amps 120/277 Volts, Double Three-Way Combination Switch |
| | Non-Grounding, Brown. |
| Weight per unit | C C |
| Product Category | |
| eatures | |
| action | (2) 3W |
| actuator | Taggla |
| amperage rating | |
| connection | Side wire non grounding |
| Contact Configuration | |
| Contact Rating | |
| operating cycles | • |
| Poles | |
| Voltage | - |
| Voltage Rating | |
| Wattage | |
| Material, Color, and Finish | |
| Color | Brown |
| Dimensions and Weight | |
| Size | 1.32 L x 0.94 W x 4.06 H |
| Descriptions | |
| Description | COMBO 2 SWITCHES 3W 15A 120/277V BN |
| ovtro long description | |
| Long Description | 15 amps 120/277 volts, Double Three-way Combination Switch, |
| Long Description | Non-Grounding, Brown. |
| Product Type | Combo 2SWITCHES 3WAY 15A120/277V BN |
| Special Features | Easily accessible break-off for separate or common feed. Side |
| • | wire #12 and #14 AWG. Two devices fit into the space of one. |
| Anufacturer Information | |
| Brand | LEGRAND-PASS & SEYMOUR |
| GTIN | 00785007693003 |
| UPC | 785007693003 |
| axonomies, Classifications, and | |
| Category Description | |
| Туре | |
| турс | Non-Grounding combination two milee-way switches |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Trade Size Amperage | 15.0 |
|-------------------------------------|---|
| Packaging | |
| Carton | 1 |
| Package | 10 |
| Weight Per each | 0.25 |
| Uses, Certifications, and Standards | |
| Application | Residential/Commercial |
| environmental conditions | Flammability: UL94 V2 |
| Mounting | WALL |
| Operating Temperature | Maximum continuous +60°C, minimum -30°C |
| standard | CULUS, UL20 |