

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



696LA Combo 2SW 1P+3W 15A 120/277V La

Pass & Seymour/Legrand

Catalog Number	696LA
Manufacturer	Pass & Seymour/Legrand
Description	15 Amps, 120/277 Volts, Single Pole, Three-Way Combination Switch, Non-Grounding, Light Almond.
Weight per unit	0.2300 (lbs/each)
Product Category	Wiring Devices

Features

action	(1) SP & (1) 3W
actuator	Toggle
amperage rating	15
	Side wire, non-grounding
Contact Configuration	N-O
Contact Rating	15 Amp, 120/277 VAC
operating cycles	30000
Poles	1 & 3-Way
Voltage Rating	0.43321299639
Wattage	Electrical power is expressed in Amps and Volts.

Dimensions and Weight

Cina	1 22 1 1/2 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Size	1 4 / 1 V 11 U / 1 / 1 / 1 / 1 / 1 / 1 / 1
.) / 5	1.32 L x 0.94 W x 4.06 H

Descriptions

Description	COMBO 2SW 1P+3W 15A 120/277V LA
extra long description	P&S 696-LA COMBO 2 SW 1P+3W 15A 120
Long Description	15 amps, 120/277 volts, Single Pole, Three-way Combination
	Switch, Non-Grounding, Light Almond.
Product Type	Combo 2 SW 1P+3W 15A 120/277V La
Special Features	Easily accessible break-off for separate or common feed. Side
	wire #12 and #14 AWG. Two devices fit into the space of one.

Manufacturer Information

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007690262
Manufacturers Part Number	696LA
UPC	785007690262

Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Туре	Non-Grounding Combination Single Pole & Three-Way Switches



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Availability		
--------------	--	--

Status	Inactive	
Packaging		
Carton	1	
Package	10	
Weight Per each	0.23	

Uses, Certifications, and Standards

Application .	Residential/Commercial
environmental conditions	Flammability: UL94 V2
Mounting	WALL
Operating Temperature	Maximum continuous +60°C, minimum -30°C
standard	UL20