

ETP Raintight 700GSR Series Gland Compression Connectors

Application

- To ground and secure EMT raceway to boxes and enclosures in wet conditions.

Features

- UL Listed Raintight.
- Green compression nut identifies the fitting as raintight.
- No disassembly required.
- Male hub threads NPS.
- Available with and without insulated throat.
- Concretetight.

Materials/Finish

- Body and nut: steel
- Knockout sealing ring: EPDM rubber
- Body and nut: zinc electroplate

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- UL Listed Raintight



7100GSR



7100GSRT

| Trade Size (Inches) | Dimensions in Millimeters (Inches) | | | | Weight per 100 kg (lb) | Catalog Number | |
|------------------------|------------------------------------|---------------------|------------------|-----------------------------|---------------------------|------------------|--|
| | Body Length | Maximum Diameter | Thread Length | Without Insulated Throat | | Insulated Throat | |
| 1/2 | 36.6 (1.44) | 27.9 (1.10) | 8.6 (0.34) | 4.5 (10) | 7050GSR | 7050GSRT | |
| 3/4 | 38.1 (1.50) | 34.5 (1.36) | 8.6 (0.34) | 6.8 (15) | 7075GSR | 7075GSRT | |
| 1 | 44.5 (1.75) | 34.5 (1.36) | 9.9 (0.39) | 10.0 (22) | 7100GSR | 7100GSRT | |
| 1-1/4 | 50.8 (2.00) | 52.6 (2.07) | 10.2 (0.40) | 16.3 (36) | 7125GSR | 7125GSRT | |
| 1-1/2 | 50.8 (2.00) | 58.7 (2.31) | 10.2 (0.40) | 18.1 (40) | 7150GSR | 7150GSRT | |
| 2 | 58.9 (2.32) | 70.9 (2.79) | 10.4 (0.41) | 24.5 (54) | 7200GSR | 7200GSRT | |
| 2-1/2 | 91.9 (3.62) | 92.2 (3.63) | 16.5 (0.65) | 68.0 (150) | 7250GSR | 7250GSRT | |
| 3 | 95.3 (3.75) | 109.0 (4.29) | 16.5 (0.65) | 83.9 (185) | 7300GSR | 7300GSRT | |
| 3-1/2 | 97.8 (3.85) | 121.9 (4.80) | 18.3 (0.72) | 97.5 (215) | 7350GSR | 7350GSRT | |
| 4 | 99.1 (3.90) | 133.9 (5.27) | 18.3 (0.72) | 108.0 (238) | 7400GSR | 7400GSRT | |

ETP Raintight 700GSR Series Gland Compression Connectors

Application

- To ground and secure EMT raceway to boxes and enclosures in wet conditions.

Features

- UL Listed Raintight.
- Green compression nut identifies the fitting as raintight.
- No disassembly required.
- Male hub threads NPS.
- Available with and without insulated throat.
- Concretetight.

Materials/Finish

- Body and nut: steel
- Knockout sealing ring: EPDM rubber
- Body and nut: zinc electroplate

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E-14895
- UL Listed Raintight



7100GSR



7100GSRT

| Trade Size (Inches) | Dimensions in Millimeters (Inches) | | | | Weight per 100 kg (lb) | Catalog Number | |
|------------------------|------------------------------------|---------------------|------------------|-----------------------------|---------------------------|------------------|--|
| | Body Length | Maximum Diameter | Thread Length | Without Insulated Throat | | Insulated Throat | |
| 1/2 | 36.6 (1.44) | 27.9 (1.10) | 8.6 (0.34) | 4.5 (10) | 7050GSR | 7050GSRT | |
| 3/4 | 38.1 (1.50) | 34.5 (1.36) | 8.6 (0.34) | 6.8 (15) | 7075GSR | 7075GSRT | |
| 1 | 44.5 (1.75) | 34.5 (1.36) | 9.9 (0.39) | 10.0 (22) | 7100GSR | 7100GSRT | |
| 1-1/4 | 50.8 (2.00) | 52.6 (2.07) | 10.2 (0.40) | 16.3 (36) | 7125GSR | 7125GSRT | |
| 1-1/2 | 50.8 (2.00) | 58.7 (2.31) | 10.2 (0.40) | 18.1 (40) | 7150GSR | 7150GSRT | |
| 2 | 58.9 (2.32) | 70.9 (2.79) | 10.4 (0.41) | 24.5 (54) | 7200GSR | 7200GSRT | |
| 2-1/2 | 91.9 (3.62) | 92.2 (3.63) | 16.5 (0.65) | 68.0 (150) | 7250GSR | 7250GSRT | |
| 3 | 95.3 (3.75) | 109.0 (4.29) | 16.5 (0.65) | 83.9 (185) | 7300GSR | 7300GSRT | |
| 3-1/2 | 97.8 (3.85) | 121.9 (4.80) | 18.3 (0.72) | 97.5 (215) | 7350GSR | 7350GSRT | |
| 4 | 99.1 (3.90) | 133.9 (5.27) | 18.3 (0.72) | 108.0 (238) | 7400GSR | 7400GSRT | |