

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



72C5282NP001 1-70W 120/277 MH Bal *Advance By Signify*

72C5282NP001
Advance By Signify Versatility In Commercial Applications Low Noise For Indoor Use; Two Dual Voltage Configurations Available: 120V/277V For The U.S Market and 120V/347V For The Canadian Market The Philips Advance Line Of F-Can Hid Ballasts Comes In Two Dual-Voltage Configurations For The Us and Canadian Market. Ballasts For These Luminaires Are Most Often Encased and Potted In Fluorescent Ballast Type Cans. Utilizes UI Class A (90°C Insulation; Has Built-In, Automatically Resetting, Thermal Protector Which Disconnects The Ba
8.9 (lbs/each)
Pulse Start Hid Ballasts
1.25/0.55
M98/143
1
HX-HPF
METAL HALIDE
1
0.90
70
Pulse
120/277
70
12
STRANDED
Metal
1.02
0.47
1.54



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

-				•	
	es	^rı	nt	\mathbf{I}	nc
	_				
_	v	v ı .	\sim ι		

Description	1-70W 120/277 MH BAL
extra long description	ADV 494112 MH BAL 70W M98/143 120/2
Long Description	Versatility in commercial applications Low noise for indoor use; Two dual voltage configurations available: 120V/277V for the U.S market and 120V/347V for the Canadian market The Philips Advance line of F-can HID ballasts comes in two dual-voltage configurations for the US and Canadian market. Ballasts for these luminaires are most often encased and potted in fluorescent ballast type cans. Utilizes UL Class A (90°C) insulation; Has built-in, automatically resetting, thermal protector which disconnects the ba
Product Type	MH Bal 70W M98/143 120/277V Fcan
Special Features	Suitable for Outdoor; UL, CSA, RoHS
Manufacturer Information	
Brand	Signify Electronics
GTIN	00781087025253
Manufacturers Part Number	494112
UPC	781087025253
Taxonomies, Classifications, and C Category Description	

Type Packaging

ckaging		
Carton	1	
Weight Per each	8 86	

Magnetic HID

Uses, Certifications, and Standards

Frequency Rating	60
standard	CSA certificate;UL certificate;RoHS Compliant