WIREMOLD®
400/800/2300 Series™ Raceway

Low Profile Design Combines Functionality With Aesthetics

Ideal for Low Voltage and Power Applications

400, 800, 2300 and 2300BACD Series™ Raceway, are a family of low-profile raceways that are designed for communication or power applications. 400, 800 and 2300 Raceway offer a single channel for either communication or power. And when power and low voltage services are both needed in a single raceway, the divided 2300BACD Raceway with it's low-profile design, is an easy-to-install option.

400,800,2300 and 2300BACD Raceways are an ideal solution for use in classrooms, offices, hospitality applications, or anywhere a small, secure, low profile raceway is needed.



2300D Series Raceway in a typical office application.


FEATURES & BENEFITS

- **Accommodates communication and/or power wiring.** Can be used for communications, computer lines, surveillance systems, fire alarms, outlets, and more.
- **Available in three sizes.** 400, 800, and 2300 sizes provide flexibility for meeting a variety of capacity and space requirements. Perfect for most small drops and horizontal runs to work stations.
- **Durable, textured PVC construction.** Available in ivory or white finish to blend with any decor. Also paintable using latex paint. Consult factory for custom color options.
- **Single- and dual-compartment low profile design.** Provides functionality and flexibility with aesthetics for single- or dual-service applications.
- **Adhesive backing for low voltage (under 50V) applications.** Allows base to be pressed onto mounting surface. Speeds installation.
- **Lightweight and easy to handle.** Saves time and labor costs. Standard 5' (1.525m) raceway lengths can be easily installed by one person. Custom lengths up to 10' (3.05m) are also available.
- **Divided FiberReady® fittings.** For use with 2300BAC and 2300BACD. Full capacity fittings provide 2" (51mm) bend radius.
- **Over-the-raceway box for 2300 and 2300D.** Boxes mount over continuous run of raceway base eliminating the need to cut raceway when locating devices.
- **Sure-Snap® boxes for 2300BACD.** Provides flush look and ease of installation.
- **Snap-on cover.** Provides security with access to wiring for changes or additions.
- **Datacom connectivity options.** Accepts industry standard and proprietary devices from a wide range of manufacturers to provide a seamless and aesthetically pleasing interface for voice, data, audio, and video applications at the point of use.
- **cULus Listed.** File E90378 Raceway, E90377 Fittings.

PEP ecopassport®

Download this product's PEP ecopasport® environmental product declaration at www.legrand.us/resources-and-downloads. This declaration conforms with ISO 14025 and 14040 and is in alignment with EN 15804.

400, 800, 2300, 2300D Series Raceway System Layout



NOTE: Illustration shows product applications only. 2315 Tee Fitting cannot be used with 2300D Divided Raceway.

400, 800, 2300, 2300D Raceway Series Wire Fill Capacities for Power

WIRE SIZE THHN/THWN	O.D. Inches	(mm)	NUMBER OF CONDUCTORS 400BAC	800BAC	2300BAC	2300BACD†
14 AWG	0.111	(2.8)	5	6	15	7
12 AWG	0.130	(3.3)	3	5	14	6
10AWG	0.164	(4.2)	0	4	12	5


400, 800, 2300, 2300D Raceway Series Wire Fill Capacities for Communications

	CABLE/WIRE SIZE	O.D. inches	(mm)	40% FILL* 400	800	2300	2300D†
UNSHIELDED TWISTED PAIR	4-Pair, 24 AWG Cat. 3	0.190	(4.8)	1	3	11	5
	4-Pair, 24 AWG Cat. 5e	0.210	(5.3)	1	3	9	4
	4-Pair, 24 AWG Cat. 6	0.250	(6.3)	1	2	6	3
	4-Pair, 24 AWG Cat. 6a**	0.354	(9.0)	0	1	3	1
	25-Pair, 24 AWG	0.410	(10.4)	0	0	2	1
COAXIAL	RG6/U	0.270	(6.9)	0	1	5	2
FIBER	Zip Cord 0.118 x 0.157	(3 x 6)	1	3	12	6	
	Round 4 Strand Fiber	0.187	(4.8)	1	3	12	6
	Round 6 Strand Fiber	0.256	(6.5)	1	2	6	3

*** Wire capacity is reduced to allow for proper conductor bend radius and maximum permissible heat rise.**
**** Category 6 augmented (6a) cable for 10 gigabit ethernet – max allowed cable diameter per addenda No. 11 ANSI TIA/EIA 568-B.2.**
† each compartment.

400BAC, 800BAC, 2300BAC, 23000BACD Series Raceway Ordering Information


Catalog No./Item		Description/Specifications
400BAC	**400BAC-WH**	**Low profile, two-piece raceway with snap-on cover** – Available in 5' (1.525m and length. Supplied with wide adhesive tape along entire length of base.
800BAC	**800BAC-WH**	
2300BAC	**2300BAC-WH**	
2300BACD	**2300BACD-WH**	



400, 800, 2300, 2000D Series Fittings Ordering Information

Catalog No./Item	Description/Specifications


400WC
800WC
2300WC



Wire Clip – For holding conductors in place.

CAT NO.	A
400WC	1/2" (12.7mm)
800WC	1" (25mm)
2300WC	1" (25mm)


406
806
2306



Cover Clip – For covering joint where two pieces of 400BAC, 800BAC or 2300BAC Series Raceway cover come together.

CAT NO.	A
406	13/16" (20.6mm)
806	1" (25mm)
2306	2" (51mm)


410B
810B
2310B



Blank End Fitting – For closing open end of 400BAC, 800BAC, or 2300BAC Raceway Series.


CAT NO.	A	B	C
410B	13/16" (20.6mm)	1/2" (12.7mm)	3/8 (9.5mm)
810B	1 1/4" (32mm)	1/2" (12.7mm)	3/8 (9.5mm)
2310B	2 1/4" (57mm)	1" (25mm)	3/8 (9.5mm)

411*




90° Flat Elbow – For right angle turns on same surface.

415*



Tee – For branches at right angles.

417*




Internal Elbow – For surfaces at right angles.

NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish.
*** For 2300BAC and 2300BACD Raceway must be mitered to use 2311 and 2318. 2315 cannot be used in divided raceway.**

Catalog No./Item	Description/Specifications


418
818
2318*



90° External Elbow – For right angle turns around external corners.


CAT NO.	A
418	11/2 (38mm)
818	2" (51mm)
2318	2 1/2" (64mm)

PVC-1




PVC Cutter – Regular duty cutter. Ideal for use with small nonmetallic raceway.

810A2



Entrance End Fitting – For connecting 400 or 800 Series Raceway with 1/2" trade size conduit or armored cable. 1/2" trade size KO on end and bottom.


811
2311* **



90º Flat Elbow – For right angle turns on same surface.

CAT NO.	A
811	2 1/2" (64mm)
2311	4 3/16" (106mm)


815
2315* **



Tee – For right angles turns on same surface.

CAT NO.	A	B
815	4 1/8" (105mm)	2 3/4" (70mm)
2315	6" (152mm)	4 1/8" (105mm)


817
2317*



Internal Elbow – For surfaces at right angles.





CAT NO.	A
817	2" (51mm)
2317	2 1/2" (64mm)





889A



Reducing Connector (800-400) – For transitioning from 800 to 400 Series Raceway.



400, 800, 2300, 2000D Series Fittings Ordering Information (continued)


Catalog No./Item	Description/Specifications
2310A 	**Entrance End Fitting** – 1/2", 3/4", and 1" trade size KOs for feeding 2300 Series Raceway.
2310DFO 	**Bend Radius Divided Entrance End Fitting** – Divided fitting to feed 2300BAC and 2300BACD Series Raceway. Includes 1/2", 3/4" and 1" trade size KOs on back and top.
2311DFO 	**Bend Radius Divided Flat Elbow** – A 90° flat corner with integral dividers to provide 2" (51mm) cable bend radius for UTP and fiber optic installations**.**
2317DFO 	**Bend Radius Divided Internal Elbow** – A 90° internal corner with integral dividers to provide 2" (51mm) cable bend radius for UTP and fiber optic installations.

Catalog No./Item	Description/Specifications
2318DFO 	**Bend Radius Divided External Elbow** – A 90° external corner with integral dividers to provide 2" (51mm) cable bend radius for UTP and fiber optic installations.
2389 	**Reducing Connector (2300BAC-800BAC)** – For transitioning from 2300BAC to 800BAC Series Raceway.
2389A 	**Reducing Connector (2300BAC-400BAC)** – For transitioning from 2300BAC to 400BAC Series Raceway.
5474 	**Transition Tap Fitting** – Makes transition from 5400 Raceway to 400BAC, 800BAC, 2300BAC Series Raceway.

NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish.

400, 800, 2300, 2000D Series Communications Boxes Ordering Information (continued)

Catalog No./Item	Description/Specifications
CM-MMB-231 	**One Insert Multimedia Box** - Compatible with 400BAC and 800BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communication Modules.
CM-MMB-232 	**Two Insert FiberReady® Multimedia Box** - Compatible with 400BAC, 800BAC, and 2300BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communications Modules.

Catalog No./Item	Description/Specifications
CM-MMB-233 	**Three-Insert FiberReady® Multimedia Box** – Compatible with 400BAC, 800BAC and 2300BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communications Modules

400, 800, 2300 Series Raceway Sure-Snap® Device Boxes

- **Interchangeable covers and bases.** Provides installation flexibility.
- **Large knockout.** Accommodates many cable types and quantities.
- **Cover removes easily.** One twist of a screwdriver removes the cover for fast changes.
- **No screws to assemble.** The secure snap assembly requires fewer tools and parts, which means a shorter installation time.




Sure-Snap Device Boxes are available in a variety of sizes and depths.

400, 800, 2300 Series Raceway Sure-Snap® Device Boxes Ordering Information
(For Non-Divided Raceways)

Catalog No./Item | **Description/Specifications**


2344
2344-2



Extra Deep Device Box – 2344 one-gang, 2344-2 two-gang. 2344-2 base has rectangular KO to enable extension from existing single-gang flush wall box and 1/2" and 1" trade size concentric KOs. Accepts NEMA Faceplates

CAT #	GANG(s)	A	B	C
2344	1	4 3/4" (121mm)	3" (76mm)	2 3/4" (70mm)
2344-2	2	4.3/4" (121mm)	4 7/8" (124mm)	2 3/4" (70mm)

2347
2347-2




Device Box – 2347 one-gang, 2347-2 two-gang. For standard switches and devices. 2347 and 2347-2 Bases have rectangular KO to enable extension from existing flush wall box and 1/2" and 1" trade size concentric KOs. Accepts NEMA Faceplates

CAT #	GANG(S)	A	B	C
2347	1	4 3/4" (121mm)	3" (76mm)	1 3/8" (35mm)
2347-2	2	4 3/4" (121mm)	4 7/8" (124mm)	1 3/8" (35mm)

NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish.
All single-gang bases have a rectangular knockout on the base.

Catalog No./Item | **Description/Specifications**


2348
2348-2
2348-3



Deep Device Box – 2348 one-gang, 2348-2 two-gang, 2348-3 three-gang. For deeper switches and devices. 2348, 2348-2, and 2348-3 Bases have rectangular KO to enable extension from existing flush wall box and 1/2" and 1" concentric KOs. Accepts NEMA Faceplates.


CAT #	GANG(S)	A	B	C
2348	1	4 3/4" (121mm)	3" (76mm)	1 3/4" (35mm)
2348-2	2	4 3/4" (121mm)	4 7/8" (124mm)	1 3/4" (44mm)
2348-3	3	4 3/4" (121mm)	7" (178mm)	1 3/4" (44mm)

2348S/51






Shallow Device Box/ Extension Box – For shallow switches and receptacles. Base has rectangular KO. Accepts NEMA Faceplates.

2348AMP



Magnetic Deep Device Box (with Grommet) – For deeper switches and devices. Magnetic backing. Base has rectangular KO. Accepts NEMA Faceplates

400, 800, 2300 Series Raceway Round Fixture Boxes for Non-Divided Raceway Ordering Information



Item	Description	Cat. No.	Diameter	Depth	Specifications
	Blank Cover	2336	4 1/2" (114mm)	—	Use with any round nonmetallic device box to convert into junction box.
	Round Extension Box	2337A	5 1/2" (140mm)	1" (25mm)	For hanging fixtures, smoke/fire alarms and other security devices with 3 1/2" (89mm) or 4 1/16" (103mm) mounting centers. 5 1/2" (140mm) diameter with open base. Not for use with ceiling fans.
	Fixture Box	2338A	5 1/2" (140mm)	1" (25mm)	For hanging smoke/fire alarms and other security devices with 3 1/2" (89mm) or 4 1/16" (103mm) mounting centers. Not for use with ceiling fans.


NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish.

Sure-Snap® Device Boxes for 2300BACD Divided Series Raceway

The 2300BAC and 2300BACD Series Divided Raceway Box family provides two unique benefits; labor savings with "over-the-raceway" installation and Sure-Snap® device boxes. The 2348D and 2344D "over-the-raceway" design eliminates cutting the raceway base to mount boxes. The base snaps on anywhere along the raceway. The Sure-Snap integral device box of the 2344SD-2A combines aesthetics with labor savings. 5507 Series Faceplates, Pass & Seymour Activate Inserts, Wiremold Open System Communication Modules and Ortronics Series II and TracJack Modules snap directly into the Sure-Snap Device Box, eliminating the need for additional faceplates. The single-gang boxes accept standard NEMA faceplates.


Sure-Snap® Device Boxes for 2300BACD Divided Series Raceway Ordering Information

Catalog No./Item	Description/Specifications
2348D 	**Device Box** – For use with 2300BACD Divided Raceway. For mounting standard switches, receptacles and industry standard faceplates for communication devices. Accepts NEMA Faceplates.
2344D 	**Extra Deep Device Box** – For use with 2300BACD Divided Raceway when additional depth is required. For mounting standard switches, receptacles and industry standard faceplates for communication devices. Accepts NEMA Faceplates.









Catalog No./Item	Description/Specifications
2344SD-2A 	**Two-Gang Deep Divided Box** – A divided two-gang box for use with 2300D Series Raceway. Provides the ability to have both power and low voltage at a single point of use. Accepts 5507 Series Faceplates, Ortronics® TracJack & Series II Modules, Pass & Seymour® Activate™ Series Inserts, and Wiremold Open System Communication Modules.







Note: Not for use with NEMA Faceplates. CM-EPLA End Plates are required when using Wiremold Open System communication modules and Pass & Seymour® Activate inserts. S2-EPL End Plates are required when using Ortronics® Series II inserts. To mount Ortronics® TracJack modules, use 5507-4TJ or 5507-6TJ Faceplates.

2344SD-2 Over-the-Raceway Box Application



5507 Series Faceplates Ordering Information

Catalog No./Item	Description/Specifications
5507AD 	**Modular Furniture Adapter** – For mounting Activate modular furniture bezels and other modular furniture adapters. Not for use with rectangular (decorator) style devices.
5507B 	**Blank Faceplate** – For covering unused compartments in the device bracket.
5507D 	**Duplex Receptacle Faceplate** – For covering duplex style devices. Accepts 106 Frame.
5507R 	**Rectangular Receptacle Faceplate** – For covering rectangular decorator style devices.
5507S 	**Rectangular Spacer** – For mounting commercial device plates. Installs between the device bracket and a device.
5507SW 	**Switch Faceplate** – For covering standard toggle switches.
5507T1 	**Single Receptacle Faceplate** – For covering single receptacles – 1.59" (40mm) diameter.
5507T2 	**Single Receptacle Faceplate** – For covering single receptacles – 1.41" (36mm) diameter.

Catalog No./Item	Description/Specifications
5507RJ 	**Dual RJ11/RJ45 Connector Faceplate** – For mounting one or two RJ type connectors – has one opening and a KO for the other.
5507FRJ 	**Flush Dual RJ11/RJ45 Connector Faceplate** – Same as 5507RJ except the connectors are recessed to provide a flush installation.
5507-4TJ 	**Ortronics® Faceplate** – For mounting Ortronics® datacom inserts. Accepts four TracJack Devices.
5507-6TJ 	**Ortronics® Faceplate** – For mounting Ortronics® datacom inserts. Accepts six TracJack Devices.
CM-EPLA 	**End Plates** – Includes two outlet identification labels with clear covers and two matching screw covers. Required for mounting Pass & Seymour® Activate™ and Wiremold Open System communication modules into the 2344SD-2A.
S2-EPL 	**End Plates** – Includes two outlet identification labels with clear covers and two matching screw covers. Required for mounting Ortronics® Series II modules into the 2344SD-2A.

NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish, and "G" for Gray finish. Consult factory for custom colors.

Electrical Wiring Systems

60 Woodlawn Street
West Hartford, CT 06110
Phone: 1.877.BY.LEGRAND (295-3472)
www.legrand.us

570 Applewood Crescent
Vaughan, Ontario L4K 4B4
Phone:905.738.9195
www.legrand.ca

ED296R18 – Updated January 2016 – For latest specs visit www.legrand.us/wiremold

© Copyright 2016 Legrand All Rights Reserved

WIREMOLD®
400/800/2300 Series™ Raceway

Low Profile Design Combines Functionality With Aesthetics

Ideal for Low Voltage and Power Applications

400, 800, 2300 and 2300BACD Series™ Raceway, are a family of low-profile raceways that are designed for communication or power applications. 400, 800 and 2300 Raceway offer a single channel for either communication or power. And when power and low voltage services are both needed in a single raceway, the divided 2300BACD Raceway with it's low-profile design, is an easy-to-install option.

400,800,2300 and 2300BACD Raceways are an ideal solution for use in classrooms, offices, hospitality applications, or anywhere a small, secure, low profile raceway is needed.



2300D Series Raceway in a typical office application.


FEATURES & BENEFITS

- **Accommodates communication and/or power wiring.** Can be used for communications, computer lines, surveillance systems, fire alarms, outlets, and more.
- **Available in three sizes.** 400, 800, and 2300 sizes provide flexibility for meeting a variety of capacity and space requirements. Perfect for most small drops and horizontal runs to work stations.
- **Durable, textured PVC construction.** Available in ivory or white finish to blend with any decor. Also paintable using latex paint. Consult factory for custom color options.
- **Single- and dual-compartment low profile design.** Provides functionality and flexibility with aesthetics for single- or dual-service applications.
- **Adhesive backing for low voltage (under 50V) applications.** Allows base to be pressed onto mounting surface. Speeds installation.
- **Lightweight and easy to handle.** Saves time and labor costs. Standard 5' (1.525m) raceway lengths can be easily installed by one person. Custom lengths up to 10' (3.05m) are also available.
- **Divided FiberReady® fittings.** For use with 2300BAC and 2300BACD. Full capacity fittings provide 2" (51mm) bend radius.
- **Over-the-raceway box for 2300 and 2300D.** Boxes mount over continuous run of raceway base eliminating the need to cut raceway when locating devices.
- **Sure-Snap® boxes for 2300BACD.** Provides flush look and ease of installation.
- **Snap-on cover.** Provides security with access to wiring for changes or additions.
- **Datacom connectivity options.** Accepts industry standard and proprietary devices from a wide range of manufacturers to provide a seamless and aesthetically pleasing interface for voice, data, audio, and video applications at the point of use.
- **cULus Listed.** File E90378 Raceway, E90377 Fittings.

PEP ecopassport®

Download this product's PEP ecopasport® environmental product declaration at www.legrand.us/resources-and-downloads. This declaration conforms with ISO 14025 and 14040 and is in alignment with EN 15804.

400, 800, 2300, 2300D Series Raceway System Layout



NOTE: Illustration shows product applications only. 2315 Tee Fitting cannot be used with 2300D Divided Raceway.

400, 800, 2300, 2300D Raceway Series Wire Fill Capacities for Power

WIRE SIZE THHN/THWN	O.D. Inches	(mm)	NUMBER OF CONDUCTORS 400BAC	800BAC	2300BAC	2300BACD†
14 AWG	0.111	(2.8)	5	6	15	7
12 AWG	0.130	(3.3)	3	5	14	6
10AWG	0.164	(4.2)	0	4	12	5


400, 800, 2300, 2300D Raceway Series Wire Fill Capacities for Communications

	CABLE/WIRE SIZE	O.D. inches	(mm)	40% FILL* 400	800	2300	2300D†
UNSHIELDED TWISTED PAIR	4-Pair, 24 AWG Cat. 3	0.190	(4.8)	1	3	11	5
	4-Pair, 24 AWG Cat. 5e	0.210	(5.3)	1	3	9	4
	4-Pair, 24 AWG Cat. 6	0.250	(6.3)	1	2	6	3
	4-Pair, 24 AWG Cat. 6a**	0.354	(9.0)	0	1	3	1
	25-Pair, 24 AWG	0.410	(10.4)	0	0	2	1
COAXIAL	RG6/U	0.270	(6.9)	0	1	5	2
FIBER	Zip Cord 0.118 x 0.157	(3 x 6)	1	3	12	6	
	Round 4 Strand Fiber	0.187	(4.8)	1	3	12	6
	Round 6 Strand Fiber	0.256	(6.5)	1	2	6	3

*** Wire capacity is reduced to allow for proper conductor bend radius and maximum permissible heat rise.**
**** Category 6 augmented (6a) cable for 10 gigabit ethernet – max allowed cable diameter per addenda No. 11 ANSI TIA/EIA 568-B.2.**
† each compartment.

400BAC, 800BAC, 2300BAC, 23000BACD Series Raceway Ordering Information


Catalog No./Item		Description/Specifications
400BAC	**400BAC-WH**	**Low profile, two-piece raceway with snap-on cover** – Available in 5' (1.525m and length. Supplied with wide adhesive tape along entire length of base.
800BAC	**800BAC-WH**	
2300BAC	**2300BAC-WH**	
2300BACD	**2300BACD-WH**	



400, 800, 2300, 2000D Series Fittings Ordering Information

Catalog No./Item	Description/Specifications


400WC
800WC
2300WC



Wire Clip – For holding conductors in place.

CAT NO.	A
400WC	1/2" (12.7mm)
800WC	1" (25mm)
2300WC	1" (25mm)


406
806
2306



Cover Clip – For covering joint where two pieces of 400BAC, 800BAC or 2300BAC Series Raceway cover come together.

CAT NO.	A
406	13/16" (20.6mm)
806	1" (25mm)
2306	2" (51mm)


410B
810B
2310B



Blank End Fitting – For closing open end of 400BAC, 800BAC, or 2300BAC Raceway Series.


CAT NO.	A	B	C
410B	13/16" (20.6mm)	1/2" (12.7mm)	3/8 (9.5mm)
810B	1 1/4" (32mm)	1/2" (12.7mm)	3/8 (9.5mm)
2310B	2 1/4" (57mm)	1" (25mm)	3/8 (9.5mm)

411*




90° Flat Elbow – For right angle turns on same surface.

415*



Tee – For branches at right angles.

417*




Internal Elbow – For surfaces at right angles.

NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish.
*** For 2300BAC and 2300BACD Raceway must be mitered to use 2311 and 2318. 2315 cannot be used in divided raceway.**

Catalog No./Item	Description/Specifications


418
818
2318*



90° External Elbow – For right angle turns around external corners.


CAT NO.	A
418	11/2 (38mm)
818	2" (51mm)
2318	2 1/2" (64mm)

PVC-1




PVC Cutter – Regular duty cutter. Ideal for use with small nonmetallic raceway.

810A2



Entrance End Fitting – For connecting 400 or 800 Series Raceway with 1/2" trade size conduit or armored cable. 1/2" trade size KO on end and bottom.


811
2311* **



90º Flat Elbow – For right angle turns on same surface.

CAT NO.	A
811	2 1/2" (64mm)
2311	4 3/16" (106mm)


815
2315* **



Tee – For right angles turns on same surface.

CAT NO.	A	B
815	4 1/8" (105mm)	2 3/4" (70mm)
2315	6" (152mm)	4 1/8" (105mm)


817
2317*



Internal Elbow – For surfaces at right angles.





CAT NO.	A
817	2" (51mm)
2317	2 1/2" (64mm)





889A



Reducing Connector (800-400) – For transitioning from 800 to 400 Series Raceway.



400, 800, 2300, 2000D Series Fittings Ordering Information (continued)


Catalog No./Item	Description/Specifications
2310A 	**Entrance End Fitting** – 1/2", 3/4", and 1" trade size KOs for feeding 2300 Series Raceway.
2310DFO 	**Bend Radius Divided Entrance End Fitting** – Divided fitting to feed 2300BAC and 2300BACD Series Raceway. Includes 1/2", 3/4" and 1" trade size KOs on back and top.
2311DFO 	**Bend Radius Divided Flat Elbow** – A 90° flat corner with integral dividers to provide 2" (51mm) cable bend radius for UTP and fiber optic installations**.**
2317DFO 	**Bend Radius Divided Internal Elbow** – A 90° internal corner with integral dividers to provide 2" (51mm) cable bend radius for UTP and fiber optic installations.

Catalog No./Item	Description/Specifications
2318DFO 	**Bend Radius Divided External Elbow** – A 90° external corner with integral dividers to provide 2" (51mm) cable bend radius for UTP and fiber optic installations.
2389 	**Reducing Connector (2300BAC-800BAC)** – For transitioning from 2300BAC to 800BAC Series Raceway.
2389A 	**Reducing Connector (2300BAC-400BAC)** – For transitioning from 2300BAC to 400BAC Series Raceway.
5474 	**Transition Tap Fitting** – Makes transition from 5400 Raceway to 400BAC, 800BAC, 2300BAC Series Raceway.

NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish.

400, 800, 2300, 2000D Series Communications Boxes Ordering Information (continued)

Catalog No./Item	Description/Specifications
CM-MMB-231 	**One Insert Multimedia Box** - Compatible with 400BAC and 800BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communication Modules.
CM-MMB-232 	**Two Insert FiberReady® Multimedia Box** - Compatible with 400BAC, 800BAC, and 2300BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communications Modules.

Catalog No./Item	Description/Specifications
CM-MMB-233 	**Three-Insert FiberReady® Multimedia Box** – Compatible with 400BAC, 800BAC and 2300BAC Series Raceway. Accepts Pass & Seymour® Activate Inserts and Wiremold Open System Communications Modules

400, 800, 2300 Series Raceway Sure-Snap® Device Boxes

- **Interchangeable covers and bases.** Provides installation flexibility.
- **Large knockout.** Accommodates many cable types and quantities.
- **Cover removes easily.** One twist of a screwdriver removes the cover for fast changes.
- **No screws to assemble.** The secure snap assembly requires fewer tools and parts, which means a shorter installation time.




Sure-Snap Device Boxes are available in a variety of sizes and depths.

400, 800, 2300 Series Raceway Sure-Snap® Device Boxes Ordering Information
(For Non-Divided Raceways)

Catalog No./Item | **Description/Specifications**


2344
2344-2



Extra Deep Device Box – 2344 one-gang, 2344-2 two-gang. 2344-2 base has rectangular KO to enable extension from existing single-gang flush wall box and 1/2" and 1" trade size concentric KOs. Accepts NEMA Faceplates

CAT #	GANG(s)	A	B	C
2344	1	4 3/4" (121mm)	3" (76mm)	2 3/4" (70mm)
2344-2	2	4.3/4" (121mm)	4 7/8" (124mm)	2 3/4" (70mm)

2347
2347-2




Device Box – 2347 one-gang, 2347-2 two-gang. For standard switches and devices. 2347 and 2347-2 Bases have rectangular KO to enable extension from existing flush wall box and 1/2" and 1" trade size concentric KOs. Accepts NEMA Faceplates

CAT #	GANG(S)	A	B	C
2347	1	4 3/4" (121mm)	3" (76mm)	1 3/8" (35mm)
2347-2	2	4 3/4" (121mm)	4 7/8" (124mm)	1 3/8" (35mm)

NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish.
All single-gang bases have a rectangular knockout on the base.

Catalog No./Item | **Description/Specifications**


2348
2348-2
2348-3



Deep Device Box – 2348 one-gang, 2348-2 two-gang, 2348-3 three-gang. For deeper switches and devices. 2348, 2348-2, and 2348-3 Bases have rectangular KO to enable extension from existing flush wall box and 1/2" and 1" concentric KOs. Accepts NEMA Faceplates.


CAT #	GANG(S)	A	B	C
2348	1	4 3/4" (121mm)	3" (76mm)	1 3/4" (35mm)
2348-2	2	4 3/4" (121mm)	4 7/8" (124mm)	1 3/4" (44mm)
2348-3	3	4 3/4" (121mm)	7" (178mm)	1 3/4" (44mm)

2348S/51






Shallow Device Box/ Extension Box – For shallow switches and receptacles. Base has rectangular KO. Accepts NEMA Faceplates.

2348AMP



Magnetic Deep Device Box (with Grommet) – For deeper switches and devices. Magnetic backing. Base has rectangular KO. Accepts NEMA Faceplates

400, 800, 2300 Series Raceway Round Fixture Boxes for Non-Divided Raceway Ordering Information



Item	Description	Cat. No.	Diameter	Depth	Specifications
	Blank Cover	2336	4 1/2" (114mm)	—	Use with any round nonmetallic device box to convert into junction box.
	Round Extension Box	2337A	5 1/2" (140mm)	1" (25mm)	For hanging fixtures, smoke/fire alarms and other security devices with 3 1/2" (89mm) or 4 1/16" (103mm) mounting centers. 5 1/2" (140mm) diameter with open base. Not for use with ceiling fans.
	Fixture Box	2338A	5 1/2" (140mm)	1" (25mm)	For hanging smoke/fire alarms and other security devices with 3 1/2" (89mm) or 4 1/16" (103mm) mounting centers. Not for use with ceiling fans.


NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish.

Sure-Snap® Device Boxes for 2300BACD Divided Series Raceway

The 2300BAC and 2300BACD Series Divided Raceway Box family provides two unique benefits; labor savings with "over-the-raceway" installation and Sure-Snap® device boxes. The 2348D and 2344D "over-the-raceway" design eliminates cutting the raceway base to mount boxes. The base snaps on anywhere along the raceway. The Sure-Snap integral device box of the 2344SD-2A combines aesthetics with labor savings. 5507 Series Faceplates, Pass & Seymour Activate Inserts, Wiremold Open System Communication Modules and Ortronics Series II and TracJack Modules snap directly into the Sure-Snap Device Box, eliminating the need for additional faceplates. The single-gang boxes accept standard NEMA faceplates.


Sure-Snap® Device Boxes for 2300BACD Divided Series Raceway Ordering Information

Catalog No./Item	Description/Specifications
2348D 	**Device Box** – For use with 2300BACD Divided Raceway. For mounting standard switches, receptacles and industry standard faceplates for communication devices. Accepts NEMA Faceplates.
2344D 	**Extra Deep Device Box** – For use with 2300BACD Divided Raceway when additional depth is required. For mounting standard switches, receptacles and industry standard faceplates for communication devices. Accepts NEMA Faceplates.









Catalog No./Item	Description/Specifications
2344SD-2A 	**Two-Gang Deep Divided Box** – A divided two-gang box for use with 2300D Series Raceway. Provides the ability to have both power and low voltage at a single point of use. Accepts 5507 Series Faceplates, Ortronics® TracJack & Series II Modules, Pass & Seymour® Activate™ Series Inserts, and Wiremold Open System Communication Modules.







Note: Not for use with NEMA Faceplates. CM-EPLA End Plates are required when using Wiremold Open System communication modules and Pass & Seymour® Activate inserts. S2-EPL End Plates are required when using Ortronics® Series II inserts. To mount Ortronics® TracJack modules, use 5507-4TJ or 5507-6TJ Faceplates.

2344SD-2 Over-the-Raceway Box Application



5507 Series Faceplates Ordering Information

Catalog No./Item	Description/Specifications
5507AD 	**Modular Furniture Adapter** – For mounting Activate modular furniture bezels and other modular furniture adapters. Not for use with rectangular (decorator) style devices.
5507B 	**Blank Faceplate** – For covering unused compartments in the device bracket.
5507D 	**Duplex Receptacle Faceplate** – For covering duplex style devices. Accepts 106 Frame.
5507R 	**Rectangular Receptacle Faceplate** – For covering rectangular decorator style devices.
5507S 	**Rectangular Spacer** – For mounting commercial device plates. Installs between the device bracket and a device.
5507SW 	**Switch Faceplate** – For covering standard toggle switches.
5507T1 	**Single Receptacle Faceplate** – For covering single receptacles – 1.59" (40mm) diameter.
5507T2 	**Single Receptacle Faceplate** – For covering single receptacles – 1.41" (36mm) diameter.

Catalog No./Item	Description/Specifications
5507RJ 	**Dual RJ11/RJ45 Connector Faceplate** – For mounting one or two RJ type connectors – has one opening and a KO for the other.
5507FRJ 	**Flush Dual RJ11/RJ45 Connector Faceplate** – Same as 5507RJ except the connectors are recessed to provide a flush installation.
5507-4TJ 	**Ortronics® Faceplate** – For mounting Ortronics® datacom inserts. Accepts four TracJack Devices.
5507-6TJ 	**Ortronics® Faceplate** – For mounting Ortronics® datacom inserts. Accepts six TracJack Devices.
CM-EPLA 	**End Plates** – Includes two outlet identification labels with clear covers and two matching screw covers. Required for mounting Pass & Seymour® Activate™ and Wiremold Open System communication modules into the 2344SD-2A.
S2-EPL 	**End Plates** – Includes two outlet identification labels with clear covers and two matching screw covers. Required for mounting Ortronics® Series II modules into the 2344SD-2A.

NOTE: No suffix denotes ivory finish. Add "–WH" suffix for white finish, and "G" for Gray finish. Consult factory for custom colors.

Electrical Wiring Systems

60 Woodlawn Street
West Hartford, CT 06110
Phone: 1.877.BY.LEGRAND (295-3472)
www.legrand.us

570 Applewood Crescent
Vaughan, Ontario L4K 4B4
Phone:905.738.9195
www.legrand.ca

ED296R18 – Updated January 2016 – For latest specs visit www.legrand.us/wiremold

© Copyright 2016 Legrand All Rights Reserved