


## INSULATING PLASTIC BUSHINGS

105°C FLAME RETARDANT

THERMOPLASTIC

| CAT# | A    | B    |
|------|------|------|
| 831  | 1.06 | .43  |
| 832  | 1.31 | .43  |
| 833  | 1.59 | .48  |
| 834  | 1.96 | .56  |
| 835  | 2.18 | .56  |
| 836  | 2.68 | .59  |
| 837  | 3.25 | .72  |
| 838  | 3.87 | .75  |
| 839  | 4.37 | .77  |
| 840  | 5.00 | .77  |
| 840A | 6.25 | 1.00 |
| 840B | 7.50 | 1.00 |

| TOPAZ CAT # | UPC#  | SIZE   | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------|----------|-----------|----------|
| 831         | 18450 | 1/2"   | 100      | 1000      | 6        |
| 832         | 18460 | 3/4"   | 100      | 1000      | 9        |
| 833         | 18470 | 1"     | 50       | 500       | 11       |
| 834         | 18480 | 1 1/4" | 25       | 250       | 5        |
| 835         | 18490 | 1 1/2" | 25       | 250       | 7        |
| 836         | 18500 | 2"     | 20       | 200       | 12       |
| 837         | 18510 | 2 1/2" | —        | 50        | 5        |
| 838         | 18520 | 3"     | —        | 25        | 3        |
| 839         | 18530 | 3 1/2" | —        | 25        | 5        |
| 840         | 18540 | 4"     | —        | 10        | 7        |
| 840A        | 18550 | 5"     | —        | 10        | 3        |
| 840B        | 18560 | 6"     | —        | 10        | 4        |



## RIGID BUSHINGS INSULATED

• 105° C. THERMOPLASTIC LINERS

ZINC DIE CAST

| CAT# | A     | B    |
|------|-------|------|
| 311  | 1.053 | .394 |
| 312  | 1.327 | .394 |
| 313  | 1.584 | .477 |
| 314  | 1.952 | .503 |
| 315  | 2.201 | .522 |
| 316  | 2.693 | .564 |
| 317  | 3.235 | .866 |
| 318  | 3.855 | .866 |
| 319  | 4.359 | .866 |
| 320  | 5.011 | .866 |

| TOPAZ CAT # | UPC#  | SIZE   | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------|----------|-----------|----------|
| 311         | 12730 | 1/2"   | 100      | 1000      | 30       |
| 312         | 12740 | 3/4"   | 50       | 500       | 20       |
| 313         | 12750 | 1"     | 50       | 500       | 40       |
| 314         | 12760 | 1 1/4" | 25       | 250       | 25       |
| 315         | 12770 | 1 1/2" | 25       | 250       | 30       |
| 316         | 12780 | 2"     | —        | 100       | 14       |
| 317         | 12790 | 2 1/2" | —        | 50        | 20       |
| 318         | 12800 | 3"     | —        | 25        | 12       |
| 319         | 12810 | 3 1/2" | —        | 25        | 14       |
| 320         | 12820 | 4"     | —        | 10        | 6        |




| CAT#  | A     | B     |
|-------|-------|-------|
| 311M  | 1.223 | .506  |
| 312M  | 1.498 | .547  |
| 313M  | 1.818 | .662  |
| 314M  | 2.423 | .735  |
| 315M  | 2.512 | .808  |
| 316M  | 3.053 | .808  |
| 317M  | 3.624 | .958  |
| 318M  | 4.172 | 1.052 |
| 319M  | 4.767 | 1.169 |
| 320M  | 5.321 | 1.178 |
| 320AM | 6.15  | 1.30  |
| 320BM | 7.19  | 1.30  |

| TOPAZ CAT # | UPC#  | SIZE   | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------|----------|-----------|----------|
| 311M        | 12830 | 1/2"   | 100      | 1000      | 20       |
| 312M        | 12840 | 3/4"   | 50       | 500       | 20       |
| 313M        | 12850 | 1"     | 50       | 500       | 40       |
| 314M        | 12860 | 1 1/4" | 25       | 250       | 43       |
| 315M        | 12870 | 1 1/2" | 25       | 100       | 25       |
| 316M        | 12880 | 2"     | 10       | 100       | 30       |
| 317M        | 12890 | 2 1/2" | —        | 50        | 20       |
| 318M        | 12900 | 3"     | —        | 25        | 13       |
| 319M        | 12910 | 3 1/2" | —        | 25        | 18       |
| 320M        | 12920 | 4"     | —        | 10        | 10       |
| 320AM       | 12922 | 5"     | —        | 10        | 25       |
| 320BM       | 12924 | 6"     | —        | 10        | 35       |

MALLEABLE IRON






## INSULATING PLASTIC BUSHINGS

105°C FLAME RETARDANT

THERMOPLASTIC

| CAT# | A    | B    |
|------|------|------|
| 831  | 1.06 | .43  |
| 832  | 1.31 | .43  |
| 833  | 1.59 | .48  |
| 834  | 1.96 | .56  |
| 835  | 2.18 | .56  |
| 836  | 2.68 | .59  |
| 837  | 3.25 | .72  |
| 838  | 3.87 | .75  |
| 839  | 4.37 | .77  |
| 840  | 5.00 | .77  |
| 840A | 6.25 | 1.00 |
| 840B | 7.50 | 1.00 |

| TOPAZ CAT # | UPC#  | SIZE   | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------|----------|-----------|----------|
| 831         | 18450 | 1/2"   | 100      | 1000      | 6        |
| 832         | 18460 | 3/4"   | 100      | 1000      | 9        |
| 833         | 18470 | 1"     | 50       | 500       | 11       |
| 834         | 18480 | 1 1/4" | 25       | 250       | 5        |
| 835         | 18490 | 1 1/2" | 25       | 250       | 7        |
| 836         | 18500 | 2"     | 20       | 200       | 12       |
| 837         | 18510 | 2 1/2" | —        | 50        | 5        |
| 838         | 18520 | 3"     | —        | 25        | 3        |
| 839         | 18530 | 3 1/2" | —        | 25        | 5        |
| 840         | 18540 | 4"     | —        | 10        | 7        |
| 840A        | 18550 | 5"     | —        | 10        | 3        |
| 840B        | 18560 | 6"     | —        | 10        | 4        |



## RIGID BUSHINGS INSULATED

• 105° C. THERMOPLASTIC LINERS

ZINC DIE CAST

| CAT# | A     | B    |
|------|-------|------|
| 311  | 1.053 | .394 |
| 312  | 1.327 | .394 |
| 313  | 1.584 | .477 |
| 314  | 1.952 | .503 |
| 315  | 2.201 | .522 |
| 316  | 2.693 | .564 |
| 317  | 3.235 | .866 |
| 318  | 3.855 | .866 |
| 319  | 4.359 | .866 |
| 320  | 5.011 | .866 |

| TOPAZ CAT # | UPC#  | SIZE   | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------|----------|-----------|----------|
| 311         | 12730 | 1/2"   | 100      | 1000      | 30       |
| 312         | 12740 | 3/4"   | 50       | 500       | 20       |
| 313         | 12750 | 1"     | 50       | 500       | 40       |
| 314         | 12760 | 1 1/4" | 25       | 250       | 25       |
| 315         | 12770 | 1 1/2" | 25       | 250       | 30       |
| 316         | 12780 | 2"     | —        | 100       | 14       |
| 317         | 12790 | 2 1/2" | —        | 50        | 20       |
| 318         | 12800 | 3"     | —        | 25        | 12       |
| 319         | 12810 | 3 1/2" | —        | 25        | 14       |
| 320         | 12820 | 4"     | —        | 10        | 6        |



| CAT#  | A     | B     |
|-------|-------|-------|
| 311M  | 1.223 | .506  |
| 312M  | 1.498 | .547  |
| 313M  | 1.818 | .662  |
| 314M  | 2.423 | .735  |
| 315M  | 2.512 | .808  |
| 316M  | 3.053 | .808  |
| 317M  | 3.624 | .958  |
| 318M  | 4.172 | 1.052 |
| 319M  | 4.767 | 1.169 |
| 320M  | 5.321 | 1.178 |
| 320AM | 6.15  | 1.30  |
| 320BM | 7.19  | 1.30  |

| TOPAZ CAT # | UPC#  | SIZE   | UNIT CTN | SHIP CASE | WT/ CASE |
|-------------|-------|--------|----------|-----------|----------|
| 311M        | 12830 | 1/2"   | 100      | 1000      | 20       |
| 312M        | 12840 | 3/4"   | 50       | 500       | 20       |
| 313M        | 12850 | 1"     | 50       | 500       | 40       |
| 314M        | 12860 | 1 1/4" | 25       | 250       | 43       |
| 315M        | 12870 | 1 1/2" | 25       | 100       | 25       |
| 316M        | 12880 | 2"     | 10       | 100       | 30       |
| 317M        | 12890 | 2 1/2" | —        | 50        | 20       |
| 318M        | 12900 | 3"     | —        | 25        | 13       |
| 319M        | 12910 | 3 1/2" | —        | 25        | 18       |
| 320M        | 12920 | 4"     | —        | 10        | 10       |
| 320AM       | 12922 | 5"     | —        | 10        | 25       |
| 320BM       | 12924 | 6"     | —        | 10        | 35       |

MALLEABLE IRON

