

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



88C Wway 8X8 N1 Conn Cooper B-Line/Cable Tray

Catalog Number 88C

Manufacturer Cooper B-Line/Cable Tray

Description Eaton B-Line Series Wireway Connector, Connector, Wireway

Connector, Nema 1, Galvanized Steel Finish, 8" X 8"

Weight per unit 0.7299 (lbs/each)

Product Category Nema Type 1 Wireway & Fittings

Features

Cover Type SCREW

dimensions 8.0000 IN X 7.9300 IN X 8.0000 IN

Material Steel

Material, Color, and Finish

Finish PLAIN (NO FINISH)

Dimensions and Weight

Height 8.00 In
Width 8.00 In

Descriptions

Description WWAY 8X8 N1 CONN

extra long description B-LINE 88 C WIREWAY CONNECTOR 8X8

Features Eaton's B-Line series wiring troughs provide reliable

environmental protection and are used to house runs of control and power cable in wiring, junction, pull, and termination

applications.

Long Description Eaton B-Line series wireway connector, Connector, Wireway

connector, NEMA 1, Galvanized steel finish, 8" X 8"

Product Type Wireway Connector 8X8

Manufacturer Information

Brand Eaton

GTIN 00782051109054

Manufacturers Part Number 88 C

UPC 782051109054

Taxonomies, Classifications, and Categories

Category Description STEEL WIRE WAY JUNCTION BOXES

Type Wireway connector

Packaging

Carton 1
Package 10
Weight Per each 0.7299

Uses, Certifications, and Standards

es, cei tiiications, and standards	
Application	Commercial / Institutional Buildings / Structures - Commercial / Institutional Buildings / Structures - OtherInd Facilities & Factories - Facility: Safety and Security SystemsCommercial / Institutional Buildings / Structures - Safety and Security SystemsCommercial / Institutional Buildings / Structures - Power Distribution and ControlsInd Facilities & Factories - Facility: Power Distribution and ControlInd Facilities & Factories - Facility: Automation and MonitoringCommercial / Institutional Buildings / St
Enclosure	NEMA 1, IP30
standard	UL Listed,CSA C22.2.,NEMA