

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## AC12C16 Encl 12X16X9 N12 Consolet Cooper B-Line/Cable Tray

Catalog Number	AC12C16
Manufacturer	Cooper B-Line/Cable Tray
Description	Eaton B-Line Series Consolet Enclosures, 12" Height, 9.12" Length, 16" Width, Nema 12, Hinged Cover, Ac Concolet, Surface Mount, Medium Single Door, External Mounting Feet, Carbon Steel, Oil-Resistant Gasket
Weight per unit	16.5 (lbs/each)
Product Category	Nema Types 12 & 13 Metallic En
Features	
Material	Polyester Powder Coated Over Wash and Phosphate Undercoat 14 Gauge Steel
Material, Color, and Finish Color	Gray
Dimensions and Weight	
Depth	9.12
Height	12
Size	16.00 In Width X 9.12 In Depth X 12.00 In Height
Width	16
Descriptions	
Description	ENCL 12X16X9 N12 CONSOLET
extra long description	B-LINE AC-12C16 TYPE 12 CONSOLET, 1
Features	Eaton's B-Line series consolets provide reliable environmental protection and house electrical controls and instruments. They are designed with an angled front surface for pushbuttons, pilot lights, switches, or other monitoring devices.
Long Description	Eaton B-Line series consolet enclosures, 12" height, 9.12" length 16" width, NEMA 12, Hinged cover, AC concolet, Surface mount, Medium single door, External mounting feet, Carbon steel, Oil-resistant gasket
Product Type	Type 12 Consolet, 12X16
Manufacturer Information	
Brand	Eaton
GTIN	00782051410020
Manufacturers Part Number	AC12C16
UPC	782051410020

## **Taxonomies, Classifications, and Categories**

Category Description	STEEL JUNCTION BOXES
Туре	Consolet enclosures



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	16.51
Uses, Certifications, and Standard	ds
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
standard	NEMA,UL 508A,CSA C22.2.