

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



AF190301113 156A, 100-250V, 3P Contactor Industrial Connections &

Catalog Number	AF190301113
Manufacturer	Industrial Connections &
Description	A 3-Phase Contactor Suitable For Various Applications Such As Motor Starting, Isolation, By-Pass and Distribution Application Up to Max 1000 V. Operated With Wide Control Voltage Range 100-250 V, 50/60 HZ and DC
Weight per unit	7.2 (lbs/each)
Product Category	IEC Contactors
Dimensions and Weight	
Size	105x196x152mm
Descriptions	
Description	156A, 100-250V, 3P CONTACTOR
extra long description	ABB AF190-30-11-13 CTR,3P,156A,100-
Long Description	A 3-phase Contactor suitable for various applications such as
	Motor starting, Isolation, By-pass and Distribution application up
	to max 1000 V. Operated with wide control voltage range
Draduct Tuna	100-250 V, 50/60 Hz and DC CTR, 3P, 156A, 100-250VAC/DC, 1/1
Product Type Special Features	Terminal type: Screw terminals
	Terminal type: serew terminals
Manufacturer Information Brand	ABB
GTIN	00888614152670
Manufacturers Part Number	
UPC	888614152670
Taxonomies, Classifications, and C	
Category Description	
Туре	
Packaging	
Carton	1
Weight Per each	7.15
Uses, Certifications, and Standard	s
Application	Suitable for various applications such as Motor starting, Isolation, By-pass and Distribution application up to max 1000 V.
Operating Temperature	-25 to +50 Degrees C
standard	CB, CE, RINA, RoHS