

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **AF30301113 AF30-30-11-13 100-250V50** *Industrial Connections &*

Industrial Connections	&
Catalog Number	AF30301113
Manufacturer	Industrial Connections &
Description	AF30 Contactors Are Used For Controlling Power Circuits Up to 690 V Ac and 220 V DC. They Are Mainly Used For Controlling 3-Phase Motors, Non-Inductive or Slightly Inductive Loads. Af Contactors Include An Electronic Coil Interface Accepting A Wide Control Voltage Uc Min Uc Max. Only Four Coils Cover Control Voltages Between 24500 V 50/60 HZ or 20500 V DC. Af Contactors Can Manage Large Control Voltage Variations. One Coil Can Be Used For Different Control Voltages Used Worldwide Without Any
Weight per unit	0.8500 (lbs/each)
Product Category	IEC Contactors
Descriptions	
Description	AF30-30-11-13 100-250V50
extra long description	ABB AF30-30-11-13 AF30-30-11-13 100
Long Description	AF30 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF contactors include an electronic coil interface accepting a wide control voltage Uc min Uc max. Only four coils cover control voltages between 24500 V 50/60 Hz or 20500 V DC. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any
Product Type	AF30-30-11-13 100-250V50/60HZ-DC CO
Manufacturer Information	
Brand	ABB
GTIN	00888614244276
Manufacturers Part Number	AF30-30-11-13
UPC	888614244276
Taxonomies, Classifications, and Category Description	Categories IEC/FREEDOM CONTACTOR
Packaging	
Carton	1
Weight Per each	0.85
. r. x. <b>y</b> x x x x x	