

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



AGC2R 2A 250V 1/4X1-1/4 Rohs Fa Glass Fuse

Bussmann Fuses

LED .	
Catalog Number	AGC2R
Manufacturer	Bussmann Fuses
Description	Fuse, Fast Acting Fuse Speed, 120/3.6K S Response Time, Ferrule
	End X Ferrule End Connection, 2 A, 250 V Ac, Glass (Body);Brass(
	End Cap) Material, Ferrule Terminal, 1/4 In Diameter, 1-1/4 In
	Overall Length, 0.006 LB
Weight per unit	0.0060 (lbs/each)
Product Category	Small Dimension Fuses
eatures	
amperage rating	2 A
connection	Ferrule End X Ferrule End
dimensions	1.2500 IN X 0.2500 IN X 0.2500 IN
Response Time	60 min at 135%, 120 sec at 200%
imensions and Weight	
Size	1/4 In Diameter X 1-1/4 In Length
escriptions	
Description	2A 250V 1/4X1-1/4 ROHS FA GLASS FUSE
extra long description	EFSE AGC-2-R BUSS SMALL DIMENSION F
Features	Fast-acting, glass tube 1/4" x 1-1/4" ferrule fuse designed to UL
- teatures	248-14 for overcurrent protection of electronic circuits. Install
	into a Bussmann Series fuse holder, block, or fuse clip, or
	purchase with available axial leads for thru-hole installation.
	Eaton's AGC fast-acting, glass tube 1/4" x 1-1/4" ferrule fuses are
	designed to UL 248-14 for overcurrent protection of electronic
	circuits. Order in cartridge fuse format and install into a
	Bussmann Series fuse holder, block, or fuse clip, or purchase w
Special Features	Interrupt Rating 100 Amp at 250 Vac, 10000 Amp at 125 Vac,
	Material Glass Tube, Nickel Plated Brass Endcap, ROHS Complian
Nanufacturer Information	
Brand	Eaton Bussmann series
GTIN	00051712655057
UPC	051712655057
axonomies, Classifications, and	Categories
Category Description	
Туре	Fast-acting glass tube fuse
ackaging	
Carton	5



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

standard

CE Marked, RoHS Compliant