



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## AH420C7W Conn Pin&Sleeve 20A 480V 3PH 3P4W WT RD *Eaton Wiring Devices*

Catalog Number	AH420C7W
Manufacturer	Eaton Wiring Devices
Description	Connector Pin and Sleeve 20 Amp 480 Volt 3 Phase 3 Pole 4 Wire WT Red
Weight per unit	40.0 (lbs/each)
Product Category	Pin & Sleeve Devices

### Features

amperage rating	20
connection	Pin & Sleeve
dimensions	8.5000 IN X 4.3750 IN X 4.3750 IN
Material	Nylon
media	Yes
Phase	3
Poles	3
Voltage Rating	3Ø 480V/AC
Wire Size	0.333-0.775

### Material, Color, and Finish

Color	Blue & Gray
-------	-------------

### Dimensions and Weight

Size	8.5 x 4.375 x 4.375
------	---------------------

### Descriptions

Description	CONN PIN&SLEEVE 20A 480V 3PH 3P4W WT RD
extra long description	CRS-H AH420C7W CONN PIN AND SLEEVE
Features	Eaton's Arrow Hart full line of pin and sleeve devices offer sturdy nylon construction, rugged design with corrosion resistant components for lasting electrical performance, and watertight sealing that provides IP69K protection so you can feel confident in even the most severe washdown environments.
Long Description	CONNECTOR PIN AND SLEEVE 20 AMP 480 VOLT 3 PHASE 3 POLE 4 WIRE WT RED
Product Type	Conn Pin and Sleeve 20A 480V 3PH 3P4W WT
Special Features	Watertight P&S connectors

### Manufacturer Information

Brand	Eaton
GTIN	00326647334750
Manufacturers Part Number	AH420C7W
UPC	032664733475



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	CONNECTOR

## Packaging

Carton	1
Package	40
Weight Per each	40

## Uses, Certifications, and Standards

Application	IEC 309 Products
environmental conditions	IP67 & IP69k
Mounting	Cable
standard	IEC, UL, CSA