

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



ALF381000 3/8" Alu Flexible Conduit 1000' Southwire Company

Catalog Number ALF381000 Manufacturer Southwire Company UI Reduced Wall Aluminum Type RW Fac, 5600 Series, Description Lightweight Reduced Wall Aluminum Flexible Conduit. Premium Aluminum Alloy. Interlocking Design. 3/8 Inch Diameter, 1000 Foot Reel 0.0700 (lbs/ft) Weight per unit Product Category Flexible Metallic Conduit **Features** 0.375/0.393 Inside Diameter Material Aluminum outside diameter 0.560/0.610 Material, Color, and Finish Color Gray Finish Aluminum Alloy **Dimensions and Weight** 1000 Length



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

| Descriptions | |
|------------------------------------|--|
| Description | 3/8" ALU FLEXIBLE CONDUIT 1000' |
| extra long description | AFC 5601-60-00 3/8 ALUM FLEX 1000' |
| Features | Reduced wall Aluminum flexible conduit is made with an aluminum alloy strip of uniform gauge for an excellent combination of strength and durability. Reduced wall flexible conduit can be used in flexible metal raceway systems for electrical power, communication cables, motor leads, listed assemblies and wire fixtures and manufactured wiring systems. The Reduced Wall product must additionally meet an impact performance test. Both constructions are UL listed for use in |
| Long Description | accordance with the NEC. UL Reduced Wall Aluminum Type RW FAC, 5600 Series, Lightweight Reduced Wall Aluminum Flexible Conduit. Premium aluminum alloy. Interlocking design. 3/8 inch Diameter, 1000 Foot Reel |
| Product Type | 3/8 Alum Flex 1000' RL |
| Short Description | 3/8 ALUM FLEX 1000' RL |
| Special Features | Interlocking design; Corrosion resistant; Cable tray installations per NEC; Environmental air-handling space installation NEC 300.22; UL Classified 1, 2 and 3-hour Through-Penetration Fire Systems UL File R14141 |
| Manufacturer Information | |
| Brand | Flexible Conduit |
| GTIN | 00077680119070 |
| Manufacturers Part Number | 5601-60-00 |
| UPC | 077680119070 |
| Taxonomies, Classifications, and C | atenories |
| Category Description | ALUMINUM GREENFIELD, Flexible Conduit |
| Туре | Flexible Aluminum Conduit |
| Trade Size | |
| Trade Size | 3/8 |
| | 570 |
| Packaging | 1000 |
| Carton | 1000 |
| Weight | 0.06 |
| Weight Per foot | 0.07 |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

| Application | For Electrical Power, Control And Communication Cables, Motor Leads, Listed Assemblies, Listed Wire Fixtures, Manufactured |
|-------------|---|
| | Wiring Systems |
| standard | UL 1, UL 1479 File Numbers E11831 And R14141, CSA File |
| | Number 15035, Federal Specification WW-C-566C, (Now |
| | Superseded By UL 1), NEC 250.118(6), 300.22(C), 348, 430.123, |
| | 501.4(B)(2), 645.5 |