

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



APR6465 3W-4P RCPT *Crouse-Hinds*

Catalog Number	APR6465
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Arktite Apr Connector, 60A,
	0.50-1.45", Three-Wire, Four-Pole, 50-400 HZ, Style 2,
	Copper-Free Aluminum, 600 Vac/250 VDC
Weight per unit	
Product Category	Pin & Sleeve Devices
Features	
amperage rating	60
connection	Pressure, Crimp/Solder
dimensions	8.2500 IN X 2.9400 IN X 2.9400 IN
Material	Copper-Free Aluminum
Poles	4
Voltage Rating	600 VAC AT 50 TO 400 HZ, 250 VDC
Wire Size	6 To 4 AWG (Building), 8 To 4 AWG (Extra Flex)
Dimensions and Weight	
Length	8-1/4
Descriptions	
Description	3W-4P RCPT
extra long description	CRS-H APR6465 60A 3W4P ARKTE CONNEC
Features	Crouse-Hinds series Arktite plugs and receptacles are used to supply power to portable electrically operated devices, such as motor generator sets, compressors, heating and cooling units, welders, conveyors, lighting systems and similar equipment. Also used where temporary power is needed, such as at trailers, building units, heavy machinery or wherever electrical loads must be quickly disconnected from power source.
Long Description	Eaton Crouse-Hinds series Arktite APR connector, 60A, 0.50-1.45", Three-wire, four-pole, 50-400 Hz, Style 2, Copper-free aluminum, 600 Vac/250 Vdc
Product Type	60A 3W4P Arkte Connect .50 to 1.45
Special Features	Watertight, Grounding Style 2, Cable Range 0.50 To 1.45 In

Diameter, NEMA 4 Enclosure



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Informatio	Ma	anuí	actur	er Inf	forma	tion
-------------------------	----	------	-------	--------	-------	------

Brand	Eaton
GTIN	00782274056005
Manufacturers Part Number	APR6465
UPC	782274056005

Taxonomies, Classifications, and Categories

Category Description	Residential GFCI devices
Type	CONNECTOR

Packaging

······································	
Carton	1
Weight Per each	3.9

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
standard	UL 1682, UL 1686, CSA C22.2, CE