

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## AR642 60A Pin & Sleeve Recpt 3W 4P 250VDC/600vac Crouse-Hinds

Catalog Number	AR642
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Arktite Ar Receptacle, 60A,
	Three-Wire, Four-Pole, 50-400 HZ, Style 2, Copper-Free
	Aluminum, Spring Door, 600 Vac/250 VDC
Weight per unit	2.7 (lbs/each)
Product Category	Pin & Sleeve Devices
Features	
dimensions	4.2500 IN X 4.2500 IN X 4.2500 IN
insulation	Fiberglass-Reinforced Polyester
Voltage Rating	600 VAC AT 50 TO 400 HZ, 250 VDC
Wire Size	6 To 4 AWG (Building), 8 To 4 AWG (Extra Flex)
Dimensions and Weight	
Height	5-1/4
Width	4-1/4
Descriptions	
Description	60A PIN & SLEEVE RECPT 3W 4P 250VDC/600VAC
extra long description	CRS-H AR642 60A 3W4P ARKTE RCPT HOU
Features	Crouse-Hinds series Arktite plugs and receptacles are used to
	supply power to portable electrically operated devices, such as
	motor generator sets, compressors, heating and cooling units,
	welders, conveyors, lighting systems and similar equipment. Also
	used where temporary power is needed, such as at trailers,
	building units, heavy machinery or wherever electrical loads must
	be quickly disconnected from power source.
Long Description	Eaton Crouse-Hinds series Arktite AR receptacle, 60A,
	Three-wire, four-pole, 50-400 Hz, Style 2, Copper-free aluminum,
Product Type	Spring door, 600 Vac/250 Vdc 60A 3W4P Arkte RCPT Hous SPDR
Special Features	Watertight, Grounding Style 2, NEMA 4 Enclosure, Reverse
Special Features	Interior
Manufacturer Information	
Brand	Eaton
GTIN	00782274062709
Manufacturers Part Number	AR642
UPC	782274062709



standard

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	egories
Category Description	Pin & Sleeve Devices
Туре	RECEPTACLE
Packaging	
Carton	1
Weight Per each	2.7
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Power Distribution and Control

UL 514, UL 1010, UL 1682, CSA C22.2