

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Temperature Rating

BIBD2503FX 250-10, 2-Sided, Uni-Tap $Burndy \ LLC$

Catalog Number	BIBD2503FX
Manufacturer	Burndy LLC
Description	Aluminum Unitap, Double Sided Entry, #10-250 Class B & C , #10-3/0 Class G, H, I, K, Dlo, 3 Port
Weight per unit	0.3900 (lbs/each)
Product Category	Large Terminals & Connectors
eatures	
Conductor Size	10 AWG-250 KCMIL
Material	Aluminum
escriptions	
Description	250-10, 2-SIDED, UNI-TAP
extra long description	BUR BIBD2503FX 250-10, 2-SIDED, 3-P
Long Description	Aluminum UNITAP, Double Sided Entry, #10-250 Class B & C ,#10-3/0 Class G,H,I,K, DLO, 3 PORT
Product Type	RUN/TAP
Special Features	Features: Clear Plastisol covered AL6061-T6 aluminum body, Saves time, lowers installation costs, eliminates taping, Oxide inhibitor pre-installed, Inhibits moisture and contaminants from entering the contact area
anufacturer Information	
Brand	Burndy LLC
GTIN	00621945438996
Manufacturers Part Number	BIBD2503FX
UPC	621945438996
exonomies, Classifications, and C	Categories
Category Description	TERMINAL BLOCK ACESSORIES
Type	BIBD, Multi-Port
nckaging Carton	1
Package	24
Weight Per each	0.39
ses, Certifications, and Standard	
Application	Tap connections and in-line splice/reductions are made quickly and easily with the UNITAP™ line of connectors
standard	UL 486A-486B

194