

Class CC, Type M and Class G Fuse Blocks

BC Series



Specifications

Description: Class CC fuse blocks for use with Class CC fuses (Bussmann LP-CC, KTK-R, and FNQ-R).

Dimensions: See Data Sheet 1105

Poles: 1 to 3

Ratings:

Volts: — 600V
Amps: — 1/0-30A
SCCR:— 200kA RMS Sym.

Agency Information: CE, UL Listed (Guide IZLT, File E14853), CSA (Class 6225-01, File 47235)

Flammability Rating: UL 94V0

DIN-Rail Adapters: See page 413 for DRA-1 & DRA-2

Catalog Numbers

| Screw | Terminal Type | | | | Poles |
|---------|---------------------------|----------------|----------------------------------|---------|-------|
| | Screw with Quick Connect* | Pressure Plate | Pressure Plate w/ Quick Connect* | Box Lug | |
| BC6031S | BC6031SQ | BC6031P | BC6031PQ | BC6031B | 1 |
| BC6032S | BC6032SQ | BC6032P | BC6032PQ | BC6032B | 2 |
| BC6033S | BC6033SQ | BC6033P | BC6033PQ | BC6033B | 3 |

Data Sheet: 1105

BCCM Series

Description: 3-pole fuse block for use with (2) Class CC fuses and (1) 1/2" x 1 1/2" fuse

Catalog Numbers

| Catalog Numbers | Terminal Type |
|-----------------|---------------------------------|
| BCCM6033SQ | Screw with Quick-Connect* |
| BCCM6033PQ | Pressure Plate w/Quick-Connect* |

*Quick-connect terminal rated for 20A max.

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

BM Series Type M



Specifications

Description: Supplementary fuse blocks for use with any 1/2" x 1 1/2" fuses (Bussmann KTK, PVM, FNQ, FNM, BAF, PV, and AGU).

Dimensions: See Data Sheet 1104

Poles: 1 to 3

DIN-Rail Adapters: See page 413 for DRA-1 & DRA-2

Ratings:

Volts: — 600Vac/dc
Amps: — 1/0-30A
SCCR:— 10kA RMS Sym.

Agency Information: CE, UL Recognized (Guide IZLT2, File E14853), CSA (Class 6225-01, File 47235).

Flammability Rating: UL 94V0.

Catalog Numbers

| Screw with Quick Connect* | Terminal Type | | | Poles |
|---------------------------|----------------------------------|---------|--|-------|
| | Pressure Plate w/ Quick Connect* | Box Lug | | |
| BM6031SQ | BM6031PQ | BM6031B | | 1 |
| BM6032SQ | BM6032PQ | BM6032B | | 2 |
| BM6033SQ | BM6033PQ | BM6033B | | 3 |

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

Data Sheet: 1104

BG & G Series



Specifications

Description: Class G fuse blocks for use with Class G fuses (Bussmann SC).

Dimensions: See Data Sheet 1106

Poles: 1 to 3

Ratings:

Volts: — 600Vac/dc (0-20A)
— 480Vac/dc (25-60A)
Amps: — 1-60A (See Catalog Numbers table)

SCCR: — 100kA RMS Sym.

Agency Information: CE, UL Listed 35-60A (Guide IZLT, File E14853), UL Recognized 1-30A, (Guide IZLT2, File E14853), CSA (Class 6225-01, File 47235).

DIN-Rail Adapters: See page 413 for DRA-1 & DRA-2.

Catalog Numbers

| Screw with Quick Connect* | Terminal Type | | | | Amps | Poles |
|---------------------------|----------------------------------|-----------|--------------------------|-------|------|-------|
| | Pressure Plate w/ Quick Connect* | Box Lug | Box Lug w/retaining clip | | | |
| BG3011SQ | BG3011PQ | BG3011B | — | 1-15 | 1 | |
| BG3012SQ | BG3012PQ | BG3012B | — | | 2 | |
| BG3013SQ | BG3013PQ | BG3013B | — | | 3 | |
| BG3021SQ | BG3021PQ | BG3021B | — | 20 | 1 | |
| BG3022SQ | BG3022PQ | BG3022B | — | | 2 | |
| BG3023SQ | BG3023PQ | BG3023B | — | | 3 | |
| BG3031S | BG3031P | BG3031B | — | 25-30 | 1 | |
| BG3032S | BG3032P | BG3032B | — | | 2 | |
| BG3033S | BG3033P | BG3033B | — | | 3 | |
| — | — | — | G30060-1CR | 35-60 | 1 | |
| — | — | — | G30060-2CR | | 2 | |
| — | — | G30060-3C | G30060-3CR | | 3 | |

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

Data Sheet: 1106

Class CC, Type M and Class G Fuse Blocks

BC Series



Specifications

Description: Class CC fuse blocks for use with Class CC fuses (Bussmann LP-CC, KTK-R, and FNQ-R).

Dimensions: See Data Sheet 1105

Poles: 1 to 3

Ratings:

Volts: — 600V
Amps: — 1/0-30A
SCCR:— 200kA RMS Sym.

Agency Information: CE, UL Listed (Guide IZLT, File E14853), CSA (Class 6225-01, File 47235)

Flammability Rating: UL 94V0

DIN-Rail Adapters: See page 413 for DRA-1 & DRA-2

Catalog Numbers

| Screw | Terminal Type | | | | Poles |
|---------|---------------------------|----------------|----------------------------------|---------|-------|
| | Screw with Quick Connect* | Pressure Plate | Pressure Plate w/ Quick Connect* | Box Lug | |
| BC6031S | BC6031SQ | BC6031P | BC6031PQ | BC6031B | 1 |
| BC6032S | BC6032SQ | BC6032P | BC6032PQ | BC6032B | 2 |
| BC6033S | BC6033SQ | BC6033P | BC6033PQ | BC6033B | 3 |

Data Sheet: 1105

BCCM Series

Description: 3-pole fuse block for use with (2) Class CC fuses and (1) 1/2" x 1 1/2" fuse

Catalog Numbers

| Catalog Numbers | Terminal Type |
|-----------------|---------------------------------|
| BCCM6033SQ | Screw with Quick-Connect* |
| BCCM6033PQ | Pressure Plate w/Quick-Connect* |

*Quick-connect terminal rated for 20A max.

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

BM Series Type M



Specifications

Description: Supplementary fuse blocks for use with any 1/2" x 1 1/2" fuses (Bussmann KTK, PVM, FNQ, FNM, BAF, PV, and AGU).

Dimensions: See Data Sheet 1104

Poles: 1 to 3

DIN-Rail Adapters: See page 413 for DRA-1 & DRA-2

Ratings:

Volts: — 600Vac/dc
Amps: — 1/0-30A
SCCR:— 10kA RMS Sym.

Agency Information: CE, UL Recognized (Guide IZLT2, File E14853), CSA (Class 6225-01, File 47235).

Flammability Rating: UL 94V0.

Catalog Numbers

| Screw with Quick Connect* | Terminal Type | | | Poles |
|---------------------------|----------------------------------|---------|--|-------|
| | Pressure Plate w/ Quick Connect* | Box Lug | | |
| BM6031SQ | BM6031PQ | BM6031B | | 1 |
| BM6032SQ | BM6032PQ | BM6032B | | 2 |
| BM6033SQ | BM6033PQ | BM6033B | | 3 |

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

Data Sheet: 1104

BG & G Series



Specifications

Description: Class G fuse blocks for use with Class G fuses (Bussmann SC).

Dimensions: See Data Sheet 1106

Poles: 1 to 3

Ratings:

Volts: — 600Vac/dc (0-20A)
— 480Vac/dc (25-60A)
Amps: — 1-60A (See Catalog Numbers table)

SCCR: — 100kA RMS Sym.

Agency Information: CE, UL Listed 35-60A (Guide IZLT, File E14853), UL Recognized 1-30A, (Guide IZLT2, File E14853), CSA (Class 6225-01, File 47235).

DIN-Rail Adapters: See page 413 for DRA-1 & DRA-2.

Catalog Numbers

| Screw with Quick Connect* | Terminal Type | | | | Amps | Poles |
|---------------------------|----------------------------------|-----------|--------------------------|-------|------|-------|
| | Pressure Plate w/ Quick Connect* | Box Lug | Box Lug w/retaining clip | | | |
| BG3011SQ | BG3011PQ | BG3011B | — | 1-15 | 1 | |
| BG3012SQ | BG3012PQ | BG3012B | — | | 2 | |
| BG3013SQ | BG3013PQ | BG3013B | — | | 3 | |
| BG3021SQ | BG3021PQ | BG3021B | — | 20 | 1 | |
| BG3022SQ | BG3022PQ | BG3022B | — | | 2 | |
| BG3023SQ | BG3023PQ | BG3023B | — | | 3 | |
| BG3031S | BG3031P | BG3031B | — | 25-30 | 1 | |
| BG3032S | BG3032P | BG3032B | — | | 2 | |
| BG3033S | BG3033P | BG3033B | — | | 3 | |
| — | — | — | G30060-1CR | 35-60 | 1 | |
| — | — | — | G30060-2CR | | 2 | |
| — | — | G30060-3C | G30060-3CR | | 3 | |

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

Data Sheet: 1106