

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BQC220220 BQC Quad BRKR 2-20A/2P Com. Trip 120/240V 10K Eaton Corp

Eaton Corp	
Catalog Number	BQC220220
Manufacturer	Eaton Corp
Description	Eaton BR Thermal Magnetic Circuit Breaker, Type BQC 1-Inch CTL Plug-On Circuit Breaker, Includes Rejection Tab Feature, (2) Two-Pole 20 A, 10 Kaic, Four-Pole, 120/240V, BQC, Common Breaker Trip, #14-4 Awg Cu/Al, BQC, Type BR Loadcenters
Weight per unit	0.9000 (lbs/each)
Product Category	Quadplex Standard Trip Plug-In
Features	
dimensions	2.0000 IN X 3.0000 IN X 2.4000 IN
interrupt rating	10 kAIC
Poles	4
Trip Type	Common breaker trip
Voltage Rating	120/240 \/
Descriptions	
Description	BQC QUAD BRKR 2-20A/2P COM. TRIP 120/240V 10K
extra long description	ETN BQC220220 BQC Quad 2-20A/2P Com
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They are designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR thermal magnetic circuit breaker, Type BQC 1-Inch CTL plug-on circuit breaker, Includes rejection tab feature, (2) Two-Pole 20 A, 10 kAIC, Four-pole, 120/240V, BQC, Common breaker trip, #14-4 AWG Cu/AI, BQC, Type BR Loadcenters
Product Type	BQC Quad 2-20A/2P Com. Trip 120/240V 10K
Special Features	Includes Rejection Tab feature
Manufacturer Information	
Brand	Eaton
GTIN	00786676371841
Manufacturers Part Number	BQC220220
UPC	786676371841

Taxonomies, Classifications, and Categories

Category Description	Loadcenter Plug In Breakers and Accessories
Туре	Thermal magnetic circuit breakers



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	0.9
Uses, Certifications, and Standar	rds
Application	Generation - Renewable Energy - Alternative EnergyMarine
	Vessels and Equipment - Marine Vessels and Equipment -
	OtherOtherGeneration - Conventional Energy - Conventional
	EnergyDatacenters - IT Space: CI and Hyper Converged
standard	UL 489, Federal Specifications Classification W-C375