

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

BR2030 BR Duplex BRKR 1-20A/1-30A 1 Pole 120/240V 10K Non *Eaton Corp*

Catalog Number	BR2030
Manufacturer	Eaton Corp
Description	Eaton BR Thermal Magnetic Circuit Breaker, Type BR 1-Inch Plug-On Circuit Breaker, C, 120V, BR, Common Breaker Trip, #14-4 Awg Cu/Al, Q28, BR, Type BR Loadcenters
Weight per unit	0.4000 (lbs/each)
Product Category	Duplex Standard Trip Plug-In
eatures	
dimensions	3.0000 IN X 1.0000 IN X 3.0000 IN
interrupt rating	10
Poles	2
Voltage Rating	120 V
escriptions	
Description	BR DUPLEX BRKR 1-20A/1-30A 1 POLE 120/240V 10K NON
extra long description	ETN BR2030 BR Duplex 1-20A/1-30A 1P
Features	Eaton's BR circuit breakers are used in indoor and outdoor BR loadcenters, spa panels, meter breakers and sub panels. They ar designed for a wide range of applications such as high short-circuit interrupt, series rating combinations with upstream main breakers, thermal magnetic, AFCI, GFCI, equipment protection and dual function AF/GF.
Long Description	Eaton BR thermal magnetic circuit breaker, Type BR 1-Inch plug-on circuit breaker, c, 120V, BR, Common breaker trip, #14-4 AWG Cu/AI, Q28, BR, Type BR Loadcenters
Product Type	BR Duplex 1-20A/1-30A 1P 120/240V 10K
anufacturer Information	
Brand	Eaton
GTIN	00786676006606
Manufacturers Part Number	BR2030
UPC	786676006606
axonomies, Classifications, and (Categories
Category Description	Consists Description (Overal Description)
Туре	Thermal magnetic circuit breakers
ackaging	
Carton	10
Package	50
-	

0.4

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Marine Vessels and Equipment - Marine Vessels and Equipment -
	OtherOtherGeneration - Renewable Energy - Alternative
	EnergyGeneration - Conventional Energy - Conventional
	EnergyDatacenters - IT Space: CI and Hyper Converged
standard	UL 489, Federal Specifications Classification W-C375